

```

uxprdb04:root# pg savecrash
#!/sbin/sh
# @(#)B.11.31_LR
# Savecrash configuration
#
#
# SAVECRASH: Set to 0 to disable saving system crash dumps.
# SAVECRASH=1

# SAVECRASH_DIR: Directory name for system crash dumps. Note: the filesystem
# in which this directory is located should have as much free
# space as your system has RAM.
# SAVECRASH_DIR=/var/adm/crash

# CHUNK_SIZE: size of single crash image file (i.e. how big you want
# each of image.n.x, image.n.x+1, etc. to be)
# If not specified, savecrash will choose one based on the
# physical memory size of the system. Can be specified in
# bytes (b), kilobytes (k), megabytes (m), or gigabytes (g).
# The default unit is kilobytes. See savecrash(1M) -s option
# for size constraints.
# CHUNK_SIZE=

# COMPRESS: Whether you want the kernel and crash image files to be
# compressed. Compression option can be:
# 0 - don't compress
# 1 - compress
# 2 - don't care (default)
# If defaulted, savecrash will choose based on the physical
# memory size and available disk space. Compressing will
# take longer for savecrash to complete.
# COMPRESS=2

# MIN_FREE: Amount of free space remaining for non-root user after
# savecrash completes. Can be specified in bytes (b),
# kilobytes (k), megabytes (m), or gigabytes (g).
# Default value is 0, and the default unit is kilobytes.
# MIN_FREE=

# SWAP_LEVEL: Defines interaction between savecrash and swapon.
# NOSWAP - don't run swapon from savecrash.
# (DO NOT PICK THIS UNLESS FOREGRD=1, below, or
# you will not have ANY auxiliary swap enabled)
# SWAPEACH - call swapon each time savecrash finishes
# saving from each dump device (default)
# SWAPEND - call swapon when savecrash finishes saving
# from all dump devices
# SWAP_LEVEL=SWAPEACH

# FOREGRD: Set to 1 to force savecrash to run as foreground process.
# FOREGRD=

# SAVE_PART: If set to 1, Preserves file system space by only saving
# those pages that reside on dump devices that are also
# swap devices. Otherwise, will save all # pages that
# were dumped.
# SAVE_PART=1

# LOG_ONLY: If set to 1, the shutdown/panic message is logged to
# /etc/shutdownlog as usual, but the crash dump is not saved.
# LOG_ONLY=0
uxprdb04:root#

```