

[Bookmark](#)[Fixed font](#)[Go to End](#)**Doc ID:** Note:132764.1**Subject:** TNSNAMES.ORA Bequeath  
Example**Type:** BULLETIN**Status:** PUBLISHED**Content Type:** TEXT/PLAIN**Creation Date:** 17-JAN-2001**Last Revision** 18-MAR-**Date:** 2003

Example: Tnsnames.ora using Bequeath

```

Beq-Local.world =
  (DESCRIPTION =
    (ADDRESS_LIST =
      (ADDRESS =
        (PROTOCOL = BEQ)
        (PROGRAM = oracle)
        (ARGV0 = oracleORCL)
        (ARGS = '(DESCRIPTION=(LOCAL=YES)(ADDRESS=(PROTOCOL=beq)))')
      )
    )
    (CONNECT_DATA = (SID = ORCL)
  )
)

```

Where:

PROGRAM        Identifies the Oracle8i executable  
 ARGV0         Identifies the Oracle executable + service name  
 ARGS          Identifies the source of the connection (local client)

On Unix, setting ORACLE\_SID and ORACLE\_HOME within the entry is often required making the complete entry look more like this:

```

DEMO=
  (description=
    (address=
      (protocol=BEQ)
      (program=/u02/app/oracle/product/8.1.6/bin/oracle)
      (ARGV0=oracleV816)
      (ARGS='(Description=(LOCAL=YES)(ADDRESS=(PROTOCOL=BEQ)))')
      (ENVS='ORACLE_SID=V816,ORACLE_HOME=/u02/app/oracle/product/8.1.6')
    )
    (CONNECT_DATA=
      (SID=V816)
    )
  )
)

```