

Oracle® Database

Quick Installation Guide

10g Release 1 (10.1) for hp HP-UX PA-RISC (64-bit)

Part No. B10815-01

January 2004

ORACLE®

This guide describes how to quickly install Oracle Database 10g on HP-UX systems. It includes information about the following:

1. Review Information About this Guide
2. Log In to the System as root
3. Check the Hardware Requirements
4. Check the Software Requirements
5. Create Required UNIX Groups and User
6. Create Required Directories
7. Configure Kernel Parameters
8. Mount the Product Disc
9. Log In as the oracle User and Configure the oracle User's Environment
10. Install Oracle Database 10g
11. Install Products from the Oracle Database 10g Companion CD
12. What to Do Next
13. Additional Information
14. Documentation Accessibility

1 Review Information About this Guide

This guide describes how to install Oracle Database 10g using the default installation options.

Tasks Described in this Guide

The procedures in this guide describe how to:

- Configure your system to support Oracle Database 10g
- Install the Oracle Database 10g software on a local file system
- Configure a general-purpose Oracle database that uses the local file system for database file storage
- Install software from the Oracle Database 10g Companion CD which improves the performance of Oracle Database 10g on your system

Results of a Successful Installation

After you successfully install Oracle Database 10g:

- The database that you created and the default Oracle Net listener process are running on the system

- Oracle Enterprise Manager Database Control and *iSQL*Plus* are running and can be accessed using a Web browser
- A single-node version of the Oracle Cluster Synchronization Services (CSS) daemon is running and is configured to start automatically when your system boots

Tasks Not Described in this Guide

This guide does **not** describe how to complete the following tasks:

- Installing the software on a system that has an existing Oracle software installation
- Installing Oracle Cluster Ready Services (CRS) and Oracle Real Application Clusters (RAC) on a cluster
- Enabling Enterprise Manager e-mail notifications or automated backups
- Using alternative storage options such as Automatic Storage Management (ASM) or raw devices for database storage

Where to Get Additional Installation Information

For more detailed information about installing Oracle Database 10g, including information about the tasks not described in this guide, see one of the following guides:

- If you are installing the software on a single system, see the *Oracle Database Installation Guide for UNIX Systems*.
- If you are installing Oracle Real Application Clusters, see the *Oracle Real Application Clusters Installation and Configuration Guide*

This guide also describes how to install Oracle Cluster Ready Services, which is a prerequisite for RAC installations.

Both of these guides are available on the product disc. To access them, use a Web browser to open the `welcome.htm` file, either in the top-level directory of the CD-ROM or in the `db` directory on the DVD-ROM, then select the **Documentation** tab.

2 Log In to the System as root

Before you install the Oracle software, you must complete several tasks as the `root` user. To log in as the `root` user, complete one of the following procedures:

Note: You must install the software from an X windows workstation, an X terminal, or a PC or other system with X server software installed.

- If you are installing the software from an X Window System workstation or X terminal:
 1. Start a local terminal session, for example, an X terminal (`xterm`).
 2. If you are not installing the software on the local system, enter the following command to enable remote hosts to display X applications on the local X server:

```
$ xhost +
```

3. If you want to install the software on a remote system, enter a command similar to the following to connect to that system:

```
$ telnet remote_host
```

4. If you are not logged in as the `root` user, enter the following command to switch user to `root`:

```
$ su - root
password:
#
```

- If you are installing the software from a PC or other system with X server software installed:

Note: If necessary, see your X server documentation for more information about completing this procedure. Depending on the X server software that you are using, you may need to complete the tasks in a different order.

1. Start the X server software.
2. Configure the security settings of the X server software to permit remote hosts to display X applications on the local system.
3. Connect to the remote system where you want to install the software and start a terminal session on that system, for example, an X terminal (`xterm`).
4. If you are not logged in as the `root` user on the remote system, enter the following command to switch user to `root`:

```
$ su - root
password:
#
```


3 Check the Hardware Requirements

The system must meet the following minimum hardware requirements:

Requirement	Minimum Value
Physical memory (RAM)	512 MB (524288 KB)
Swap space	1 GB (1048576 KB) or twice the size of RAM On systems with 2 GB or more of RAM, the swap space can be between one and two times the size of RAM
Disk space in /tmp	400 MB (409600 KB)
Disk space for software files	3.5 GB (3670016 KB) This value includes 1 GB (1048576 KB) of disk space required to install the Oracle Database 10g Products from the Companion CD (optional, but recommended).
Disk space for database files	1.2 GB (1258290 KB)
System architecture	64-bit

To ensure that the system meets these requirements, follow these steps:

1. To determine the physical RAM size, enter the following command:

```
# /usr/sbin/dmefg | grep "Physical:"
```

If the size of the physical RAM installed in the system is less than 512 MB, you must install more memory before continuing.

2. To determine the size of the configured swap space, enter the following command:

```
# /usr/sbin/swapinfo -a
```

If necessary, see your operating system documentation for information about how to configure additional swap space.

3. To determine the amount of free disk space available in the `/tmp` directory, enter the following command:

```
# bdf /tmp
```

If there is less than 400 MB of disk space available in the `/tmp` directory, complete one of the following steps:

- Delete unnecessary files from the `/tmp` directory to achieve the required disk space.

- Set the `TEMP` and `TMPDIR` environment variables when setting the `oracle` user's environment (described later).
 - Extend the file system that contains the `/tmp` directory. If necessary, contact your system administrator for information about extending file systems.
4. To determine the amount of free disk space available on the system, enter the following command:

```
# bdf
```

This command displays the disk space usage on all mounted file systems. To complete the installation, the system must satisfy *either* of the following conditions:

- 4.7 GB (4928307 KB) of free disk space is available on two file systems: one with at least 3.5 GB (3670016 KB) free for the Oracle software and another with at least 1.2 GB free for the preconfigured database
- 4.7 GB of free disk space is available for the Oracle software and database on a single file system

Note: While installing the Oracle database on a disk drive separate from the software does provide a performance improvement, for best performance, the Oracle database files should be distributed across three or more disks. The *Oracle Database Installation Guide for UNIX Systems* describes this more complex and time-consuming type of installation. However, this type of installation is recommended only for experienced users.

5. To determine whether the system architecture is 64-bit, enter the following command:

```
# /bin/getconf KERNEL_BITS
```

This command should return the following output. If you do not see the expected output, you cannot install the software on this system.

```
64
```

4 Check the Software Requirements

The system must meet the following minimum software requirements:

- The version of HP-UX must be HP-UX 11i (11.11) PA-RISC or higher.
- HP-UX 11i Quality Pack (GOLDQPK11i), June 2003 or later must be installed.
- The following patches must be installed:
 - PHCO_28123: cumulative SAM patch
 - PHKL_29198: Psets Enablement Patch; top(1)
 - PHNE_28476: Cumulative STREAMS Patch
 - PHNE_28923: LAN product cumulative patch
 - PHSS_28871: ld(1) and linker tools cumulative patch
 - PHSS_28880: HP aC++ -AA runtime libraries (aCC A.03.50)
 - PHCO_26331: mountall cumulative patch, Dev IDs enabler
 - PHCO_29109: Pthread enhancement and fixes
 - PHKL_25468: eventport (/dev/poll) pseudo driver
 - PHKL_25842: Thread Abort

- PHKL_25993: thread nostop for NFS, rlimit, Ufalloc fix
 - PHKL_25994: Thread NOSTOP, Psets Enablement, Ufalloc
 - PHKL_25995: ufalloc;VxFS3.5;SPP fragmentation
 - PHKL_26468: Shared synchronization performance support
 - PHKL_28489: copyin EFAULT, LDCD access type
- You must install any additional recommended patches for Java SDK 1.4.2.

See the following Web site for a list of patches required by Java SDK 1.4.2:

<http://www.hp.com/products1/unix/java/patches/index.html>

To ensure that the system meets these requirements, follow these steps:

1. To determine which version of HP-UX is installed, enter the following command:

```
# uname -a
HP-UX hostname B.11.11 U 9000/800 109444686 unlimited-user
license
```

In this example, the version of HP-UX 11i is 11.11.

2. To determine whether the HP-UX 11i Quality Pack is installed, enter the following command:

```
# /usr/sbin/swlist -l bundle | grep GOLD
```

If the Quality Pack is not installed, or if the date is before June 2003, download the latest Quality Pack from the following URL and install it:

http://www.software.hp.com/SUPPORT_PLUS/qpk.html

3. To determine whether a patch is installed, enter a command similar to the following:

```
# /usr/sbin/swlist -l patch | grep PHSS_28880
```

Alternatively, to list all installed patches, enter the following command:

```
# /usr/sbin/swlist -l patch | more
```

If a required patch is not installed, download it from the following URL and install it:

<http://itresourcecenter.hp.com>

5 Create Required UNIX Groups and User

The following local UNIX groups and user must exist on the system:

- The `oinstall` group (the Oracle Inventory group)
- The `dba` group (the OSDBA group)
- The `oracle` user (the Oracle software owner)

The `oinstall` and `dba` groups and the `oracle` user may already exist on your system. To determine whether they exist already, and if necessary, to create them, follow these steps:

1. To determine whether the `oinstall` and `dba` groups exist, enter the following commands:

```
# grep oinstall /etc/group
# grep dba /etc/group
```

If the output from these commands shows the specified group name, that group already exists.

2. If necessary, enter the following commands to create the `oinstall` and `dba` groups:

```
# /usr/sbin/groupadd oinstall
# /usr/sbin/groupadd dba
```


3. To determine whether the `oracle` user exists and belongs to the correct groups, enter the following command:

```
# id oracle
```

If the `oracle` user exists, this command displays information about the groups to which the user belongs. The output should be similar to the following, indicating that `oinstall` is the primary group and `dba` is a secondary group:

```
uid=502(oracle) gid=502(oinstall) groups=502(oinstall),503(dba)
```

4. If necessary, complete one of the following actions:

- If the `oracle` user exists, but its primary group is not `oinstall` or it is not a member of the `dba` group, enter the following command:

```
# /usr/sbin/usermod -g oinstall -G dba oracle
```

- If the `oracle` user does not exist, enter the following command to create it:

```
# /usr/sbin/useradd -g oinstall -G dba oracle
```

This command creates the `oracle` user and specifies:

- `oinstall` as the primary group
- `dba` as the secondary group

5. Enter the following command to set the password of the `oracle` user:

```
# passwd oracle
```

6 Create Required Directories

Create directories with names similar to the following and specify the correct owner, group, and permissions for them:

- `/u01/app/oracle` (the Oracle base directory)
- `/u02/oradata` (an optional Oracle datafile directory)

The Oracle base directory must have 3.5 GB (3670016 KB) of free disk space, or 4.7 GB (4928307 KB) of free disk space if you choose not to create a separate Oracle datafile directory. The Oracle datafile directory must have 1.2 GB of free disk space.

Note: If you do not want to create a separate Oracle datafile directory, you can install the datafiles in a subdirectory of the Oracle base directory (not recommended for production databases).

To determine where to create these directories, follow these steps:

1. Enter the following command to display information about all mounted file systems:

```
# bdf
```

This command displays information about all of the file systems mounted on the system, including:

- The physical device name
- The total amount, used amount, and available amount of disk space, in kilobytes
- The mount point directory for that file system

2. From the display, identify either one or two file systems that meet the following requirements:

- Two file systems:

Identify one file system with 3.5 GB of free disk space, for the Oracle base directory, and another file system with 1.2 GB of free disk space for the Oracle datafile directory.

- One file system:

Identify one file system with 4.7 GB of free disk space, for both the Oracle base directory and the Oracle datafile directory.

3. Note the name of the mount point directory for each file system that you identified.

In the following examples, /u01 is the mount point directory used for the software and /u02 is the mount point directory used for the Oracle datafile directory. You must specify the appropriate mount point directories for the file systems on your system.

To create the required directories and specify the correct owner, group, and permissions for them, follow these steps:

Note: In the following procedure, replace /u01 and /u02 with the appropriate mount point directories that you identified in Step 3 previously.

1. Enter the following command to create subdirectories in the mount point directory that you identified for the Oracle base directory:

```
# mkdir -p /u01/app/oracle
```

2. If you intend to use a second file system for the Oracle database files, create an `oradata` subdirectory in the mount point directory that you identified for the Oracle datafile directory (shown as /u02 in the examples):

```
# mkdir /u02/oradata
```

3. Change the owner and group of the directories that you created to the `oracle` user and the `oinstall` group:

```
# chown -R oracle:oinstall /u01/app/oracle /u02/oradata
```

4. Change the permissions on the directories that you created to 775:

```
# chmod -R 775 /u01/app/oracle /u02/oradata
```

7 Configure Kernel Parameters

Verify that the following kernel parameters are set either to the formula shown, or to values greater than or equal to the recommended value shown:

Parameter	Recommended Formula or Value
ksi_alloc_max	(nproc*8)
max_thread_proc	256
maxdsiz	1073741824 (1 GB)
maxdsiz_64bit	2147483648 (2 GB)
maxssiz	134217728 (128 MB)
maxssiz_64bit	1073741824 (1 GB)
maxswapchunks	16384

Parameter	Recommended Formula or Value
maxuprc	$((nproc*9)/10)$
msgmap	$(2+msgmni)$
msgmni	4096
msgseg	32767
msgtql	4096
ncsize	$(ninode+vx_ncsize)$
nfile	$(15*nproc+2048)$
nflocks	4096
ninode	$(8*nproc+2048)$
nkthread	$((nproc*7)/4)+16)$
nproc	4096
semmap	$(semmni+2)$
semmni	4096
semmns	$(semmni*2)$
semmnu	$(nproc-4)$

Parameter	Recommended Formula or Value
semvmx	32767
shmmax	The size of physical memory (0X4000000) or 1073741824, whichever is greater.
shmmni	512
shmseg	120
vps_ceiling	64

To view the current value or formula specified for these kernel parameters, and to change them if necessary, follow these steps:

- Optionally, set the DISPLAY environment variable to specify the display of the local system:

- Bourne, Bash, or Korn shell:

```
$ DISPLAY=local_host:0.0 ; export DISPLAY
```

- C shell:

```
% setenv DISPLAY local_host:0.0
```


2. Start System Administration Manager (SAM):

```
# /usr/sbin/sam
```

3. Choose the **Kernel Configuration** area, then choose the **Configurable Parameters** area.
4. Check the value or formula specified for each of these parameters and, if necessary, modify that value or formula.

If necessary, see the SAM online help for more information about completing this step.

5. Exit from SAM.

If you modified the value specified for any static parameter, you must rebuild the kernel and reboot the system.

6. If necessary, when the system restarts, log in and switch user to root.

8 Mount the Product Disc

The Oracle Database 10g software is available on both CD-ROM and DVD-ROM. These discs are in ISO 9660 format with Rockridge extensions.

To mount the product disc, follow these steps:

1. If necessary, enter a command similar to following to unmount the currently mounted disc, then remove it from the drive:

```
# /usr/sbin/umount /SD_CDROM
```

In this example, /SD_CDROM is the mount point directory for the CD-ROM drive.

2. Insert the disc into the CD-ROM or DVD-ROM drive.
3. To mount the disc, enter commands similar to the following:

```
$ su - root  
# /usr/sbin/mount -F cdfs -o rr /dev/dsk/cxytydz /SD_CDROM
```

In this example, /SD_CDROM is the CD-ROM mount point directory and /dev/dsk/cxytydz is the device name for the CD-ROM device, for example /dev/dsk/c0t2d0.

9 Log In as the oracle User and Configure the oracle User's Environment

You run the Installer from the `oracle` account. However, before you start the installer you must configure the environment of the `oracle` user. To configure the environment, you must:

- Set the default file mode creation mask (`umask`) to `022` in the shell startup file.
- Set the `DISPLAY`, `ORACLE_BASE`, and `ORACLE_SID` environment variables.

To set the `oracle` user's environment, follow these steps:

1. Start another terminal session.
2. Enter the following command to ensure that X Window applications can display on this system:

```
$ xhost +
```

3. Complete one of the following steps:
 - If the terminal session is not connected to the system where you want to install the software, log in to that system as the `oracle` user.

- If the terminal session is connected to the system where you want to install the software, switch user to `oracle`:

```
$ su - oracle
```

4. To determine the default shell for the `oracle` user, enter the following command:

```
$ echo $SHELL
```

5. Open the `oracle` user's shell startup file in any text editor:

- Bourne shell (`sh`), Bash shell (`bash`), or Korn shell (`ksh`):

```
$ vi .profile
```

- C shell (`csh` or `tcsh`):

```
% vi .login
```

6. Enter or edit the following line in the shell startup file, specifying a value of `022` for the default file creation mask:

```
umask 022
```

7. Save the file and exit from the editor.

8. To run shell startup script, enter the following command:

- Bourne, Bash, or Korn shell:

```
$ . ~/.profile
```

- C shell:

```
% source ~/.login
```

9. If you determined that the `/tmp` directory had insufficient free disk space when checking the hardware requirements, enter the following commands to set the `TEMP` and `TMPDIR` environment variables. Specify a directory on a file system with sufficient free disk space.

- Bourne, Bash, or Korn shell:

```
$ TEMP=directory  
$ TMPDIR=directory  
$ export TEMP TMPDIR
```

- C shell:

```
% setenv TEMP directory  
% setenv TMPDIR directory
```

10. If you are not installing the software on the local system, enter the following command to direct X applications to display on the local system:

- Bourne, Bash, or Korn shell:

```
$ DISPLAY=local_host:0.0 ; export DISPLAY
```

- C shell:

```
% setenv DISPLAY local_host:0.0
```

In this example, *local_host* is the host name or IP address of the system you want to use to display the Installer (your workstation or PC).

11. Enter commands similar to the following to set the ORACLE_BASE and ORACLE_SID environment variables:

- Bourne, Bash, or Korn shell:

```
$ ORACLE_BASE=/u01/app/oracle  
$ ORACLE_SID=sales  
$ export ORACLE_BASE ORACLE_SID
```

- C shell:

```
% setenv ORACLE_BASE /u01/app/oracle
% setenv ORACLE_SID sales
```

In these examples, `/u01/app/oracle` is the Oracle base directory that you created earlier and `sales` is the name that you want to call the database (typically no more than five characters).

12. Enter the following commands to ensure that the `ORACLE_HOME` and `TNS_ADMIN` environment variables are not set:

- Bourne, Bash, or Korn shell:

```
$ unset ORACLE_HOME
$ unset TNS_ADMIN
```

- C shell:

```
% unsetenv ORACLE_HOME
% unsetenv TNS_ADMIN
```

13. To verify that the environment has been set correctly, enter the following commands:

```
$ umask
$ env | more
```

Verify that the `umask` command displays a value of `022` and the environment variables that you set in this section have the correct values.

10 Install Oracle Database 10g

After configuring the oracle user's environment, start the Installer and install the Oracle software, as follows:

Note: The following examples show paths to the `runInstaller` script on a CD-ROM. If you are installing the software from DVD-ROM, use a command similar to the following:

```
$ /mount_point/db/runInstaller
```

1. To start the Installer, enter the following commands:

```
$ cd /tmp  
$ /SD_CDRom/runInstaller
```

If the Installer does not appear, see the *Oracle Database Installation Guide for UNIX Systems* for information about how to troubleshoot X display problems.

2. Use the following guidelines to complete the installation:
 - The following table describes the recommended action for each Installer screen.

Note: If you have completed the tasks listed previously, you can complete the installation by choosing the default values on most screens.

- If you need more assistance, or if you want to choose an option that is not a default, click **Help** for additional information.
- If you encounter errors while installing or linking the software, see the *Oracle Database Installation Guide for UNIX Systems* for information about troubleshooting.

Screen	Recommended Action
Welcome	Click Next .
Specify Inventory Directory and Credentials	<p>Note: This screen appears only during the first installation of Oracle products on a system.</p> <p>Specify the following information, then click Next:</p> <p>Enter the full path of the inventory directory</p> <p>Verify that the path is similar to the following, where <i>oracle_base</i> is the value that you specified for the ORACLE_BASE environment variable:</p> <p><i>oracle_base/oraInventory</i></p> <p>Specify operating system group name</p> <p>Verify that the group specified is the Oracle Inventory group:</p> <p>oinstall</p>
Run orainstRoot.sh	<p>If prompted, run the following script in a separate terminal window as the <code>root</code> user:</p> <p><i>oracle_base/oraInventory/orainstRoot.sh</i></p>
Specify File Locations	<p>In the Destination section, verify that the Path value for the Oracle home directory is similar to the following, then click Next:</p> <p><i>oracle_base/product/10.1.0/db_1</i></p>

Screen	Recommended Action
Select Installation Type	Select Enterprise Edition or Standard Edition , then click Next .
Product-Specific Prerequisite Checks	<p>Verify that all of the prerequisite checks succeed, then click Next.</p> <p>The Installer checks the system to verify that it is configured correctly to run Oracle software. If you have completed all of the pre-installation steps in this guide, all of the checks should pass.</p> <p>In some circumstances, a check might fail even if you have completed all of the pre-installation steps. For example, you might have installed a later patch that obsoletes one of those listed in this guide.</p> <p>If a check fails, review the cause of the failure listed for that check on the screen. If possible, rectify the problem and rerun the check. Alternatively, if you are satisfied that your system meets the requirements, you can select the check-box for the failed check to manually verify the requirement.</p>
Select Database Configuration	Accept the default choices, then click Next .

Screen	Recommended Action
Specify Database Configuration Options	<p>Specify the following information, then click Next:</p> <p>Note: If you set the ORACLE_SID environment variable, its value is used as the default value for the global database name and SID.</p> <p>Global Database Name</p> <p>Specify a name for the database, followed by the domain name of the system:</p> <p><i>sales.your_domain.com</i></p> <p>The value that you specify, up to the first period, is also used for the SID value.</p> <p>Select Database Character Set</p> <p>Accept the default value, which is based on your system locale, or if you need to support more than one language, click Help for more information about the supported character sets.</p> <p>Create database with example schemas</p> <p>Choose this option to create the EXAMPLE tablespace that contains the Sample Schemas (optional, but recommended).</p>
Select Database Management Option	<p>Accept the default values, then click Next.</p> <p>Note: You can enable e-mail notifications after you have installed the software.</p>

Screen	Recommended Action
Specify Database File Storage Option	Select the File System option and specify the database file location, then click Next . Specify database file location: Specify the Oracle datafiles directory, if you created it: <code>/u02/oradata</code> Alternatively, accept the default location: <code>oracle_base/oradata</code>
Specify Backup and Recovery Options	Accept the default values, then click Next . Note: You can enable automated backups after you have installed the software.
Specify Database Schema Passwords	Enter and confirm passwords for all of the privileged database accounts, then click Next . Note: Oracle recommends that you specify a different password for each account. You must remember the passwords that you specify.
Summary	Review the information displayed, then click Install .
Install	The Install screen displays status information while the product is being installed.

Screen	Recommended Action
Configuration Assistants	<p>The Configuration Assistants screen displays status information for the configuration assistants that configure the software and create a database.</p> <p>After the Database Configuration Assistant finishes, click OK to continue.</p>
Setup Privileges	<p>When prompted, run the following script in a separate terminal window as the <code>root</code> user:</p> <pre data-bbox="327 377 567 397"><code>oracle_home/root.sh</code></pre> <p>In this example, <code>oracle_home</code> is the directory where you installed the software. The correct path is displayed on the screen.</p> <p>Press Return to accept the default values for each prompt displayed by the script. When the script finishes, click OK.</p>

Screen	Recommended Action
End of Installation	<p>The configuration assistants configure several Web-based applications, including Oracle Enterprise Manager Database Control. This screen displays the URLs configured for these applications. Make a note of the URLs used.</p> <p>The port numbers used in these URLs are also recorded in the following file:</p> <p><code>oracle_home/install/portlist.ini</code></p> <p>To exit from the Installer, click Exit, then click Yes.</p>

11 Install Products from the Oracle Database 10g Companion CD

The Oracle Database 10g Companion CD contains products that improve the performance of or complement Oracle Database 10g. For most installations, Oracle recommends that you install Oracle Database 10g Products from the Companion CD.

Note: If you intend to use Oracle JVM or Oracle *interMedia*, you *must* install the Oracle Database 10g Products installation type from the Companion CD. This installation optimizes the performance of those products on your system.

Products Included on the Companion CD

The Companion CD includes two sets of products:

- **Oracle Database 10g Products**

Includes Oracle Database Examples, Oracle Workflow server, natively compiled Java libraries for Oracle JVM and Oracle *interMedia*, Oracle Text supplied knowledge bases, and Legato Single Server Version (LSSV)

Note: You must install these products into the same Oracle home directory as Oracle Database 10g Release 1 (10.1.0).

- **Oracle Database 10g Companion Products**

Includes Oracle HTTP Server and Oracle HTML DB

Note: You must install Oracle HTTP Server into its own Oracle home directory. You must install Oracle HTML DB either with Oracle HTTP Server, or into an Oracle home directory that contains Oracle HTTP Server.

The following subsection describes how to install Oracle Database 10g Products. For more information about the products on the Companion CD, and for more detailed information about installing them, see the *Oracle Database Companion CD Installation Guide* which is located on the Companion CD.

Installing Oracle Database 10g Products

To install Oracle Database 10g Products, follow these steps:

1. As the `root` user, mount the Oracle Database 10g Companion CD CD-ROM or the Oracle Database 10g DVD-ROM.

For more information about mounting discs, see Section 8, "Mount the Product Disc" on page 26.

2. If necessary, log in as the Oracle software owner user that you used to install Oracle Database 10g (typically `oracle`).

3. Enter a command similar to the following to start the Installer:

- CD-ROM installations:

```
$ /mount_point/runInstaller
```

- DVD-ROM installations:

```
$ /mount_point/companion/runInstaller
```

The following table describes the recommended action for each Installer screen:

Screen	Recommended Action
Welcome	Click Next .
Specify File Locations	In the Destination section, select the Name or Path value that specifies the Oracle home directory where you installed Oracle Database 10g, then click Next . The default Oracle home path is similar to the following: <i>oracle_base/product/10.1.0/db_1</i>
Select a Product to Install	Select Oracle Database 10g Products , then click Next .

Screen	Recommended Action
Summary	Review the information displayed, then click Install .
Install	The Install screen displays status information while the product is being installed.
Setup Privileges	<p>When prompted, run the following script in a separate terminal window as the <code>root</code> user:</p> <pre><i>oracle_home</i>/root.sh</pre> <p>In this example, <i>oracle_home</i> is the directory where you installed the software. The correct path is displayed on the screen.</p> <p>Note: Unless you want to install Legato Single Server Version, enter 3 to quit the installation of LSSV.</p> <p>When the script finishes, click OK.</p>
End of Installation	To exit from the Installer, click Exit , then click Yes .

12 What to Do Next

To become familiar with this release of Oracle Database, Oracle suggests that you complete the following tasks:

- Log into Oracle Enterprise Manager Database Control using a Web browser.

Oracle Enterprise Manager Database Control is a Web-based application that you can use to manage a single Oracle database. The default URL for Database Control is:

```
http://host.domain:5500/em/
```

To log in, use the user name SYS and connect as SYSDBA. Use the password that you specified for this user during the Oracle Database 10g installation.

- See Chapter 4 of the *Oracle Database Installation Guide for UNIX Systems* for information about required and optional post-installation tasks, depending on the products that you want to use.
- Review Chapter 5 in the *Oracle Database Installation Guide for UNIX Systems* for information about how to use Database Control to learn about the configuration of your installed database.

- Read the *Oracle Database 2 Day DBA* guide, to learn more about using Oracle Enterprise Manager Database Control to administer a database.

This guide, designed for new Oracle DBAs, describes how to use Database Control to manage all aspects of an Oracle database installation. It also provides information about how to enable e-mail notifications and automated backups, which you might not have configured during the installation.

13 Additional Information

This section contains information about the following:

- Product Licenses
- Purchasing Licenses, Version Updates, and Documentation
- Contacting Oracle Support Services
- Locating Product Documentation

Product Licenses

You are welcome to install and evaluate the products included in this media pack for 30 days under the terms of the Trial License

Agreement. However, you must purchase a program license if you want to continue using any product after the 30 day evaluation period. See the following section for information about purchasing program licenses.

Purchasing Licenses, Version Updates, and Documentation

You can purchase program licenses, updated versions of Oracle products, and printed versions of Oracle documentation from the Oracle Store Web site:

<http://oraclestore.oracle.com/>

Contacting Oracle Support Services

If you have purchased Oracle Product Support, you can call Oracle Support Services for assistance 24 hours a day, seven days a week. For information about purchasing Oracle Product Support or contacting Oracle Support Services, go to the Oracle Support Services Web site:

<http://www.oracle.com/support/>

Locating Product Documentation

Documentation for Oracle products is available in both HTML and Adobe portable document format (PDF) formats from several locations:

- On discs in the media pack:
 - Platform-specific documentation is available on the product discs. To access the documentation, see the `welcome.htm` file located in the top-level directory of the CD-ROM or DVD-ROM.
 - Generic product documentation is available on the Oracle Documentation Library CD-ROM and on the DVD-ROM.
- From the Oracle Technology Network Web site:

<http://otn.oracle.com/documentation/>

To view PDF documents, download the free Adobe Acrobat Reader from the Adobe Web site, if necessary:

<http://www.adobe.com/>

14 Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For additional information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Code Examples in Documentation

JAWS, a Windows screen reader, may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, JAWS may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Support for Hearing and Speech Impaired Customers

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week:

- For technical questions, call 1.800.446.2398
- For non-technical questions, call 1.800.464.233

Copyright © 1996, 2004, Oracle.
All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

