

Chapter 8

-

Ignite-UX

INDEX

Overview	4
Obtaining Ignite-UX	4
Application CD-ROM/DVD	5
HP-UX 11i Core OS CD/DVD 1	5
WWW to HP's Software Depot	5
FTP to HP's Software Depot	5
Ignite-UX Mailing Lists	5
Ignite-UX Updates	5
Ignite-UX FAQs	5
Installing Ignite-UX	6
Installing Ignite-UX Bundles Downloaded from the Net	6
Installing Ignite-UX from Application CD	6
Installing Ignite-UX from HP-UX 11i CoreOS CD1	7
Configuring the Ignite-UX Server	7
Starting Ignite-UX	7
Configuring the Ignite-UX Server	7
Configuring the Ignite-UX Server for Itanium clients	9
Using bootpd method:	9
Using the instl_bootd method:	10
Setting up a Boot Helper	12
Useful Tips Based on Practical Experience	13
Ignite-UX System Recovery Tools - Limitations	15
Ignite-UX System Recovery Tools - make_recovery	16
Ignite-UX System Recovery Tools - make_tape_recovery	16
Overview	16
Creating a make_tape_recovery Tape - Ignite-UX Server GUI	16
Creating a make_tape_recovery tape - Command Line Examples	17
Verifying the make_tape_recovery Tape	19
Restoring from a make_tape_recovery Tape	20
Restoring from a make_tape_recovery Tape on Itaniums systems	21
Ignite-UX System Recovery Tools - make_net_recovery	21
Overview	21
Large File Support for Archives Greater than 2GB	22
Archive Configuration Policies	22
Exporting the archive directory	23
Creating a make_net_recovery Archive - Ignite-UX Server GUI	23
Creating a make_net_recovery Archive - Command Line Examples	24
Verifying the Network Recovery Archive	25
Restoring from the Network Recovery Archive	26
Creating a Bootable Recovery Tape with a make_net_recovery Archive	26
Recovering Mirrored Disks after Installation with Ignite-UX	27
Creating SD-UX and non-SD-UX Software Depots	28
Creating an HP-UX Core-OS Depot	28
Creating a Support Plus Patch Bundle Depot	29

Creating an Individual Patch Depot.....	29
Special Handling of Patch, ACE and HWE Installations	30
Creating an Application Depot	31
Creating non-SD-UX Depots.....	31
Creating Ignite-UX Config Files for SD-UX and non-SD-UX Depots.....	31
Managing the INDEX File.....	32
Modifying/Adding Depots.....	33
Example 1 - Creating SD-UX Depots for an HP-UX 11.00 Installation.....	33
Example 2 - Creating a CD-ROM SD-UX Depot	34
Booting and Installing an HP-UX Client	35
Booting the Client from the Ignite-UX Server - Using the User Interface.....	36
Booting the Client from the Ignite-UX Server - Using the bootsys Command.....	36
Booting the Itanium and PA-RISC Clients from the Network	37
Booting the Client using make_boot_tape.....	39
Performing a non-interactive Ignite-UX Installation	39
Cloning with Golden System Images	40
Creating a Golden System Image	40
Creating a Bootable Golden System Image Tape.....	42
Creating a Bootable Golden System Image CD-ROM.....	44
Additional information	48

Overview

Ignite-UX

- is an installation tool for HP-UX systems. The Ignite-UX clients can be installed from software depots containing the Core OS, patches and applications, or from archived “images”. These depots do not necessarily need to be placed onto the Ignite-UX server; any NFS-capable system can be used as the depot server;
- can be used for cloning systems. A so-called Golden System Image will be created from pre-configured source systems. This Golden System Image contains the configuration of the source system, but target specific information like the network configuration and log files will be exchanged. As a prerequisite, the systems must be nearly identical regarding the hardware setup. Additionally, the installed software must be compatible for both systems;
- can use post load scripts to further customize your system;
- can be used to create your own installation media. You can create bootable tapes and CD-/DVD-ROMs;
- can be used to archive and recover the root volume group (vg00). With `make_tape_recovery` and `make_net_recovery` volume groups (VGs) other than the root volume group can be recovered as well. However, under normal circumstances, these VGs should be backed up using proper backup tools, for example `fbackup`. Do not put Ignite-UX with “backup” and “restore” in one sentence. Ignite-UX is no considered for data backup, but rather for system recovery!
- is free of charge.

All necessary information like the Administration Guide, Release Notes, FAQs, etc. can be found at <http://www.software.hp.com/products/IUX>. There are also documents to be found in `/opt/ignite/share/doc`.

Obtaining Ignite-UX

For an Ignite-UX server running HP-UX 11.0, 11i, 11iv2 (11.23) obtain Ignite-UX version C.x (as of this writing C.6.0.x is the current version). An Ignite-UX C.x server can install HP-UX 11.x OS and applications on Ignite-UX clients.

For an Ignite-UX server running HP-UX 10.x, obtain Ignite-UX version A.x. An Ignite-UX A.x server can only install HP-UX 10.x clients. The latest version is A.3.7. It is not available on the web anymore; you have to scan through older Application or CoreOS CDs (2002 and earlier)

Ignite-UX is available from these sources in standard Software Distributor (SD) depot format:

Application CD-ROM/DVD

This CD is supplied with HP-UX OS media.

HP-UX 11i Core OS CD/DVD 1

The Core OS CD already contains the "HP-UX Installation Utilities".

WWW to HP's Software Depot

The software depot is located at <http://www.software.hp.com/products/IUX/download.html>.

You may download one or more of the individual Ignite-UX bundles or choose the entire product.

Example: Your Ignite-UX server is running HP-UX 11.00; your Ignite-UX clients run HP-UX 11.00 and 11.i. You will have to download the Ignite-UX C-version selecting both bundles for "HP-UX 11.00" and "HP-UX 11i version 1.0 (B.11.11)". Or you can choose to download "All 4 bundles".

FTP to HP's Software Depot

The FTP depot does not seem to be updated anymore; the last files are from 2002.

```
# /usr/bin/ftp www.software.hp.com
login: anonymous
passwd: email_address
ftp> cd /dist/swdepot
ftp> bin
ftp> get file_name.tar
```

file_name choices for 11.0/11i server/systems: ignite11_11.00.tar, ignite11_ALL.tar

Ignite-UX Mailing Lists

Ignite-UX Updates

To receive a email when a new version of Ignite-UX is available, write an email to: majordomo@hpfcfn.fc.hp.com with following content:

```
subscribe ignite-ux-notify
your_email_address
end
```

Ignite-UX FAQs

Write an empty email to:
iux_faq@igniteux.fc.hp.com

Installing Ignite-UX

Installing Ignite-UX Bundles Downloaded from the Net

```
# /usr/sbin/swinstall -s <full path of downloaded file> \*
```

Example: ignite11_all.tar downloaded to /var/tmp

```
# /usr/sbin/swinstall -s /var/tmp/ignite_all.tar \*
```

NOTE: NetInstall is an obsolete application and should not be found on any currently supported installation of HP-UX. This note is “just in case”.

Ignite-UX is a replacement for the Net-Install product. If your server contains the Net-Install bundle (HPUX-Install product), Ignite-UX will require that the NetInstall bundle be removed (using `swremove`), or that you touch the file `/tmp/okay_to_remove_net_install` before loading Ignite-UX, in which case loading Ignite-UX will automatically remove the NetInstall software. Otherwise loading any of the Ignite-UX software bundles will give an error.

Installing Ignite-UX from Application CD

Look for the required device file for your CD-ROM. If the mount point does not exist, create it with `mkdir`. Then mount the Applications CD to `/SD_CDROM`.

```
# /usr/sbin/ioscan -fnC disk
```

```
Class I H/W Path Driver S/W State H/W Type Description
=====
disk 0 8/4.5.0 sdisk CLAIMED DEVICE SEAGATE ST32171W
      /dev/dsk/c0t5d0 /dev/rdisk/c0t5d0
disk 1 8/4.6.0 sdisk CLAIMED DEVICE SEAGATE ST34371W
      /dev/dsk/c0t6d0 /dev/rdisk/c0t6d0
disk 2 8/16/5.2.0 sdisk CLAIMED DEVICE TOSHIBA CD-ROM XM-5401TA
      /dev/dsk/c1t2d0 /dev/rdisk/c1t2d0
```

```
# /usr/bin/mkdir /SD_CDROM
```

```
# /usr/sbin/mount /dev/dsk/c1t2d0 /SD_CDROM
```

To find out which bundles and filesets are available for installation, you can use:

```
# /usr/bin/ls /SD_CDROM
```

Then either select the whole bundle for installation with:

```
# /usr/sbin/swinstall -s /SD_CDROM B5725AA
```

Or for example if you only want to load the filesets for installing HP-UX 11.00 and 11.i Ignite-UX clients:

```
# /usr/sbin/swinstall -s /SD_CDROM Ignite-UX-11-00
```

```
# /usr/sbin/swinstall -s /SD_CDROM Ignite-UX-11-11
```

Installing Ignite-UX from HP-UX 11i CoreOS CD1

To install Ignite-UX, you need to mark one of the Ignite-UX filesets or the complete bundle B5725AA for installation in the software tab after choosing the Advanced Installation screen.

Configuring the Ignite-UX Server

Starting Ignite-UX

The search path `/opt/ignite/bin` has been added to `/etc/PATH` during the installation. To update your current `PATH` variable source `/etc/PATH` use:

```
# . ./etc/PATH
```

or simply login again. To startup Ignite-UX:

```
# /opt/ignite/bin/ignite
```

If the error message occurs stating the Ignite-UX server not being set up as an NFS server, start NFS with:

```
# /usr/bin/vi /etc/rc.config.d/nfsconf
```

```
NFS_SERVER=1  
NFS_CLIENT=1
```

```
# /sbin/init.d/nfs.server start  
# /sbin/init.d/nfs.client start
```

Look up if the `/etc/exports` file already has following entry:

```
/var/opt/ignite/clients -anon=2
```

Then export the directories with:

```
# /usr/sbin/exportfs -av
```

Configuring the Ignite-UX Server

Either follow the `<Tutorial/Server Setup>` or step out of the tutorial choosing `<Do not show this screen again>` and `<OK>`. Then choose the quick setup selecting `<Options>` `<Server Configuration...>` from the Ignite-UX screen. The following describes the quick setup.

Server options:

- Select the `<Default Configuration>` box and highlight the Operating System you want to use from the list. When doing a client installation, this configuration will be installed on targets if no other is specified. The default setting can be overridden on a per-client basis by Ignite-UX.
- Click on the `<Default Printer>` list to display the available (configured) printers. Select the one you want to use. If needed, use SAM's `<Default Printer>` area to configure a new printer onto the system. This will be the printer for printing the

manifest or installation history. The printer address will be checked by Ignite-UX before a job is sent.

- Select the appropriate `<Client Timeout (minutes)>` time, or choose `<off>`, to set the time limit for the client to be connected without responding. This will set a limit on the time since the client install log has been written in. Some points in the installation may require 15 to 30 minutes. A warning note will be displayed if this time is exceeded. Setting Client Timeout to `<off>` disables this notification.
- Use the `<Run client installation UI on>` list to designate where you want to see the client User Interface for this installation. If you have a server configured, you can have the choice of running the client installation interface from either the `<target>` (as a Terminal User Interface) or the Ignite-UX `<server>` (as the ignite screen). If the client installation is to be non-interactive (no interface), select `<none>`. The default location for the interface display is the Ignite-UX `<server>`.
- At `<Configure Booting IP Addresses...>` enter IP addresses that have **not** been assigned to a client or reserve the IP of an Ignite-UX client to its LLA address (MAC address). Ignite-UX uses these IP's temporarily to boot clients. If you reserved an IP, only the client with the corresponding MAC address can be booted with this IP. You also can edit the `/etc/opt/ignite/instl_boottab` file manually (for more help see the file itself):

```
# /usr/bin/vi /etc/opt/ignite/instl_boottab
15.1.53.180
15.1.53.181:0x08000969DE78::reserve
```

As an alternative, you can also use the `/etc/bootptab` or DHCP for assigning temporary boot IP's (Do not use DHCP unless you are very familiar with it).

Example `/etc/bootptab` entry for an Ignite-UX client:

```
sysname:\
hn:\
vm=rfc1048:\
ht=ether:\
ha=080009352575:\
ip=15.1.51.82:\
sm=255.255.248.0:\
bf=/opt/ignite/boot/boot_lif
```

Session options:

- `<Confirm New Clients>` controls the appearance of a dialog screen each time a new client is booted from the Ignite-UX server.
- `<Ask for customer information during client installation>`: select this to see the form for `<Customer Name, " System Serial #, and Order Number>` when installing clients.
- `<Show the welcome screen for the install server>`: select this to automatically display the Ignite-UX server Welcome screen. This is a useful default if many new operators run Ignite-UX.
- `<Halt the client after installation>`: select this to cause the client system to

halt (rather than reboot) after installation.

- <Automatically move completed clients to history>: select this button to automatically add completed clients to the end of the history log, `/var/opt/ignite/clients/history/history.log`. It will also move their config and manifest files to history for future reference. The client icon will be removed from the client-server screen. The client must be complete (fully installed) for this to take place.

Configuring the Ignite-UX Server for Itanium clients

Itanium systems lack the ability to boot directly from the Ignite-UX server. On PA-RISC systems you can specify the LAN address of the Ignite-UX server in the boot command “`boot lan.<IP> install`”. This is not possible on Itanium, where the “`lanboot`” command on the EFI shell will send a DHCP/BOOTP broadcast into the subnet, choosing the server, which answers first. There are two mutually exclusive options available to configure the Ignite-UX server for Itanium clients:

- In HP-UX 11.23, the `bootpd` server has been modified so that it is possible to configure `bootpd` to respond to anonymous Itanium clients
- In Ignite-UX 4.2, the Ignite `instl_bootpd` server has been modified so that it will respond to anonymous Itanium clients

Use `bootpd` method, if:

- Ignite-UX server is running HP-UX 11.23 or greater
- Any release of Ignite-UX is installed
- `bootpd` is being used, e.g. this machine is a DHCP/BOOTP server
- Manual configuration of files is ok (`/etc/dhcptab`)

Use `instl_bootpd` method, if:

- The Ignite-UX server is running any OS release
- Ignite-UX 4.2 (or greater) is installed
- `bootpd` is not being used on this machine
- You would like to use the same method (screens, setup, etc.) for Itanium and PA-RISC clients
- Manual configuration of files is not desired (do not want to manually change `/etc/dhcptab`)

Using `bootpd` method:

To use this feature, set up an entry similar to the following in `/etc/dhcptab`:

```
dhcp_device_group:\
  re:\
  ncid:\
  class-id="PXEClient:Arch:00002:.*":\
  lease-time=300:\
  subnet-mask=255.255.255.0:\
```

```
addr-pool-start-address=192.168.1.10:\
addr-pool-last-address=192.168.1.20:\
bf=/opt/ignite/boot/nbp.efi
```

The following is a brief explanation for each of the parts of the description above as well as what areas to customize:

subnet-mask	the subnet mask of your Itanium client
addr-pool-*	starting and ending IP addresses to allocate
ba:	broadcast the response
bf=	boot file for network bootstrap loader
class-id	00002 stands for Itanium, 00000 would be x86

Restart the bootpd daemon

Note: Prior to release 4.2 there were problems with the class-id and bootpd recognizing it, see the customer viewable document KBNL00000383 in K-Mine.

Using the instl_bootd method:

- instl_bootd daemon is used by Ignite-UX to boot PA-RISC clients
- configure instl_bootd using the Options:Server Configuration screen
- configuration file is /etc/opt/ignite/instl_bootptab
- instl_bootd daemon normally runs on ports 1067/1068 (unique) used only for booting PA-RISC clients
- Ignite 4.2 and later: instl_bootd has been enhanced to respond to Itanium clients on standard BOOTP network ports 67/68
- in /etc/inetd.conf:
- comment out:
boots dgram udp wait root /usr/sbin/bootpd bootpd
- add:
boots dgram udp wait root /opt/ignite/sbin/instl_bootd instl_bootd
- Restart inetd

The following are some example steps that have been used to allow an Itanium system to boot from a PA-RISC system:

1) The following entry was added into in /etc/bootptab:

```
iatest:\
  bf=/opt/ignite/boot/nbp.efi:\
  hn:\
  vm=rfc1048:\
  ht=ether:\
  ha=00306e100b32:\
  ip=15.1.51.252:\
  sm=255.255.248.0
```

iatest	replace this with the hostname of your Itanium system.
ha=00306e100b32	replace this with the MAC address of your Itanium system.
ip=15.1.51.252	replace this with the IP address of your Itanium system.
sm=255.255.248.0	replace this with the subnet mask of your Itanium system.

```

hn:                tells bootpd to pass back the hostname to the client, leave as is.
vm=rfc1048         vendor magic cookie, leave as is.
ht=ether           hardware type is Ethernet.

```

For consistency if it was required that PA-RISC systems boot using bootp as well the boot file would be given as:

```

        bf=boot_lif:\
        hd=/opt/ignite/boot:\
or
        bf=/opt/ignite/boot/boot_lif:\

```

This would allow a PA-RISC system to boot using bootp as well (note that this would preclude the use of the install option to boot lan from the boot console handler).

A `/etc/bootptab` entry is required for each MAC address.

Troubleshooting checklist for Itanium boot situations with `/etc/bootptab`

In setting up an `/etc/bootptab` configuration, there are several places where things can go wrong. Following is a typical error that indicates that the client was unable to boot from the server:

```

Shell> lanboot

Running LoadFile()

CLIENT MAC ADDR: 00 30 6E 10 0B 32

PXE-E16: Valid PXE offer not received.
Exit status code: Invalid Parameter

```

If this error occurs, following is a checklist that can be used to help troubleshoot the problem:

1) Check `inetd`

- Check `/etc/inetd.conf` to make certain "bootps" and "tftp" entries have been uncommented. Make certain the "tftp" line contains `/opt/ignite` and `/var/opt/ignite` paths on the tftp line.
- Was `inetd` restarted or given an option to re-read the configuration files (`inetd -c`), after they were edited? Is the `inetd` process running?
- Check for entries in `/var/adm/inetd.sec` that may cause `inetd` to deny service to certain clients.
- Check `/var/adm/syslog/syslog.log` to make certain `inetd` was restarted, and that no bad messages are found. Check for messages from "bootpd" and "tftpd"

2) Check `bootpd`

- Check the `/etc/bootptab` entry. Make certain the MAC address matches the client MAC address. Use `"dhcptools -v"` to validate the format of the `/etc/bootptab` file.
- Check for entries in `/etc/dhcpdeny` to insure that `bootpd` is not set up to deny service

for particular clients.

- Check `/var/adm/syslog/syslog.log` for a message from `bootpd` that indicates it was started when a `bootpd` packet was received.
- If packets were not received, use a tool such as `tcpdump` to check for network packets. Verify that `bootp` packets are being seen by the system.
- Find out if there are other systems on the network that may also be replying to the booting client system.
- If the system booting is on a different subnet to the `bootp` server ensure that any router in between allows the forwarding of `bootp` requests (this is router specific on how it would be configured).

3) Check `tftpd`

- Check the `tftp` line in `/etc/inetd.conf` to make certain `/opt/ignite` and `/var/opt/ignite` directories are listed.
- Check the `tftpd` connection manually by using the "`tftp`" command, for example:

```
$ tftp <server-name>
tftp> get /opt/ignite/boot/nbp.efi /tmp/nbp.efi
Received n bytes in s seconds
tftp> quit
```

Caveats: Because the Itanium client sends a broadcast no other DHCP servers should be in the same subnet as the Ignite-UX server and the client. Other DHCP servers may answer faster than the Ignite-UX client, leading to failed installation attempts.

Setting up a Boot Helper

If the client is not in the same subnet as the Ignite-UX server and the clients need to be booted from the network (the client is currently not running HP-UX 9.x or later), a boot helper needs to be installed. The boot helper must be on a HP-UX system within the subnet of the Ignite-UX client.

Note: For setting up a boot helper on 9.x systems, please refer to the Ignite-UX Admin Guide.

Example: The `ignite11_all.tar` fileset was downloaded to `/var/tmp` on the Ignite-UX server.

```
# /usr/sbin/swinstall -s <Ignite_Server_IP>:/var/tmp/ignite11_all.tar \
  Ignite-UX.MinimumRuntime
# /opt/ignite/bin/instl_adm -t <Ignite_Server_IP>
# /opt/ignite/bin/instl_adm -g <Gateway_to_Ignite_Server>
```

Check your settings with:

```
# /opt/ignite/bin/instl_adm -d
```

Now, edit the `/etc/opt/ignite/instl_boottab` or `/etc/bootptab` on the boot helper to assign IP addresses that have **NOT** been assigned to a client or reserve the IP of an Ignite-UX client to its LLA address (MAC address). Please see also "*Configuring the Ignite-UX Server*".

Remember to configure the boot helper for Itanium clients, if required (see chapter before).

Useful Tips Based on Practical Experience

- Everything has to be executed as the root user. The `umask(1)` must be set to `umask 022`, so every user can read the ignite-UX config files. If these config files are not "world readable", the client boot will stop with an `tftp` error.
- It is strongly recommended to use the standard directories `/var/opt/ignite/data/Rel_B.xx.yy` for your own config files. If other directories are used, they have to be exported via `tftp` and NFS.
- An up-to-date `tar`, `pax`, `bootp`, `tftp`, NFS, ARPA and LVM patch level should be installed as well on the Ignite-UX server as well as on the client system. For all needed patches please look up the latest Release Notes at <http://www.software.hp.com/products/IUX/docs.html>, chapter "Required Patches" in the latest Release Notes at <http://www.software.hp.com/products/IUX/docs.html>.
- The most problematic when installing from network is permission and network protocol errors. Before installing the client, you should check `tftp`, `inet`, NFS, etc. The `/var/adm/syslog/syslog.log` can be very useful regarding this issue. Check the `/etc/exportfs` and `/etc/inetd.conf` for correct settings. Often the `/etc/exports` file states `anon=-2` instead of `-anon=2`

```
# /usr/bin/vi /etc/exports
/var/opt/ignite/clients -anon=2
```

- When changing config files, you should always check them with:

```
# /opt/ignite/bin/instl_adm -T
```

Also check the network settings with:

```
# /opt/ignite/bin/instl_adm -d
```

- When creating a Golden System Image, make sure that the source system does not have the LLA (MAC address) of the network interface set explicitly. Otherwise, the same LLA will be used by the cloned target system. The LLA is set in the section `HP_BASE100_STATION_ADDRESS` in `/etc/rc.config.d/hpbase100conf`.
- If an installation via `boot_sys` fails or you have accidentally booted a client:

- 1) Stop the boot process and boot into Single User Mode:

```
BOOT ADMIN> boot pri isl -> Interact with IPL? -> n
```

- 2) Boot the hpux kernel:

```
ISL> hpux (;0)/stand/vmunix
```

- 3) Correct the AUTO file

```
# /usr/sbin/mkboot -a "hpux" /dev/rdisk/c0t1d0
```

If the old HP-UX system has already been overwritten via Ignite-UX, you have to boot the system over the network.

- If you have problems booting from a boot server, try following:

```
BOOT ADMIN> boot lan INSTALL -> Interact with IPL? -> y
You now can see which server wrongly answers the boot request. Or do a
# /usr/bin/tail /var/adm/syslog/syslog.log
on the Ignite-UX server to see if maybe there isn't any unassigned IP available for the
client.
```

- If you are using different DDS drives for backup and recovery, you should always use a DDS1 device file for creating a tape. Using the DDS1 device file makes the tape compatible with other DDS tape drives. Creating a DDS1 device file:

1) Look up the hardware path

```
# /usr/sbin/ioscan -fC tape

Class I H/W Path Driver S/W State H/W Type Description
=====
tape 0 8/16/5.6.0 stape CLAIMED DEVICE HP C1533A
```

2) Create the device file

```
# /usr/sbin/mksf -v -H 8/16/5.6.0 -b DDS1 -n -a
```

This will create the device file, `/dev/rmt/clt6d0DDS1n`, for example.

- If you can't boot the client either from hard disk or from network, you can create a bootable tape which will then contact the next available Ignite-UX server.

a) using `make_medialif`

```
# /opt/ignite/bin/make_medialif -m -l /tmp/helper.lif
# /usr/bin/dd if=/tmp/helper.lif of=/dev/rmt/clt6d0DDS1n obs=2k
```

Note: Use a DDS1 device and blocksize of 2k as well as check that the correct Ignite-UX server IP is set with `# /opt/ignite/bin/instl_adm -d !`

b) using `make_boot_tape`

```
# /opt/ignite/bin/instl_adm -d > tmp_config_file
```

Edit the `tmp_config_file` as appropriate. Then create the bootable tape:

```
# /opt/ignite/bin/make_boot_tape -f tmp_config_file -v \
-d /dev/rmt/clt6d0DDS1n
```

- Ignite-UX does not set the maximal physical extents (Max PE per PV) correspondingly high enough to implement larger hard disk into the VG. These parameters can be set on the Ignite-UX server.

Note: The maximum physical extents of a boot disk is 5628. You have to increase the PE size for larger hard disks.

- You can also write a golden system image onto tape if you have space problems:

```
# /opt/ignite/data/scripts/make_sys_image -d /dev/rmt/0m -s local
```

- When using `make_sys_image`, important system files are temporarily replaced which leads to intensive disruptions on a productive system, among other things, the name resolution, login, etc. Therefore, if you run `make_sys_image`, the system should never be in use by other applications!!!
- If a `make_sys_image` was disrupted e.g. with `# kill -9, # shutdown, etc.`, then among other things the `/etc/hosts` and the transition links may have also been removed. To recover from missing transition links, do the following in the multi-user run level:

```
# /sbin/pax -r -pe -f /tmp/ign_configure/keepsafe  
# /opt/upgrade/bin/tlinstall
```

Ignite-UX System Recovery Tools - Limitations

Logical Volume Physical Extent Allocation Not Preserved:

The LVM physical extents allocated to a logical volume may be in a different location on the disk than before. The recovery tools use a very specific and complex algorithm for extending logical volumes to ensure success (such as extending contiguous volumes before non- contiguous).

VxVM disk groups is not included in earlier Ignite versions:

Up to Ignite-UX version B.3.7, the disk groups managed by VERITAS Volume Manager (VxVM) cannot be included in the Ignite-UX archive. If they are included, an error will occur. Those disk groups will be left undisturbed and re-integrated to the system after the recovery is complete.

LVM Disk Mirrors not restored:

The tools will create a recovery tape for a system with mirrored disks, but it will not restore the mirrored disk configuration. If the system is later recovered, previously mirrored volumes will no longer be mirrored. They can be manually re-mirrored after the system is up. For more details, see the white paper

</opt/ignite/share/doc/diskmirror.pdf>.

EFI partition on Itanium systems may grow in size:

Beginning with Ignite-UX version C.6.0.x the default EFI partition size changed from 100MB to 500MB, in order to accommodate enough space for new purposes not yet implemented. If the EFI partition was 100MB it will be resized to 500MB during recovery. This may introduce disk space problems, if the disk is fully used. You can change the default size from 500MB to any other size in the installation routine.

Ignite-UX System Recovery Tools - make_recovery

The `make_recovery` command has been obsolete for some time, but was shipped with Ignite-UX along with its replacements command `make_tape_recovery`. Executing `make_recovery` prompted a note saying:

```
NOTE:      make_recovery(103): The make_recovery command will be replaced by
           make_tape_recovery.  Both commands are supported in this release
           (Ignite-UX Revision 3.2).  Please read the man page
           make_tape_recovery(1M) for usage of the new command.  In a
           future release, make_recovery will be replaced by a script that
           calls make_tape_recovery.
```

With Ignite-UX version C.6.0.x the `make_recovery` command was dropped completely and is not available.

Be aware that options used with `make_recovery` are not identical with the same options used with `make_tape_recovery`. Example: the “-A” option has different meanings for `make_recovery` and `make_tape_recovery`. By default ‘`make_recovery -A`’ archived the complete root volume group, whereas ‘`make_tape_recovery -A`’ will only include “essential” files and directories.

Ignite-UX System Recovery Tools - make_tape_recovery

Overview

- Can be executed locally (also using a Terminal User Interface) as well as from the Ignite-UX server.
- Creates a bootable DDS/DLT tape. It can also span multiple tapes if run locally.
- Besides the root volume group, other volume groups can be archived as well.
Note: This is not recommended, because Ignite-UX is not a backup tool. Backup data with proper backup utilities such as `fbackup`, `tar`, etc.
- The client specific configuration files are either stored locally or on the Ignite-UX server.
- Replaces `make_recovery` since Ignite-UX versions A.3.2/B.3.2.

Creating a make_tape_recovery Tape - Ignite-UX Server GUI

On your host system, allow the Ignite-UX server to access the display with:

```
# xhost +<Ignite_server_name>
for example
# xhost +host1
```

Export the display if necessary:

```
# export DISPLAY=<hostname>:0
```

for example

```
# export DISPLAY=host1:0
```

On the Ignite-UX server start Ignite-UX as root:

```
# /opt/ignite/bin/ignite
```

In case of a new client, add the new client first:

Choose <Actions> <Add New Client for Recovery...>

Then start the Tape Recovery Archive Creation:

Click on the client icon and select <Actions> <Create Tape Recovery Archive ...>
You will now be guided through some screens for additional configuration.

Note: Do not forget to press <add selected disk/vg> for the vg00 in the Archive Content screen if you want to backup the complete vg00. Otherwise, only a core OS will be backed up. You may also include other VGs, directories or files and also exclude certain ones.

Creating a make_tape_recovery tape - Command Line Examples

When the server is stated using the `-s` option, the configuration, log and status files will be created on the Ignite-UX server at:

```
/var/opt/ignite/recovery/clients/0x{LLA}/recovery/<date,time>.
```

If no Ignite-UX server is stated, they will be created locally on the client system at
`/var/opt/ignite/recovery/<date,time>.`

Note: Every example below shows the command line with and without the `-s` option to remind you of the different possibilities.

Archiving up only essential core OS files using the default device file `/dev/rmt/0mn`

```
# /opt/ignite/bin/make_tape_recovery  
or  
# /opt/ignite/bin/make_tape_recovery -s <Ignite_server>
```

Note: `make_tape_recovery` will check if there are configuration files from previously saved archives. If no configuration files exist that have different settings, only a core OS (essential files) will be archived. `/opt/ignite/recovery/mnr_essentials` lists the files and directories that are considered essential.

Archiving the complete root volume group using the default device file `/dev/rmt/0mn`

```
# /opt/ignite/bin/make_tape_recovery -x inc_entire=vg00  
or  
# /opt/ignite/bin/make_tape_recovery -x inc_entire=vg00 -s  
<Ignite_server>
```

Note: Remember that the “-A” option is different from `make_recovery`:

- A: Based on the files that are specified for inclusion, this option identifies the disk(s) and/or VG(s) that contain these files and includes all files from the disk(s)/VG(s) in the archive. If no further files are specified for inclusion, the default essentials file list `/opt/ignite/recovery/mnr_essentials` is used for specifying the included files.

Archiving the complete root VG using a non-default device file

```
# /opt/ignite/bin/make_tape_recovery -Av -a c0t1d0BESTn
or
# /opt/ignite/bin/make_tape_recovery -Av -a c0t1d0BESTn \
-s <Ignite_server>
```

- a: Tape drive device file. Always use a no-rewind device file. You can use DDS and supported DLT tape drives. For supported DLT's please see the Release Notes at <http://www.software.hp.com/products/IUX/docs.html>.

Archiving complete VGs/disks - including and excluding files and directories

```
# /opt/ignite/bin/make_tape_recovery -x inc_entire=vg00 \
-x inc_entire=vg01
or
# /opt/ignite/bin/make_tape_recovery -x inc_entire=vg00 \
-x inc_entire=vg01 -s <Ignite_server>
```

`-x inc_entire=vg_name|/dev/dsk/<name>`: Includes all file systems contained on the VG. Use the VG name (such as `vg00`) when you want all file systems that are part of that LVM VG to be included in the archive. You also can specify disks. For this, use a block device file of the format `/dev/dsk/<name>` when specifying a whole-disk (non-LVM) file system.

Further `-x` arguments:

`-x include=file|dir`: Includes the file or directory in the recovery archive but does not cross any mount points.

`-x inc_cross=file|dir`: Includes the file or directory in the recovery archive and crosses mount points to access any directories that are mounted or files contained in directories that are mounted.

`-x exclude=file|dir`: Excludes the file or directory from the archive. When a directory is specified, no files beneath that directory will be stored in the archive.

Archiving choosing the archive contents in interactive mode

```
# /opt/ignite/bin/make_tape_recovery -i
or
# /opt/ignite/bin/make_tape_recovery -i -s <Ignite_server>
```

- i: Causes `make_tape_recovery` to run interactively to allow you to select which

files and directories are to be included in the recovery archive.

Note: Better start directly from the Ignite-UX server. If you use it anyway, do not forget to press <add selected disk/vg> for the vg00 in the Archive Content screen if you want to backup the complete vg00. Otherwise only a core OS will be backed up!

Backing up the root VG to change the system configuration

```
# /opt/ignite/bin/make_tape_recovery -Av -I
or
# /opt/ignite/bin/make_tape_recovery -Av -I -s <Ignite_server>
```

-I: Cause the system recovery process to always present the interactive menus when booting from the tape during the later installation.

Using make_tape_recovery in preview mode

```
# /opt/ignite/bin/make_tape_recovery -v -p
or
# /opt/ignite/bin/make_tape_recovery -v -p -s <Ignite_server>
```

-p: If the tape was created without stating an Ignite-UX server, the files will be located at /var/opt/ignite/recovery/latest.
If the IUX server was stated, the files are at
/var/opt/ignite/clients/<LLA>/recovery/<date,time>.

Only following files will be created which can be edited before presuming the tape creation:

archive_cfg, control_cfg, system_cfg

The files that end in _cfg contain configuration information that can be changed, like converting from HFS to JFS.

flist

This file list all files will be included in the tar archive.

Note: Only delete user specific files as deleting other files can cause corruption of the archive.

After making the desired changes, you can use the -r option to resume the tape creation based on the changes you made.

```
# /opt/ignite/bin/make_tape_recovery -r
```

Verifying the make_tape_recovery Tape

Looking up the log files

If make_tape_recovery was run locally, look up the log files at
/var/opt/ignite/recovery/<date,time>/.

If it was run from the Ignite-UX server, look up log files at
/var/opt/ignite/recovery/clients/0x{LLA}/recovery/<date,time>.

recovery.log	progress and error log file
flist	tar archive content

Checking boot volume on tape (LIF header)

```
# /opt/ignite/bin/copy_boot_tape -u /dev/rmt/0mn -b -d /tmp
# /usr/bin/lifls -l /tmp/bootimage
```

Checking the tar archive on the tape

```
# /usr/bin/mt -t /dev/rmt/0mn rew
# /usr/bin/mt -t /dev/rmt/0mn fsf 1
# /usr/bin/tar tvf /dev/rmt/0m
```

Note: 0m not 0mn

Extracting single files from the tar archive

```
# /usr/bin/mt -t /dev/rmt/0mn rew
# /usr/bin/mt -t /dev/rmt/0mn fsf 1
# /usr/bin/tar xvf /dev/rmt/0m filename1 filename2
```

Restoring from a make_tape_recovery Tape

automatically

- 1) Insert the System Recovery tape into the tape drive.
- 2) Boot the system.
- 3) Interrupt the boot sequence to redirect it to the tape drive.
- 4) Select no intervention with ISL.
- 5) Allow the install process to complete automatically.

interactive mode (changing system configuration, cloning)

- 1) Insert the System Recovery tape into the tape drive.
- 2) Boot the system.
- 3) Interrupt the boot sequence to redirect it to the tape drive.
- 4) Cancel the non-interactive installation by hitting the <Return> key when the following messages are displayed:

```
WARNING: The configuration information calls for a non- interactive
installation.
Press <Return> within 10 seconds to cancel batch-mode installation:
```

The "Ignite-UX Welcome" screen will be presented.

Select the option: [`Install HP-UX`]

Then select the option: [] `Advanced Installation`

5) Make any desired changes to the file systems, hostname, IP address, timezone, root password, DNS server, and gateway information.

6) Select [`GO`] to proceed with the installation.

Restoring from a `make_tape_recovery` Tape on Itaniums systems

1) Insert the CoreOS CD-ROM into the CD-ROM drive.

2) Boot the system.

3) Interrupt the boot sequence to redirect it to the CD-ROM drive.

4) Cancel the non-interactive installation by hitting the <Return> key when the following messages are displayed:

```
WARNING: The configuration information calls for a non- interactive
installation.
Press <Return> within 10 seconds to cancel batch-mode installation:
```

The “User Interface and Media Options” screen will be presented.

5) Check “Media only installation” and “Guided installation”

The “Media Installation” screen will be presented.

6) Check “Boot from CD/DVD, Recover from Tape” option

7) Choose the appropriate tape drive in the “Tape Drive Selection” screen

8) Make any desired changes to the file systems, hostname, IP address, timezone, root password, DNS server, and gateway information.

9) Select [`GO`] to proceed with the installation.

Ignite-UX System Recovery Tools - `make_net_recovery`

Overview

Can be executed locally (also using a Terminal User Interface) as well as from the Ignite-UX server using the Ignite-UX user interface.

Creates an archive on the Ignite-UX or another Archive Server (must be an NFS server).

Besides the root volume group other volume groups can be archived as well.

Note: This is not recommended because Ignite-UX is not a backup tool. Backup other volume groups with proper backup utilities such as `fbackup`, `tar`, etc.

The client specific configuration files are stored on the Ignite-UX server.

Large File Support for Archives Greater than 2GB

Specific support for large files is needed if archives greater than 2GB are to be created. To support NFS mount and network data transfer of large files, you will need to have NFS PV3 installed on both the client and server. If the client or server is running HP-UX 10.20, the Networking ACE patch (containing the NFS PV3 software) should be installed and updated with a patch cited in the Ignite-UX Release Notes. HP-UX 11.00 and later versions come with PV3 by default. The Ignite-UX Release Notes located at:

<http://www.software.hp.com/products/IUX/docs.html> identify which patches are required for NFS support of archives greater than 2GB for HP-UX 10.20, 11.00 and later. You may also need to download the latest `gzip` Version from <http://hpux.asknet.de/hppd/hpux/Gnu/>.

Determining if your file system supports large files and changing to large file support

- a) Without Online-JFS, you must create a new file system to change the file system to support largefiles.

Check if the file system supports large files with:

```
# /usr/sbin/fstyp -v /dev/vgxx/lvolx|grep f_flag

f_flag: 16  large files are activated
f_flag: 0   large files are inactive
```

- b) With Online-JFS

```
# /usr/sbin/fsadm -F vxfs /file_system_path
```

If the output shows `largefiles`, then large files are activated.

If it shows `nolargefiles` large files are inactive.

To change a file system to support large files, do following:

```
# /usr/sbin/fsadm -F file_system -o largefiles /dev/vgxx/lvolx
for example
# /usr/sbin/fsadm -F vxfs -o largefiles /dev/vg01/lvol6
```

In order for clients to be affected by the change if the file system is already exported, re-run:

```
# /usr/sbin/exportfs -av
```

Archive Configuration Policies

When specifying archive content, either via the Ignite-UX GUI or in the `make_net_recovery`

command line, the following rules apply:

- No essential file or directory can be excluded.
- Files and directories inside an included directory will be included recursively.
- If a symbolic link to a file or directory is included, only the link will be included in the archive, not the actual file or directory, unless it, too, is included. A warning will be given when the item itself is a symbolic link.
- If a directory is included which contains symbolic links to other files or directories, the symbolic links will be included but not the referenced files or directories, unless they, too, are included. No warnings are given regarding these links.
- If a directory contains local mount points, the files and directories under the local mount points will not be included, by default. This policy can be waived by specifying the option `inc_cross` (include directory and cross-mount points), in the selection interface or command line.
- In case of conflicting entries in the selections, Exclusions take precedence over inclusions.

Exporting the archive directory

The default archive location on the Ignite-UX server is `/var/opt/ignite/recovery/archives/<hostname>`. The hostname is the name of the system being archived. If the recovery archive creation is initiated from the Ignite-UX GUI on the Ignite-UX server and the archive is saved on the Ignite-UX server, the `/etc/exports` file will be edited automatically. If you put the archive onto another path or archive server, the directory used to store the archives must be exported from the archive server to each client.

- 1) On the archive server, create a directory for each client to hold the archive of the client's files. It is best to use the default path but you can also state other paths.

```
# /usr/bin/mkdir -p /var/opt/ignite/recovery/archives/<client_hostname>
```

- 2) Change the owner and group to bin

```
# /usr/bin/chown bin:bin \  
/var/opt/ignite/recovery/archives/<client_hostname>
```

- 3) Edit `/etc/exports` on the archive server to add an entry for each client.

```
# /usr/bin/vi  
  
/var/opt/ignite/recovery/archives/<client_hostname> \  
-anon=2,access=<client_hostname>
```

- 4) Run the `exportfs` command to have the edits to the `exports` file take effect:

```
# /usr/sbin/exportfs -a
```

Creating a `make_net_recovery` Archive - Ignite-UX Server GUI

On your host system, allow the Ignite-UX server to access the display with:

```
# xhost +<Ignite_server_name>
for example
# xhost +host1
```

Export the display if necessary:

```
# export DISPLAY=<hostname>:0
for example
# export DISPLAY=host1:0
```

On the Ignite-UX server start Ignite-UX as root:

```
# /opt/ignite/bin/ignite
```

In case of a new client, add the new client first:

Choose <Actions> <Add New Client for Recovery...>

Start the Tape Recovery Archive Creation:

Click on the client icon and select
<Actions> <Create Network Recovery Archive ...>
You will now be guided through some screens for additional configuration.

Note: Do not forget to press <add selected disk/vg> for the vg00 in the Archive Content screen if you want to backup the complete vg00. Otherwise, only a core OS will be backed up. You may also include other VGs, directories or files and also exclude certain ones.

Creating a `make_net_recovery` Archive - Command Line Examples

Archiving only essential core OS files

```
# /opt/ignite/bin/make_net_recovery -s <Ignite_server>
```

Note: `make_net_recovery` will check if there are configuration files from previously saved archives. If no configuration files exist that have different settings, only a core OS (essential files) will be backed up. `/opt/ignite/recovery/mnr_essentials` lists the files and directories that are considered essential.

Archiving the complete root VG

```
# /opt/ignite/bin/make_net_recovery -Av -s <Ignite_server>
```

-A: Based on the files that are specified for inclusion, this option identifies the disk(s) and/or VGs that contain these specified files and includes all files from the disk(s)/VGs in the archive. If no further files are specified for inclusion, the default essentials file list `/opt/ignite/recovery/mnr_essentials` is used for specifying the included files.

-v: Verbose mode, error and process logs will be displayed.

Archiving the complete root VG to a different archive location

```
# /opt/ignite/bin/make_net_recovery -Av \
```

```
-a archive_server:archive_directory_path -s <Ignite_server>
for example
# /opt/ignite/bin/make_net_recovery -Av -a host2:/my_archives -s host1
```

-a: Specifies the NFS server and location to store the archive. The archive directory must be NFS exported and sufficient disk space is required.

Archiving complete VGs/disks and including and excluding files and directories

```
# /opt/ignite/bin/make_net_recovery -x inc_entire=vg00 \
-x inc_entire=vg01 -s <Ignite_server>
```

-x inc_entire=vg_name|/dev/dsk/<name>: Includes all file systems contained on the VG. Use the VG name (such as vg00) when you want all file systems that are part of that LVM VG to be included in the archive. You also can specify disks. For this, use a block device file of the format /dev/dsk/<name> when specifying a whole-disk (non-LVM) file system.

Further -x arguments:

-x include=file|dir: Includes the file or directory in the recovery archive but does not cross any mount points.

-x inc_cross=file|dir: Includes the file or directory in the recovery archive and crosses mount points to access any directories that are mounted or files contained in directories that are mounted.

-x exclude=file|dir: Excludes the file or directory from the archive. When a directory is specified, no files beneath that directory will be stored in the archive.

Please see also *"Archive configuration policies"*.

Archiving choosing the archive contents in interactive mode

```
# /opt/ignite/bin/make_net_recovery -i -s <Ignite_server>
```

-i: Causes make_net_recovery to run interactively to allow you to select which files and directories are to be included in the recovery archive.

Note: better start directly from the Ignite-UX server. If you use it anyway, do not forget to press <add selected disk/vg> for the vg00 in the Archive Content screen if you want to backup the complete vg00. Otherwise only a core OS will be backed up!

Verifying the Network Recovery Archive

Looking up the log files at

```
/var/opt/ignite/recovery/clients/0x{LLA}/recovery/<date,time>/
```

recovery.log	progress and error log file
flist	tar archive content

Checking the zipped tar archive

```
# /usr/contrib/bin/gzcat \  
  /var/opt/ignite/recovery/archives/<hostname>/<date,time> \  
  | tar -tvf - > /tmp/archive_content  
or  
# /usr/contrib/bin/gzcat \  
  /var/opt/ignite/recovery/archives/<hostname>/<date,time> \  
  | tar -tvf - | more
```

Restoring from the Network Recovery Archive

Please see chapter *"Booting and installing an HP-UX client"*.

Note: If you have problems installing for a `make_net_recovery` archive, check the `/var/opt/ignite/clients/CINDEX` file and the config files mentioned in the `CINDEX` file. Also make sure that the archive is exported via NFS.

Creating a Bootable Recovery Tape with a `make_net_recovery` Archive

Note: It is important that the archive fits onto a single tape.

Example: The hostname is `sys1`, the recovery archive is named "2002-03-12,09:00"

Creating the LIF header (Boot Header)

```
# /usr/bin/cd /var/opt/ignite/clients/sys1/recovery/2002-03-12,09:00  
# /opt/ignite/bin/make_medialif \  
  -f system_cfg -f control_cfg -f archive_cfg \  
  -C "2002-03-12,09:00 sys1 recovery image" \  
  -a -l /var/tmp/my_lif
```

Now modify the LIF file to set it up for use on the tape:

```
# /opt/ignite/bin/instl_adm -d -F /var/tmp/my_lif > /var/tmp/cfg
```

Edit the `/var/tmp/cfg` file and add the following lines to the end of the file:

```
control_from_server=FALSE  
run_ui=TRUE
```

Or, if you just want the recovery to proceed without any interaction, make `run_ui FALSE` and specify to allow warnings, as shown in the following:

```
control_from_server=FALSE  
run_ui=FALSE  
env_vars += "INST_ALLOW_WARNINGS=10"
```

Then, issue the following command:

```
# /opt/ignite/bin/instl_adm -F /var/tmp/my_lif -f /var/tmp/cfg
```

Writing the LIF Header and the network recovery archive onto tape

Create a DDS1 device file if you do not have one already. A DDS1 device file is compatible with most tape drives:

```
# /usr/sbin/ioscan -fC tape

Class I  H/W Path      Driver   S/W State H/W Type  Description
=====
tape  0  8/16/5.6.0  stape   CLAIMED  DEVICE  HP   C1533A

# /usr/sbin/mksf -v -H 8/16/5.6.0 -b DDS1 -n -a
```

This will create the device file, `/dev/rmt/clt6d0DDS1n`, for example.

Rewind the tape and write the LIF Header and the archive onto the tape:

```
# /usr/bin/mt -t /dev/rmt/clt0d0DDS1n rew
# /usr/bin/dd if=/var/tmp/my_lif of=/dev/rmt/clt0d0DDS1n obs=2k
# /usr/bin/dd \
  if=/var/opt/ignite/recovery/archives/sys1/2002-03-12,09:00
  of=/dev/rmt/clt0d0DDS1n obs=10k
```

Then rewind the tape again:

```
# /usr/bin/mt -t /dev/rmt/clt0d0DDS1n rew
```

Recovering Mirrored Disks after Installation with Ignite-UX

It is possible to use Ignite-UX for backing up the root volume group of mirrored disks, but Ignite-UX will not preserve the mirror configurations. The disk mirrors will be lost and must be reconfigured using LVM commands. The boot header of the mirrored disks will be touched as well when recovering using Ignite-UX (`pvcreate`)!

Example: The mirror disk is `/dev/dsk/clt6d0`.

Make sure the disk is removed from the root volume group.

```
# /usr/sbin/vgreduce /dev/vg00 /dev/dsk/clt6d0
```

Create the Boot Header on the mirrored disk.

```
# /usr/sbin/pvcreate -f -B /dev/rdisk/clt6d0
```

Add the mirrored disk back to the group.

```
# /usr/sbin/vgextend /dev/vg00 /dev/dsk/clt6d0
```

Copy the boot area to the disk.

```
# /usr/sbin/mkboot -l /dev/rdisk/clt6d0
```

```
# /usr/sbin/mkboot -a \"hpux -lq\" /dev/rdisk/c1t6d0
```

Allocate the mirrors. Mirrors must be allocated for all logical volumes that were previously mirrored.

```
# /usr/sbin/lvextend -m 1 /dev/vg00/lvol1 /dev/dsk/c1t6d0
# /usr/sbin/lvextend -m 1 /dev/vg00/lvol2 /dev/dsk/c1t6d0
# /usr/sbin/lvextend -m 1 /dev/vg00/lvol3 /dev/dsk/c1t6d0
...
```

Update the BDRA and LABEL file.

```
# /usr/sbin/lvlnboot -r /dev/vg00/lvol3
# /usr/sbin/lvlnboot -b /dev/vg00/lvol1
# /usr/sbin/lvlnboot -s /dev/vg00/lvol2
# /usr/sbin/lvlnboot -d /dev/vg00/lvol2
```

Creating SD-UX and non-SD-UX Software Depots

Creating an HP-UX Core-OS Depot

It is assumed that the CD-ROM drive is connected at `/dev/dsk/c1t2d0` (to be looked up with `# /usr/bin/ioscan -fnC disk`).

Note: do not mount the CD-ROM for creating Core-OS depots.

Example 1: A disk depot for an HP-UX 10.20 workstation installation will be created.

Please insert the HP-UX 10.20 Core-OS CD-ROM for workstations (700 systems). The depot will be named `core_700` and will be created at `/var/opt/ignite/depots/Rel_B.10.20`.

```
# /opt/ignite/bin/make_depots -s /dev/dsk/c1t2d0 -r B.10.20 -a 700
or
# /opt/ignite/bin/make_depots -s /dev/dsk/c1t2d0 \
  -d /var/opt/ignite/depots/Rel_B.10.20/core_700
```

Note: If you want to create an HP-UX 10.20 depot on an 11.x Ignite-UX server, you must additionally use the `-x layout_version=0.8` option.

If you would like to create a depot for an HP-UX B.10.20 server, please specify `-a 800` or use the `-d` option to specify `core_800`.

Example 2: A disk depot for an HP-UX 11.00 installation will be created.

Please insert the HP-UX 11.00 Core-OS CD-ROM. The depot will be named `core` and will be created at `/var/opt/ignite/depots/Rel_B.11.00`.

```
# /opt/ignite/bin/make_depots -s /dev/dsk/c1t2d0 -r B.11.00
or
# /opt/ignite/bin/make_depots -s /dev/dsk/c1t2d0 \
  -d /var/opt/ignite/depots/Rel_B.11.00/core
```

Example 3: A disk depot for an HP-UX 11i installation will be created.

Please insert the first of the two HP-UX 11i Core-OS CD-ROMs in the CD-ROM drive. The depot will be named `mcoe_core` and will be created at:

```
/var/opt/ignite/depots/Rel_B.11.11.
```

```
# /opt/ignite/bin/make_depots -s /dev/dsk/c2t3d0 \  
-d /var/opt/ignite/depots/Rel_B.11.11/mcoe_core
```

When the `make_depots` command has succeeded, please insert the second Core-OS CD-ROM and repeat above step using exactly the same command line.

Creating a Support Plus Patch Bundle Depot

Because the SupportPlus CD-ROM contains not only one, but several depots in form of patch bundles, the CD-ROM must be mounted first. If the mountpoint `/SD_CDROM` does not yet exist, create it with `mkdir`. Mount the SupportPlus CD to `/SD_CDROM`. To find out which depots are available for installation, you can use `# ls /SD_CDROM`.

Example 1: A support plus patch bundle depot for an HP-UX 10.20 workstation installation will be created.

```
# /opt/ignite/bin/make_depots -s /SD_CDROM/XSW700GR1020 \  
-d /var/opt/ignite/depots/Rel_B.10.20/XSW700GR1020
```

Note: If you want to create HP-UX 10.20 depots on an 11.x Ignite-UX server, you must additionally use the `-x layout_version=0.8` option. Remember that 10.20 clients are not officially supported.

Example 2: A support plus patch bundle depot for an HP-UX 11.00 installation will be created.

```
# /opt/ignite/bin/make_depots -s /SD_CDROM/QPK1100 \  
-d /var/opt/ignite/depots/Rel_B.11.00/QPK1100
```

Example 3: A support plus patch bundle depot for an HP-UX 11i-installation will be created.

```
# /opt/ignite/bin/make_depots -s /SD_CDROM/GOLDQPK11i \  
-d /var/opt/ignite/depots/Rel_B.11.11/GOLDQPK11i
```

Creating an Individual Patch Depot

Example: individual patches for HP-UX 11.00 were downloaded to `/tmp/patch_download`.

1) Unpacking the patches in `/tmp/patch_download`.

```
# /usr/bin/cd /tmp/patch_download  
# for i in PH*  
> do  
> sh $i  
> done
```

2) Moving the descriptions for example to `/tmp/patch_description`.

```
# /usr/bin/mkdir /tmp/patch_description
# /usr/bin/mv /tmp/patch_download/*.text /tmp/patch_description
```

3) Creating the individual patch depot.

```
# /usr/bin/mkdir /var/opt/ignite/depots/Rel_B.11.00/my_patches
# for i in PH*.depot
> do
> /usr/sbin/swcopy -s ${PWD}/${i} \* @ \
  /var/opt/ignite/depots/Rel_B.11.00/my_patches
> done
```

Note: If you want to use `swcopy` for HP-UX 10.20 depots on a 11.x Ignite-UX server, you must additionally use the `-x layout_version=0.8` option.

4) Making sure all installed patches are included in the individual patch depot.

```
# /usr/sbin/swlist -d @ /var/opt/ignite/depots/Rel_B.11.00/my_patches
```

5) Converting the individual patches into a single bundle and putting the bundle in the patch depot (Ignite-UX can only handle SD bundles).

```
# /opt/ignite/bin/make_bundles -B -n individual_patches \
-t "HP-UX 11.00 Patches" \
  /var/opt/ignite/depots/Rel_B.11.00/my_patches
```

6) Running `swlist` again to verify the creation of the bundle.

```
# /usr/sbin/swlist -d @ /var/opt/ignite/depots/Rel_B.11.00/my_patches
```

To display the patches of this bundle, use

```
# /usr/sbin/swlist -l product \
-d @ /var/opt/ignite/depots/Rel_B.11.00/my_patches
```

7) Changing individual patch depots.

If you need to add additional patches to the depot in the future, simply `unshar` the patches as described above, `swcopy` them into the patch depot, and rerun `make_bundles`. If you would like to remove a patch from the depot, simply use the `swremove` command and rerun `make_bundles`. The example below removes the patch `PHKL_8376` from the patch depot which was previously named `individual_patches` via the `-n` option.

```
# /usr/sbin/swremove -d individual_patches.PHKL_8376 \
@ /var/opt/ignite/depots/Rel_B.11.00/my_patches
```

Special Handling of Patch, ACE and HWE Installations

For issues regarding ...

- Avoiding Backup Patch Files
- Avoiding Problems With Superseded Patches
- Using Ignite-UX with Additional Core Enhancements (ACE) and Hardware

Extensions (HWE)

...please see the Ignite-UX Admin Guide at
<http://www.software.hp.com/products/IUX/docs.html>

Creating an Application Depot

Example 1: Copying an application from one of the application CDs.

If the mount point `/SD_CDRROM` does not yet exist, create it with `mkdir`. Then mount the application CD to `/SD_CDRROM`. To find out which products are available for installation, you can use `# ls /SD_CDRROM`. For further examples, please see `swcopy (1M)`.

```
# /usr/sbin/swcopy -s /SD_CDRROM B3691AA_TRY \  
@ /var/opt/ignite/depots/Rel_B.11.00/my_applications
```

Example 2: Copying applications from a depot

All software from the depot `/my_depots/depot1` which is located on `host1` to `/var/opt/ignite/depots/Rel_B.11.00/my_applications` will be copied.

```
# /usr/sbin/swcopy -s host1:/my_depots/depot1 \* \  
@ /var/opt/ignite/depots/Rel_B.11.00/my_applications
```

Note: If you want to use `swcopy` for HP-UX 10.20 depots on a 11.x Ignite-UX server, you must additionally use the `-x layout_version=0.8` option.

Creating non-SD-UX Depots

If the source is a non-SD-UX depot, the `make_depots` command is not applicable. Do not attempt to use non-core-OS archives (such as layered applications) that contain files that get loaded in `/var/adm/sw/*`. Delivering files in this directory in this method may corrupt the software distributor database. Please proceed with the next step "*Creating Ignite-UX Config Files for SD-UX and non-SD-UX Depots*".

Creating Ignite-UX Config Files for SD-UX and non-SD-UX Depots

Example 1: Creating Config Files for all SD-UX depots found in the default location
`/var/opt/ignite/depots/Rel_B.xx.yy`

```
# /opt/ignite/bin/make_config -r B.11.00
```

Example 2: Creating Config Files for all SD-UX depots located at
`/my_depots/Rel_B.11.00`

```
# /usr/bin/cd /my_depots/Rel_B.11.00  
# for i in *  
> do  
> /opt/ignite/bin/make_config -s ${PWD}/${i} \  
-c /var/opt/ignite/data/Rel_B.11.00/${i}.cfg  
> done
```

Example 3: Creating a Config File for one SD-UX Depot located on another system at
`/my_depots/Rel_B.11.00/core`

```
# /opt/ignite/bin/make_config -s host1:/my_depots/Rel_B.11.00/core \
-c /var/opt/ignite/data/Rel_B.11.00/core.cfg
```

Example 4: Creating Ignite-UX Config Files for Individual Patch Depots

```
# /opt/ignite/bin/make_config \
-s /var/opt/ignite/depots/Rel_B.11.00/my_patches \
-c /var/opt/ignite/data/Rel_B.10.20/my_patches.cfg
```

Example 5: Creating Ignite-UX Config Files for Non-SD Depots

A sample config file for a non-coreOS (application) tar, cpio, pax archive can be found at `/opt/ignite/data/examples/noncore.cfg`.

Copy the `noncore.cfg` file to `/var/opt/ignite/data/Rel_B.xx.yy` and edit it manually as described within the sample file itself.

```
# /usr/bin/cp /opt/ignite/data/examples/noncore.cfg \
/var/opt/ignite/data/Rel_B.11.00/non_SD_config.cfg
```

When done editing this file, check it with

```
# /opt/ignite/bin/instl_admin -T -f \
/var/opt/ignite/data/Rel_B.11.00/non_SD_config.cfg
```

Managing the INDEX File

The order of the `INDEX` file determines in which order the depots will be loaded. There must always be a HP-UX release specific config file such as `/opt/ignite/data/Rel_B.11.00/config` as the first line. If you are using the `/var/opt/ignite/config.local` file, it should always be the last entry for the `cfg` clause.

Example 1: using the `manage_index` command to add the config file

`/var/opt/ignite/data/Rel_B.11.00/core.cfg` into the `/var/opt/ignite/INDEX` file for the `cfg` clause "HP-UX B.11.00 Default".

```
# /opt/ignite/bin/manage_index -a -f \
/var/opt/ignite/data/Rel_B.11.00/core.cfg -c "HP-UX B.11.00 Default"
```

Example 2: adding the required config files manually to the `/var/opt/ignite/INDEX` file for the `cfg` clause "HP-UX B.11.00 Default".

```
# /usr/bin/vi /var/opt/ignite/INDEX

cfg "HP-UX B.11.00 Default" {
    description "This selection supplies a HP-UX B.11.00
default installation"
    "/opt/ignite/data/Rel_B.11.00/config"
    "/opt/ignite/data/Rel_B.11.00/hw_patches_cfg"
    "/var/opt/ignite/data/Rel_B.11.00/core.cfg"
    "/var/opt/ignite/data/Rel_B.11.00/XSWGR1100.cfg"
    "/var/opt/ignite/data/Rel_B.11.00/individual_patches.cfg"
    "/var/opt/ignite/data/Rel_B.11.00/my_applications.cfg"
```

```

    "/var/opt/ignite/config.local"
}

```

Modifying/Adding Depots

- 1) Use `make_depots`, `swcopy` or `swremove` to edit your depots.
- 2) Rerun `make_config` for the corresponding release to update your config files.
- 3) Run `manage_index` for each newly added software depot.

Example 1 - Creating SD-UX Depots for an HP-UX 11.00 Installation

- 1) Look up the device file for the CD-ROM drive.

```

# /usr/sbin/ioscan -fnC disk

Class I  H/W Path      Driver  S/W State  H/W Type  Description
-----
disk  0   8/0/19/0.6.0  sdisk   CLAIMED   DEVICE    IBM   DDRS-34560WS
      /dev/dsk/c0t6d0  /dev/rdisk/c0t6d0
disk  2   8/16/5.1.0    sdisk   CLAIMED   DEVICE    TOSHIBA CD-ROM XM-5701TA
      /dev/dsk/clt1d0  /dev/rdisk/clt1d0
disk  1   8/16/5.5.0    sdisk   CLAIMED   DEVICE    QUANTUM FIREBALL1050S
      /dev/dsk/clt5d0  /dev/rdisk/clt5d0

```

- 2) Insert the HP-UX 11.00 Core-OS CD, but do not mount it. Then create the Core Os depot.

```

# /opt/ignite/bin/make_depots -s /dev/dsk/clt1d0 -r B.11.00
or
# /opt/ignite/bin/make_depots -s /dev/dsk/clt1d0 \
  -d /var/opt/ignite/depots/Rel_B.11.00/core

```

Note for HP-UX 11i: For the second CD, repeat `make_depots` with the same syntax.

- 3) Insert the Support Plus CD and mount it at `/SD_CDROM`.

```

# /usr/bin/mkdir /SD_CDROM
# /usr/sbin/mount /dev/dsk/clt1d0 /SD_CDROM

```

- 4) Create the General Release Patch depot:

```

# /opt/ignite/bin/make_depots -s /SD_CDROM/QPK1100 \
  -d /var/opt/ignite/depots/Rel_B.11.00/QPK1100

```

- 5) Export the depots via NFS, if you did not use the default directory or you placed the depots on another depot server.

```

# /usr/bin/vi /etc/exports

    /ignite/depots -anon=2

# /usr/sbin/exportfs -av

```

- 6) Create config files for the depot at `/var/opt/ignite/data/Rel_B.11.00`.

```

# /opt/ignite/bin/make_config -r B.11.00

```

If you have not used the `/var/opt/ignite/data/Rel_B.11.00`, you must specify the

config files individually:

```
# /opt/ignite/bin/make_config -v \
-s host1:/var/opt/ignite/depots/Rel_B.11.00/core \
-c /var/opt/ignite/data/Rel_B.11.00/core.cfg

# /opt/ignite/bin/make_config -v \
-s host1:/var/opt/ignite/depots/Rel_B.11.00/QPK1100 \
-c /var/opt/ignite/data/Rel_B.11.00/QPK1100.cfg
```

7) Add the configuration to the `/var/opt/ignite/INDEX` file:

Copy the `cfg` section of "HP-UX B.11.00 Default" completely and rename the new section as you like, e.g. "HP-UX B.11.00 my installation" and use following scripts:

```
cfg "HP-UX B.11.00 Default" {
    description "HP-UX B.11.00 my installation"
    "/opt/ignite/data/Rel_B.11.00/config"
    "/opt/ignite/data/Rel_B.11.00/hw_patches_cfg"
    "/var/opt/ignite/data/Rel_B.11.00/core.cfg"
    "/var/opt/ignite/data/Rel_B.11.00/QPK1100.cfg"
    "/var/opt/ignite/config.local"
}
```

8) Check the `INDEX` file with:

```
# /opt/ignite/bin/instl_admin -T
```

9) Please see chapter "*Booting and installing an HP-UX client*" to install the client.

Example 2 - Creating a CD-ROM SD-UX Depot

Note: You can only create a CD-ROM depot for installations containing one Core-OS CD.

1) Look up the device file for the CD-ROM drive.

```
# /usr/sbin/ioscan -fnC disk

Class I  H/W Path          Driver  S/W State  H/W Type  Description
=====
disk  0  8/0/19/0.6.0     sdisk   CLAIMED    DEVICE     IBM   DDRS-34560WS
        /dev/dsk/c0t6d0  /dev/rdisk/c0t6d0
disk  2  8/16/5.1.0       sdisk   CLAIMED    DEVICE     TOSHIBA CD-ROM XM-5701TA
        /dev/dsk/c1t1d0 /dev/rdisk/c1t1d0
disk  1  8/16/5.5.0       sdisk   CLAIMED    DEVICE     QUANTUM FIREBALL1050S
        /dev/dsk/c1t5d0 /dev/rdisk/c1t5d0
```

2) Insert the Core-OS CD and mount it at `/SD_CDROM`.

```
# /usr/bin/mkdir /SD_CDROM
# /usr/sbin/mount /dev/dsk/c1t1d0 /SD_CDROM
```

3) Register the CD-ROM as an depot with `swreg`:

```
# /usr/sbin/swreg -l depot @ /SD_CDROM
```

- 4) Create a config file of this depot at `var/opt/ignite/data/Rel_B.xx.yy/core.cfg`:

```
# /opt/ignite/bin/make_config -s /SD_CDRROM \  
-c /var/opt/ignite/data/Rel_B.11.00/core.cfg
```

- 5) Add the configuration to the `/var/opt/ignite/INDEX` file:

Copy the `cfg` section of "HP-UX B.11.00 Default" completely and rename the new section as you like, for example "HP-UX B.11.00 Custom".

Use following scripts:

```
cfg "HP-UX B.11.00 Default" {  
    description "HP-UX B.11.00 my installation"  
    "/opt/ignite/data/Rel_B.11.00/config"  
    "/opt/ignite/data/Rel_B.11.00/hw_patches_cfg"  
    "/var/opt/ignite/data/Rel_B.11.00/core.cfg"  
    "/var/opt/ignite/config.local"  
}
```

- 6) Check the `INDEX` file with:

```
# /opt/ignite/bin/instl_adm -T
```

- 7) Please see chapter "*Booting and installing an HP-UX client*" to install the client.

Booting and Installing an HP-UX Client

If the client system is running HP-UX 9.X or later, you can either use the `bootsys(1M)` command or perform a network boot to install the client. It can be invoked either from a command shell, or from the Ignite-UX screen.

If the client is currently not up and running HP-UX 9.X or later, the client has to be booted over the network. If the client is not in the same subnet as the Ignite-UX server, the client has to be booted from the boot helper. For more details on supported systems, please look up chapter "*Networking Issues*" in the Ignite-UX Release Notes at <http://www.software.hp.com/products/IUX/docs.html>.

Make sure that you have at least one booting IP available in the `/etc/opt/ignite/instl_boottab`, `/etc/bootptab` or via DHCP on the Ignite-UX server respectively the boot helper.

Note: The IP must be an unassigned IP!

If you do not have any unassigned IP's available and you are using the `/etc/opt/ignite/instl_boottab`, reserve the client's IP and the corresponding MAC address by inserting a line with the `reserve` option:

```
# /usr/bin/vi /etc/opt/ignite/instl_boottab  
  
1.3.4.5:0060B0F99816::reserve (IP:MAC_address::reserve)
```

Booting the Client from the Ignite-UX Server - Using the User Interface

Note: The clients must be currently running HP-UX 9.x or later.

- 5) Starting the Ignite-UX screen:

```
# /opt/ignite/bin/ignite
```

- 6) Booting the client using bootsys:

If you have not yet a client icon, select `<ACTIONS>` `<BOOT NEW CLIENT>`. Enter the hostname and if required the password. After the client has booted, the client icon will appear on the Ignite-UX screen.

- 7) Starting the client installation:

Right-click the client icon and choose `<INSTALL CLIENT>` `<New Install>`.

- 8) Configuring the client installation:

Select one of you previously created cfg selections from the `/var/opt/ignite/INDEX` file or an `make_net_recovery` archive. For this, click on `<Configurations:>` from the Basic Tab.

Adjust any other parameters like selecting the boot disk, etc.

For adding/removing Software to be installed, please go to the `<Software>` tab.

At the `<System>` tab, you can adjust you system settings like the hostname, IP adress, etc.

Please go to the `<File System>` tab for tuning file system sizes, LVM parameters, etc.

At the `<Advanced>` tab, select or deselect any scripts you have available from the `/var/opt/ignite/INDEX` file. These scripts will be executed during the final reboot, before the startup scripts (rc scripts) are called up.

- 9) Starting the installation:

Click on the the `< Go!>` button.

You can look up the installation progress now via the log file.

Booting the Client from the Ignite-UX Server - Using the bootsys Command

Note: If you have already run an install session from the server, issuing `bootsys` without the option `-w` will result in an automatic installation without further intervention!

Interactive installation

```
# /opt/ignite/bin/bootsys -w <system_name>
```

Enter the password if required. After the client has booted, the client icon will appear on the Ignite-UX screen. For further options please see the manpage of `bootsys`.

You can now proceed with step 3) from "*Booting the Client from the Ignite-UX server - Using the User Interface*".

Automatic installation

To start an automatic installation, please enter:

```
# /opt/ignite/bin/bootsys -a -I <cfg_configuration> -v <system_name>
```

-a: If no configuration is given with the `-I` option, the defaults will be used for the automatic installation.

-I : You can specify a configuration which is listed as a `cfg` section in the `/var/opt/ignite/INDEX` file. To find out which configuration is available, use:

```
# /opt/ignite/bin/manage_index -l
```

Booting the Itanium and PA-RISC Clients from the Network

Note: For booting older workstations please see the Ignite-UX Admin Guide at <http://docs.hp.com/hpux/onlinedocs/B2355-90704/B2355-90704.html>

- 1) Switch the client on and interrupt the boot sequence pressing any key.
- 2) Boot from the Ignite-UX server or boothelper using one of these ways:
 - a) **PA-RISC:** If your network only has one Ignite-UX server available, enter:

```
BOOT ADMIN> boot lan install
```

Itanium: If your network only has one Ignite-UX server available, enter:

```
EFI shell> lanboot
```

- b) **PA-RISC:** If you want to boot from a certain Ignite-UX server, enter:

```
BOOT ADMIN> boot lan.15.10.18.156 install
```

where 15.10.18.156 is the IP of the Ignite-UX server.

Itanium: This option is not available on Itanium. There should only be one Ignite server per subnet and no other DHCP/BOOTP servers.

- c) **PA-RISC:** If the client is not in the same subnet as the Ignite-UX server, direct the installation to a boot helper:

```
BOOT ADMIN> boot lan.15.10.18.156 install
```

where 15.10.18.156 is the IP of the Ignite-UX boot helper

The client will be booted from the boot helper and then redirected to the Ignite-UX server to complete the installation.

Itanium: Again, this option is not available on Itanium. There should only be one Ignite boot helper per subnet and no other DHCP/BOOTP servers.

- d) **PA-RISC:** Otherwise make the system search for servers and pick one or explicitly tell the system where to boot, as follows

```
BOOT ADMIN> search lan install
```

The list of servers will be displayed with IP addresses. Pick the IP address of the Ignite-UX server you want to boot from by entering, for example:

```
BOOT ADMIN> boot lan.15.10.18.156 install
```

where 15.10.18.156 is the IP of the Ignite-UX server or boot helper

Note: It typically takes two or three searches before the Ignite-UX server will be found, due to a built-in delayed response from the server system.

Itanium: Again, this option is not available on Itanium.

- 3) Enter `n` when asked if you want to interact with IPL (there is no IPL on Itanium).
- 4) If the networking startup fails, press `<Enter>`
Note: This behavior is normal. Just enter the networking parameters now. The networking startup will always fails if you have not specified the networking parameters via the `bootsys` command or the `INSTALLFS` file (`instl_adm` settings).
- 5) Choose the keyboard if it has not been selected automatically via the `INSTALLFS` file or other config files.
- 6) Choose `[Install HP-UX]`
- 7) If you want to proceed the installation from the the Ignite-UX server now, please choose:

```
[ * ] Remote graphical interface running on the Ignite-UX server
```

If you want to proceed the Installation from the Client, please choose:

```
[ * ] Remote graphical interface running on the Ignite-UX server
```

Booting the Client using make_boot_tape

make_boot_tape can be used if the client does not support a network boot or if the client is not on the same subnet as the Ignite-UX server.

The system will be booted from the Ignite-UX kernel on the tape and then the Ignite-Ux server will be contacted to proceed with the installation.

Typically the tape is created on the Ignite-UX server, because it contains Ignite-UX server specific information from the INSTALLFS file (edited with instl_adm).

The tape can also be used if you have several lan cards and you want to use another than the built-in lan card for installation. You will be asked which lan card you want to initialize.

- 1) Create a DDS1 device file for the tape drive first.

```
# /usr/sbin/ioscan -fC tape

Class      I  H/W Path      Driver      S/W State H/W Type  Description
=====
tape       0  8/16/5.6.0  stape      CLAIMED   DEVICE   HP       C1533A

# /usr/sbin/mksf -v -H 8/16/5.6.0 -b DDS1 -n -a
```

The device file will be called something like /dev/rmt/clt6d0DDS1n.

- 2) Check your instl_adm settings and edit them if necessary.

```
# /opt/ignite/bin/ instl_adm -d > /tmp/config_file

# /usr/bin/vi /tmp/config_file

server="15.140.10.59"
netmask[]="0xfffff800"
```

- 3) Create the boot tape

```
# /opt/ignite/bin/make_boot_tape -f /tmp/config_file \
-d /dev/rmt/clt6d0DDS1n -v
```

- 4) Now you can boot from tape to contact the Ignite-UX server.

Note: Itanium systems cannot boot from tape, therefore the boot tape option is useless for them.

Performing a non-interactive Ignite-UX Installation

Note: the client will be installed without any user interaction.

- 1) First you have to adjust the boot kernel /opt/ignite/boot/INSTALLFS of the Ignite-UX

server. Read the current configuration and save it to a `defaults` file:

```
# /opt/ignite/bin/instl_admin -d >/var/opt/ignite/defaults
```

- 2) Now edit this `defaults` file adding following lines:

```
run_ui=false
control_from_server=false
env_vars+="INST_ALLOW_WARNINGS=1"
```

With this step the interactive user interface has been switched off and the client will be installed automatically when booting from the net.

- 3) It is recommended to make further settings, because during the installation, you now cannot adjust any parameters like system name and IP address.
Note: Do not forget to take them out of the configuration after performing the installation of the client. Additionally make sure that in the `/etc/opt/ignite/instl_boottab`, only the entry for the client to be installed is available. Also make sure that nobody else uses the Ignite-UX server while you have set these parameters!

Add following parameters:

```
system_name="blubber"
ip_addr="1.2.3.4"
timezone="MET-1METDST"
```

For further information about possible parameter setting, see the `instl_admin(4)` manpage.

- 4) When you have done all necessary settings, change the boot image `INSTALLFS` after checking the syntax:

```
# /usr/bin/cd /opt/ignite/boot
# /opt/ignite/bin/instl_admin -T -f /var/opt/ignite/defaults
```

If the syntax is ok, edit the boot image

```
# /opt/ignite/bin/instl_admin -f /var/opt/ignite/defaults
```

- 5) Before starting the non-interactive installation, you should have checked the used config files (for the Golden Image, SD-UX depots, etc.) before in interactive mode to see if they are working.
- 6) Please see chapter *"Booting and installing an HP-UX client"* to install the client

Cloning with Golden System Images

Creating a Golden System Image

!!! Note: Because files like `/etc/hosts` and `devices` files are temporarily removed from the clients system during the execution of `make_sys_image`, the system should not be in use **!!!**

- 1) Install the required operating system, patches and applications at the source system and configure it to your needs.
- 2) Create the archive directory on the Ignite-UX server:

```
# /usr/bin/mkdir -p /var/opt/ignite/archives/Rel_B.xx.yy
```

- 3) Copy `/opt/ignite/data/scripts/make_sys_image` from the Ignite-UX Server to `/tmp` at the source system and make it executable.
- 4) Run `make_sys_image` on the source system with following options:

```
# /opt/ignite/data/scripts/make_sys_image -v \  
-f <script with files or directories to exclude> \  
-d <directory to place the archive> \  
-s <ip-address of system to place the archive>
```

for example

```
# /opt/ignite/data/scripts/make_sys_image -v -f /tmp/exclude \  
-d /var/opt/ignite/archives/Rel_B.10.20 -s 1.2.3.4
```

`-f`: You also can list single files. For further information please see the man page of `make_sys_image`. In this example, the directories `/space` and `/export` will not be saved into the Golden System Image. The exclude file has following format:

```
# /usr/bin/cat exclude
```

```
+ ONLY NO_ARCHIVE  
  /space  
  /export
```

`-d` : The chosen directory must have enough space . The Image will be created as a gnuzip file and is about half the size of the data to be saved. It also has to be exported via NFS.

`-s`: Instead of the Ignite-UX server IP, you can also state `local` for creating the System Image locally. Then you can copy the archive named `<hostname>.gz` later to the Ignite-UX or another archive server.

You may check the image contents with:

```
# gzcat <hostname>.gz | pax -v | grep <file_name>
```

- 5) Copy the config files and edited them correspondingly. If you have used the `-s local` option you will have to copy the files from the Ignite-UX server, if Ignite-UX is not installed on the local system.

For HP-UX 10.x copy `/opt/ignite/data/examples/core.cfg` to `/var/opt/ignite/data/Rel_B.10.20/core_700_archive.cfg`

For HP-UX 11.x copy `/opt/ignite/data/examples/core11.cfg` to `/var/opt/ignite/data/Rel_B.11.00/core_archive.cfg`

Edit the copied config files changing following in the section `sw_source`:

```
nfs_source = "<Ignite_Server_IP>:/var/opt/ignite/archives/Rel_B.11.00"
```

Note: This is the path to the archive which has to be NFS exported.

Rename the `archive_path` in the section `init sw_sel "golden image1"` so it matches the name of the Golden Image. And if desired change the description as well.

```
archive_path = "<hostname>.gz"
description = "My Golden System Archive"
```

Get the file system size information of the Golden Image with `archive_impact`:

```
/opt/ignite/lbin/archive_impact -t -g \
/var/opt/ignite/archives/Rel_B.11.00/<hostname>.gz
```

Exchange the current sample "impacts" lines of the config file with the output of the `archive_impact` command, for example:

```
impacts = "/" 30 Kb
impacts = "/etc" 1722 Kb
impacts = "/opt" 123430 Kb
...
```

6) Add the new configuration to the `/var/opt/ignite/INDEX` file:

```
cfg "HP-UX B.11.00 archive" {
    description "HP-UX B.11.00 archive"
    "/opt/ignite/data/Rel_B.11.00/config"
    "/var/opt/ignite/data/Rel_B.11.00/core_archive.cfg"
    "/var/opt/ignite/config.local"
}
```

7) Check the `INDEX` file with:

```
# /opt/ignite/bin/instl_adm -T
```

8) Ensure that the client and the archive directory are exported via NFS.

```
# /usr/bin/vi /etc/exports

    /var/opt/ignite/clients -anon=2
    /var/opt/ignite/archives/Rel_B.11.00 -ro,anon=2

# /usr/sbin/exportfs -av
```

9) Please see chapter "*Booting and installing an HP-UX client*" to install the client.

Creating a Bootable Golden System Image Tape

!!! Note: Because files like `/etc/hosts` and `devices` files are temporarily removed from the clients system during the execution of `make_sys_image`, the system should not be in use **!!!**

Please repeat step 1) to 4) of chapter "*Creating a Golden System image*".

5) Then copy the config files and edited them correspondingly:

For HP-UX 10.x copy `/opt/ignite/data/examples/core.cfg` to

```
/var/opt/ignite/data/Rel_B.10.20/golden_image_cd.cfg
```

For HP-UX 11.x copy `/opt/ignite/data/examples/core11.cfg` to
`/var/opt/ignite/data/Rel_B.11.00/golden_image_cd.cfg`

Change following in the section `sw_source`:

```
source_type="MT"
change_media=FALSE ← uncomment this line
```

Then comment these lines:

```
# nfs_source = "15.1.54.123:/var/opt/ignite/archives"
# ftp_source = "anonymous@15.1.54.123:iux"
# remsh_source = "user@15.1.54.123"
```

Rename the `archive_path` in the section `init sw_sel "golden image1"`, so it matches the name of the Golden Image:

```
archive_path = "<hostname>.gz"
```

and eventually change the description

```
description = "My Golden System Archive"
```

Get the file system size information of the Golden Image with `archive_impact`:

```
# /opt/ignite/lbin/archive_impact -t -g \  
/var/opt/ignite/archives/Rel_B.11.00/<hostname>.gz
```

Exchange the current sample "impacts" lines of the config file with the output of the `archive_impact` command, for example:

```
impacts = "/" 30 Kb
impacts = "/etc" 1722 Kb
impacts = "/opt" 123430 Kb
...
```

- 6) In the next step an HFS file system needs to be created which is a little larger than the Golden Image:

```
# /usr/sbin/lvcreate -L <image+10%-MB> -n goldenimage /dev/vg00
# /usr/sbin/newfs -F hfs -f 2048 /dev/vg00/rgoldenimage
respectively for an Image > 2GB
# /usr/sbin/newfs -F hfs -f 2048 -o largefiles /dev/vg00/rgoldenimage

# /usr/bin/mkdir /bootcd
# /usr/sbin/mount /dev/vg00/goldenimage /bootcd
# /usr/bin/cp /tmp/<hostname>.gz /bootcd
# /usr/sbin/umount /bootcd
```

- 8) Then create the boot (LIF) header for the tape. For example, create a LIF image based on `/var/opt/ignite/data/Rel_B.11.00/core_archive.cfg`. The LIF image will be named `uxinstlftape`. For further information please see the manpage of `make_medialif`.

```
# /opt/ignite/bin/make_medialif\
-f /opt/ignite/data/Rel_B.11.00/config\
-f /var/opt/ignite/data/Rel_B.11.00/core_archive.cfg\
-l /var/opt/ignite/data/Rel_B.11.00/uxinstlf_tape
```

- 9) The next step would be to write the LIF header and the Golden Image onto tape. Therefore, you have to use a Non-Rewind DDS-1 Device, for example:

```
# /usr/bin/mt -t /dev/rmt/c0t3d0DDS1n rew
# /usr/bin/dd if=/var/opt/ignite/data/Rel_B.11.00/uxinstlf_tape \
of=/dev/rmt/c0t3d0DDS1n obs=2k
# /usr/bin/dd if=/var/opt/ignite/archives/Rel_B.11.00/<hostname>.gz \
of=/dev/rmt/c0t3d0DDS1n obs=10k
# /usr/bin/mt -t /dev/rmt/c0t3d0DDS1n rew
```

- 10) Now you have created a bootable tape. If you install from it, you will receive the "Welcome" screen of the Cold Installation process. You can also change system parameters like file system sizes just as you were used to.

Creating a Bootable Golden System Image CD-ROM

!!! Note: Because files like `/etc/hosts` and devices files are temporarily removed from the clients system during the execution of `make_sys_image`, the system should not be in use **!!!**

Please repeat step 1) to 4) of chapter "*Creating a Golden System image*".

- 5) Then copy the config files and edited them correspondingly:

For HP-UX 10.x copy `/opt/ignite/data/examples/core.cfg` to `/var/opt/ignite/data/Rel_B.10.20/golden_image_cd.cfg`

For HP-UX 11.x copy `/opt/ignite/data/examples/core11.cfg` to `/var/opt/ignite/data/Rel_B.11.00/golden_image_cd.cfg`

Change following in the section `sw_source`:

```
source_type="DSK"
change_media=FALSE ← uncomment this line
```

Then comment these lines:

```
# nfs_source = "15.1.54.123:/var/opt/ignite/archives"
# ftp_source = "anonymous@15.1.54.123:iux"
# remsh_source = "user@15.1.54.123"
```

Rename the `archive_path` in the section `init sw_sel "golden image1"`, so it matches the name of the Golden Image:

```
archive_path = "<hostname>.gz"
```

and eventually change the description

```
description = "My Golden System Archive"
```

Get the file system size information of the Golden Image with `archive_impact`:

```
# /opt/ignite/lbin/archive_impact -t -g \  
  /var/opt/ignite/archives/Rel_B.11.00/<hostname>.gz
```

Exchange the current sample "impacts" lines of the config file with the output of the `archive_impact` command, for example:

```
impacts = "/" 30 Kb  
impacts = "/etc" 1722 Kb  
impacts = "/opt" 123430 Kb  
...
```

- 6) In the next step an HFS file system needs to be created which is a little larger than the Golden Image:

```
# /usr/sbin/lvcreate -L <image+10%-MB> -n goldenimage /dev/vg00  
  
# /usr/sbin/newfs -F hfs -f 2048 /dev/vg00/rgoldenimage  
respectively for an Image > 2GB  
# /usr/sbin/newfs -F hfs -f 2048 -o largefiles /dev/vg00/rgoldenimage  
  
# /usr/bin/mkdir /bootcd  
# /usr/sbin/mount /dev/vg00/goldenimage /bootcd  
# /usr/bin/cp /tmp/<hostname>.gz /bootcd  
# /usr/sbin/umount /bootcd
```

- 7) Then copy the config files and edited them correspondingly:

For HP-UX 10.x copy `/opt/ignite/data/examples/core.cfg` to `/var/opt/ignite/data/Rel_B.10.20/golden_image_cd.cfg`

For HP-UX 11.x copy `/opt/ignite/data/examples/core11.cfg` to `/var/opt/ignite/data/Rel_B.11.00/golden_image_cd.cfg`

Change following in the section `sw_source`:

```
source_type="DSK"  
change_media=FALSE ← uncomment this line
```

Then comment these lines:

```
# nfs_source = "15.1.54.123:/var/opt/ignite/archives"  
# ftp_source = "anonymous@15.1.54.123:iux"  
# remsh_source = "user@15.1.54.123"
```

Rename the `archive_path` in the section `init sw_sel "golden image1"`, so it matches the name of the Golden Image:

```
archive_path = "<hostname>.gz"
```

and eventually change the description

```
description = "My Golden System Archive"
```

Get the file system size information of the Golden Image with `archive_impact`:

```
# /opt/ignite/lbin/archive_impact -t -g \  
  /var/opt/ignite/archives/Rel_B.11.00/<hostname>.gz
```

Exchange the current sample "impacts" lines of the config file with the output of the `archive_impact` command, for example:

```
impacts = "/" 30 Kb  
impacts = "/etc" 1722 Kb  
impacts = "/opt" 123430 Kb  
...
```

- 8) Now create the Boot (LIF) Header for the CD-ROM . For example, create a LIF image based on `/var/opt/ignite/data/Rel_B.11.00/golden_image_cd.cfg`. The LIF image will be named `uxinstlfl_cd`. For further information please see the manpage of `make_medialif`.

```
# /opt/ignite/bin/make_medialif \  
  -f /opt/ignite/data/Rel_B.11.00/config \  
  -f /var/opt/ignite/data/Rel_B.11.00/golden_image_cd.cfg \  
  -l /tmp/uxinstlfl_cd
```

- 9) In the next step an HFS file system needs to be created which is a little larger than the Golden Image:

```
# /usr/sbin/lvcreate -L <image+10%-MB> -n goldenimage /dev/vg00  
  
# /usr/sbin/newfs -F hfs -f 2048 /dev/vg00/rgoldenimage  
respectively for an Image > 2GB  
# /usr/sbin/newfs -F hfs -f 2048 -o largefiles /dev/vg00/rgoldenimage  
  
# /usr/bin/mkdir /bootcd  
# /usr/sbin/mount /dev/vg00/goldenimage /bootcd  
# /usr/bin/cp /tmp/<hostname>.gz /bootcd  
# /usr/sbin/umount /bootcd
```

- 10) Now copy the Golden Image into a `dd` file:

```
# /usr/bin/dd if=/dev/vg00/goldenimage of=/tmp/bootcd_hfs bs=1024k
```

- 11) Now the LIF Image has to be put in front of the Golden Image file:

```
# /opt/ignite/lbin/instl_combine -F /tmp/uxinstlfl_cd \  
  -C /tmp/bootcd_hfs
```

- 12) Now you can burn the Image onto CD-ROM. For this, you can use an CD Writer Utility "CDRecord" at <ftp://ftp.fokus.gmd.de/pub/unix/cdrecord>

```
# cdrecord -v speed=2 dev=1,5,0 /tmp/bootcd_hfs
```

The `dev` syntax depends on the bus, target, LUN – you can look up the values with:

```
# cdrecord -scanbus
```

If you want to test everything before while having the laser burner turned off, you have to call up `cdrecord` with:

```
# cdrecord -dummy -v speed=2 dev=1,5,0 /tmp/bootcd_hfs
```

- 13) The Golden Image CD should now be ready – install from it as it being a Cold Installation Medium – just boot from CD.

Copying a bootable CD-ROM using UNIX

- 1) To copy a CD-ROM, you can use for example the CD Writer Utility "CDRecord" at <ftp://ftp.fokus.gmd.de/pub/unix/cdrecord>.

Insert the original CD-ROM into the drive

```
# cdrecord -toc -dev=1,3,0
first: 1 last 1
track: 1 lba: 0 ( 0) 00:02:00 adr: 1 control: 4 mode: 1
track:lout lba: 306565 ( 1226260) 68:09:40 adr: 1 control: 4 mode: -1
```

- 2) Then eventually insert the CD into a faster drive.

```
# /usr/bin/dd if=/dev/SD_CDRROM of=/image/cdimage.raw bs=2k count=306564
```

Note: one number less! When doing the `dd` there shouldn't be any IO/Error. But there would be an error if you would state 306565.

Insert the blank disk omitting eject

```
# cdrecord -vv -eject -speed=2 -dev=1,3,0 /image/cdimage.raw
```

Additional information

Ignite-UX Administration Guide

<http://docs.hp.com/hpux/onlinedocs/B2355-90704/B2355-90704.html>

Ignite-UX and vPars

If you like to use Ignite-Ux with HP-UX Virtual Partitions (vPars) refer to [vPars chapter](#).