

HP Integrated Lights-Out - Internet Explorer provided by Dell
https://vizaoppcilo.vizaop.com/ilo/index.htm

Server Name: VIZAOPDC
ILO Name: VIZAPOPCILLO
Current User: Gonzalo Isorna

System Status | Remote Console | **Virtual Devices** | Administration

Virtual Power
Power Regulator
Virtual Media
Virtual Indicators
Virtual Serial Port
Virtual Serial Port Configuration

Virtual Serial Port Configuration

Insight Agent | Log out

Internet | Modo protegido: desactivado 100%

HP Integrated Lights-Out - Internet Explorer provided by Dell

Server Name: VIZAPOPCDC
iLO Name: VIZAPOPCILO
Current User: Gonzalo Isorna

Global Settings

Security Settings

- Idle Connection Timeout (minutes): 30
- Enable Lights-Out Functionality: Yes No
- Passthrough Configuration: Enabled Disabled Automatic
- Enable iLO ROM-Based Setup Utility: Yes No
- Require Login for iLO RBSU: Yes No
- Show iLO IP during POST: Yes No
- Remote Console Port Configuration: Enabled (telnet) Disabled Automatic
- Remote Console Data Encryption: Yes No (telnet)
- Enable Remote Console Acquire: Yes No
- SSL Encryption Strength: 128-bit
- Current Cipher: RC4-MD5 with 128 bit encryption
- Web Server Non-SSL Port: 80
- Web Server SSL Port: 443
- Virtual Media Port: 17388
- Remote Console Port: 23
- Terminal Services Port: 3389
- Secure Shell (SSH) Port: 22
- Enable Secure Shell (SSH) Access: Yes No
- Serial Command Line Interface Status: Disabled
- Serial Command Line Interface Speed(bits/second): 9600
- Minimum Password Length: 0
- Remote Keyboard Model: SPANISH

NOTE: The Integrated Lights-Out subsystem must be restarted before any port changes you make on this screen will take effect. Pressing the Apply button below terminates your browser connection and restarts Integrated Lights-Out.

Virtual Serial Port - Internet Explorer provided by Dell

Server Name: VIZAPOPCDC

NOTE: If the operating system application has already started you may need to press 'ENTER' in order to obtain a prompt. Virtual Serial Port functionality can be enabled and configured in RBSU. Please click the Help icon for security information.

```
Virtual Serial Port is not enabled. Use the server RBSU to configure.
```

RC4 Secured (128 Bit)