

SWITCH CONFIGURATION

1810G-8

Network Details	
Protocol Type	<input checked="" type="radio"/> Static <input type="radio"/> DHCP
IP Address	<input type="text" value="10.10.94.10"/> (X.X.X.X)
Subnet Mask	<input type="text" value="255.255.255.0"/>
Gateway Address	<input type="text" value="10.10.94.1"/>
MAC Address	B4:39:D6:C4:FA:F0

Home
 Setup Network

- ▶ Status
- ▶ Network Setup
- ▶ Switching
- ▶ Security
- ▶ Trunks
- ▼ VLANs
 - VLAN Configuration
 - VLAN Ports
 - Participation / Tagging
- ▶ LLDP
- ▶ Diagnostics
- ▶ Maintenance

VLANs ▶ VLAN Configuration

VLAN

Create VLAN

Create VLAN ID (2 - 4093)

Number of VLANs 3

VLAN ID	VLAN NAME	Set Name	Delete VLAN
1	Default	<input type="checkbox"/>	<input type="checkbox"/>
10	Crew	<input type="checkbox"/>	<input type="checkbox"/>
20	Guests	<input type="checkbox"/>	<input type="checkbox"/>

See below:

VLAN 1: Untagged in all ports.

VLAN 10: Tagged in all ports.

VLAN 20: Tagged in all ports.

Home
 Setup Network
 ▶ Status
 ▶ Network Setup
 ▶ Switching
 ▶ Security
 ▶ Trunks
 ▼ VLANs
 VLAN Configuration
 VLAN Ports
 Participation / Tagging
 ▶ LLDP
 ▶ Diagnostics
 ▶ Maintenance

VLANs ▶ Participation / Tagging

VLAN Tagging

VLAN

Tag / Untag / Exclude All

Port	<input type="text" value="1"/> <input type="button" value="U"/>	<input type="text" value="2"/> <input type="button" value="U"/>	<input type="text" value="3"/> <input type="button" value="U"/>	<input type="text" value="4"/> <input type="button" value="U"/>	<input type="text" value="5"/> <input type="button" value="U"/>	<input type="text" value="6"/> <input type="button" value="U"/>	<input type="text" value="7"/> <input type="button" value="U"/>	<input type="text" value="8"/> <input type="button" value="U"/>
------	---	---	---	---	---	---	---	---

Home
 Setup Network
 ▶ Status
 ▶ Network Setup
 ▶ Switching
 ▶ Security
 ▶ Trunks
 ▼ VLANs
 VLAN Configuration
 VLAN Ports
 Participation / Tagging
 ▶ LLDP
 ▶ Diagnostics
 ▶ Maintenance

VLANs ▶ Participation / Tagging

VLAN Tagging

VLAN

Tag / Untag / Exclude All

Port	<input type="text" value="1"/> <input type="button" value="T"/>	<input type="text" value="2"/> <input type="button" value="T"/>	<input type="text" value="3"/> <input type="button" value="T"/>	<input type="text" value="4"/> <input type="button" value="T"/>	<input type="text" value="5"/> <input type="button" value="T"/>	<input type="text" value="6"/> <input type="button" value="T"/>	<input type="text" value="7"/> <input type="button" value="T"/>	<input type="text" value="8"/> <input type="button" value="T"/>
------	---	---	---	---	---	---	---	---

Home
 Setup Network
 ▶ Status
 ▶ Network Setup
 ▶ Switching
 ▶ Security
 ▶ Trunks
 ▼ VLANs
 VLAN Configuration
 VLAN Ports
 Participation / Tagging
 ▶ LLDP
 ▶ Diagnostics
 ▶ Maintenance

VLANs ▶ Participation / Tagging

VLAN Tagging

VLAN

Tag / Untag / Exclude All

Port	<input type="text" value="1"/> <input type="button" value="T"/>	<input type="text" value="2"/> <input type="button" value="T"/>	<input type="text" value="3"/> <input type="button" value="T"/>	<input type="text" value="4"/> <input type="button" value="T"/>	<input type="text" value="5"/> <input type="button" value="T"/>	<input type="text" value="6"/> <input type="button" value="T"/>	<input type="text" value="7"/> <input type="button" value="T"/>	<input type="text" value="8"/> <input type="button" value="T"/>
------	---	---	---	---	---	---	---	---

AP Configuration

HP 530 NA

ProCurve Access Point 530	
System Name	<input type="text"/>
Location	<input type="text"/>
Contact	<input type="text"/>
IP Address	10.10.94.11
MAC Address	00:14:C2:A5:0B:6C
Software Version	WA.01.19
Country Code	US
System Uptime	1 hours 8 mins 38 secs
<input type="button" value="Update"/>	

+ Network Setup
Ethernet

Untagged VLAN

Management VLAN

Speed / Duplex

Connection Type

Static IP Address

Subnet Mask

Default Gateway

DNS Nameservers

Domain

Update

+ Network Setup

Radio

Radio 1

Status On Off

Mode IEEE 802.11g

Max Tx Power 18.0 dBm

Tx Power Reduction 0 (0-18dB)

Channel Auto

Maximum Stations 256 (0-256)

Advanced Settings

Radio 2

Status On Off

Mode IEEE 802.11a

Max Tx Power 18.0 dBm

Tx Power Reduction 0 (0-18dB)

Channel Auto

Maximum Stations 256 (0-256)

Advanced Settings

+ Network Setup

WLANs

WLAN	Radio		SSID	Closed System	VLAN ID	Security	
	1	2					
1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	SSID 1 testing	<input type="checkbox"/>	10	wpa-psk	<input type="button" value="Edit"/>
2	<input type="checkbox"/>	<input checked="" type="checkbox"/>	SSID 2 testing	<input type="checkbox"/>	20	wpa-psk	<input type="button" value="Edit"/>
3	<input type="checkbox"/>	<input type="checkbox"/>	SSID 3	<input type="checkbox"/>		no-security	<input type="button" value="Edit"/>
4	<input type="checkbox"/>	<input type="checkbox"/>	SSID 4	<input type="checkbox"/>		no-security	<input type="button" value="Edit"/>
5	<input type="checkbox"/>	<input type="checkbox"/>	SSID 5	<input type="checkbox"/>		no-security	<input type="button" value="Edit"/>