Bottom enclosure

```
┌─────────────────────────────────────────────────────────────────────────┐
│ dsf - HyperTerminal                                              _ □ X    │
├───────────────────────────────────────────────────────────────────────────┤
│ File  Edit  View  Call  Transfer  Help                                    │
├───────────────────────────────────────────────────────────────────────────┤
│ [icons]                                                                    │
├───────────────────────────────────────────────────────────────────────────┤
│ Power Supply Status              Power Management Module Uptime:028083674 │
│ lqqqqwqqqqqwqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqwqqqqqqwqqqqqqqqqqqqqqqqqk  │
│ xSlotx FW  x Status: OV=Over Voltage, OC=Over Current,x  Power  x Temperature  x │
│ x  # x Ver.x  OT=Over Temp, PFAIL=Power Supply Failed x  Used   x Input Output x │
│ tqqqnqqqqqnqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqnqqqqqqqnqqqqqqwqqqqqqqqu  │
│ x  1 x 1.7 x Present - Power Good                     x  255W x  22C x   30C x │
│ x  2 x 1.7 x Present - Power Good                     x  306W x  21C x   30C x │
│ x  3 x 1.7 x Present - Power Good                     x  255W x  21C x   29C x │
│ x  4 x 1.7 x Present - Power Good                     x  306W x  21C x   31C x │
│ x  5 x 1.7 x Present - Power Good                     x  204W x  20C x   27C x │
│ x  6 x 1.7 x Present - Power Good                     x  306W x  23C x   31C x │
│ tqqqvqqqqvqqqqqqqqqqqqqqqqqqqqwqqqqqqqqqqqqqqqqqqqqvqqqqqqqqnqqqqqvqqqqqqqu  │
│ x Mode: Primary Power Source    x Enclosure Power Used:    1785W x Backplane    x │
│ x Faults:  0 (See Faults page) x Zone Power Allocated:    5169W x Temperature  x │
│ x UID LED: Off                 x                                tqqqqqqqqqqqqqqu │
│ x Topology: OK                 x Power Zone Setting:         3  x A Side:  31C x │
│ tqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqvqqqqqqqqqqqqqqqqqqqqqqqqqqu Center:   33C x │
│ x                                                              x B Side:  31C x │
│ x Press "R" for detailed redundancy info                      tqqqqqqqqqqqqqqu │
│ x                                                              x Version:v2.40x │
│ x                                                              x          x    │
│ mqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqvqqqqqqqqqqqqqqqqj  │
│                                                                            │
│     H=Help E=Set Serial Number F=Faults R=Redundancy S=Rack Space=Redraw   │
├───────────────────────────────────────────────────────────────────────────┤
│ Connected 00:07:02   VT100J   9600 8-N-1   SCROLL  CAPS  NUM  Capture  Print echo │
└─────────────────────────────────────────────────────────────────────────┘
```

Bottom enclosure

```
┌─────────────────────────────────────────────────────────────────────────┐
│ dsf - HyperTerminal                                              _ □ X    │
├───────────────────────────────────────────────────────────────────────────┤
│ File  Edit  View  Call  Transfer  Help                                    │
├───────────────────────────────────────────────────────────────────────────┤
│ [icons]                                                                    │
├───────────────────────────────────────────────────────────────────────────┤
│ Rack Status                      Power Management Module Uptime:028083699 │
│ lqqqqqqqqqqqqqqqqqqqqqqqqqqwqqqqqqqqqqqqqqqqqqqwqqqqqqqqqwqqqqqqqwqqqqqqqqqqqqqqqqqqk │
│ x Description              x Serial           x Power   x Power x           x │
│ x                         x Number           x Alloc.  x Zone  x           x │
│ tqqqqqqqqqqqqqqqqqqqqqqqqqnqqqqqqqqqqqqqqqqqqqnqqqqqqqqqnqqqqqqqnqqqqqqqqqqqqqqqqqqu │
│ x Blade Enclosure         x [████████]        x 1754W x  3  x           x │
│ x Blade Enclosure         x [████████]        x 1705W x  3  x           x │
│ x Blade Enclosure         x [████████]        x 1710W x  3  x           x │
│ x Power Enclosure         x [████████]        x N/A   x  3  x           x │
│ x Power Enclosure         x [████████]        x N/A   x  3  x           x │
│ tqqqqqqqqqqqqqqqqqqqqqqqqqvqqqqqqqqqqqqqqqqqqqvqqqqqqqqqvqqqqqqqvqqqqqqqqqqqqqqqqqqu │
│ x               Total power allocated:    5169W                           x │
│ x                                                                         x │
│ x                                                                         x │
│ x                                                                         x │
│ x                                                                         x │
│ x                                                                         x │
│ x                                                                         x │
│ x                                                                         x │
│ x                                                                         x │
│ tqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqu │
│ x Enclosure Link Speed:    4 frames/second                                x │
│ mqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj │
│                                                                            │
│     H=Help M=Main E=Set Serial Number F=Faults R=Redundancy Space=Redraw   │
├───────────────────────────────────────────────────────────────────────────┤
│ Connected 00:07:27   VT100J   9600 8-N-1   SCROLL  CAPS  NUM  Capture  Print echo │
└─────────────────────────────────────────────────────────────────────────┘
```

Bottom enclosure

```
dsf - HyperTerminal

File  Edit  View  Call  Transfer  Help

 Redundant Status                Power Management Module Uptime:028083720
qqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqq
 ICMB    A     BOTH    B
 98D1    998   240    516   z-class chassis
 80F6   1261   240    204   z-class chassis
 A475    958   240    512   z-class chassis      lqqqqqqq redundancy key qqqqqqqqqqk
 4CBB  >8721<        >8721< power chassis        xXXXX = not PS redundant          x
 425D  >8721<        >8721< power chassis        xXXXX = not bus bar redundant     x
                                                 xXXXX = not pwr. encl. redundant  x
                                                 mqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqj




Power 17442      17442 Total Power Available =        17442
ZLoad  3217       1232 Total Power Consumed =          5169
PLoad   720        720 Total Shared Power Consumed =    720
To Go 13505      15490
0           |        |         |       A         |          |      17442
----------------
0           |        |         |       B         |          |      17442
---------
                H=Help M=Main E=Set Serial Number F=Faults S=Rack Space=Redraw

Connected 00:07:49    VT100J    9600 8-N-1   SCROLL   CAPS   NUM   Capture   Print echo
```

Top enclosure

```
dsf - HyperTerminal

File  Edit  View  Call  Transfer  Help

 Power Supply Status             Power Management Module Uptime:028083514
lqqqqwqqqqqwqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqwqqqqqqqqqwqqqqqqqqqqqqqqqqqk
xSlotx FW  x Status: OV=Over Voltage, OC=Over Current,x  Power   x Temperature    x
x  #  x Ver.x  OT=Over Temp, PFAIL=Power Supply Failed x  Used   x Input Output   x
tqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqwqqqqqqqqqqqqwqqqqqqqqqqqqqqqu
x  1 x 1.7 x Present - Power Good                      x    306W x  21C x   30C x
x  2 x 1.7 x Present - Power Good                      x    153W x  20C x   28C x
x  3 x 1.7 x Present - Power Good                      x    153W x  21C x   29C x
x  4 x 1.7 x Present - Power Good                      x    153W x  20C x   27C x
x  5 x 1.7 x Present - Power Good                      x    204W x  21C x   29C x
x  6 x 1.7 x Present - Power Good                      x    204W x  22C x   29C x
tqqqqqvqqqqqvqqqqqqqqqqqqqqqqqqqqqqqqqwqqqqqqqqqqqqqqqqqvqqqqqqqqqqqnqqqqqvqqqqqqqqqqqu
x Mode: Secondary Power Source x Enclosure Power Used:   1377W x Backplane       x
x Faults:  0 (See Faults page) x Total Power information is   x Temperature    x
x UID LED: Off                 x only available in Primary or tqqqqqqqqqqqqqqqqu
x Topology: OK                 x Split power source modes     x A Side:  29C x
tqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqvqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqu Center:  31C x
x                                                              x B Side:  31C x
x Press "R" for detailed redundancy info                      tqqqqqqqqqqqqqqqqu
x                                                              x Version:v2.40x
x                                                              x            x
mqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqqvqqqqqqqqqqqqqqqqqqqqqj

            H=Help E=Set Serial Number F=Faults R=Redundancy S=Rack Space=Redraw

Connected 00:08:19    VT100J    9600 8-N-1   SCROLL   CAPS   NUM   Capture   Print echo
```