

HP TippingPoint

TippingPoint Operating System MIB Guide

TippingPoint Operating System 3.2

Abstract

This document is a reference guide for the TippingPoint Operating System MIBs.



5998-1407

Part number: 5998-1407
Third edition: November 2011

Legal and notice information

© Copyright 2010-2011 Hewlett-Packard Development Company, L.P.

Hewlett-Packard Company makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

This document contains proprietary information, which is protected by copyright. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard. The information is provided "as is" without warranty of any kind and is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

TippingPoint®, the TippingPoint logo, and Digital Vaccine® are registered trademarks of Hewlett-Packard. All other company and product names may be trademarks of their respective holders. All rights reserved. This document contains confidential information, trade secrets or both, which are the property of Hewlett-Packard. No part of this documentation may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from Hewlett-Packard or one of its subsidiaries.

Adobe® and Acrobat® are trademarks of Adobe Systems Incorporated.

Intel and Itanium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Microsoft, Windows, Windows NT, and Windows XP are U.S. registered trademarks of Microsoft Corporation.

Oracle® is a registered U.S. trademark of Oracle Corporation, Redwood City, California.

UNIX® is a registered trademark of The Open Group.

Printed in the US.

TippingPoint Operating System MIB Guide TippingPoint Operating System 3.2

Table of Contents

NMS and MIBs	1
Overview	1
Enabling NMS Communication	1
Using the IPS MIBs	2
TIPPINGPOINT-REG-MIB	2
TPT-COMPACT-FLASH	2
TPT-DDOS	3
TPT-HEALTH	12
TPT-HIGH-AVAIL	16
TPT-HOST	20
TPT-LICENSE	21
TPT-MISC-NOTIFY	22
TPT-MULTIDV	26
TPT-NPSTATS	27
TPT-POLICY	29
TPT-PORT-CONFIG	40
TPT-PORT-MAPPING	41
TPT-RESOURCE	42
TPT-SMSMIBS	48
TPT-SMS-TRAP-MIB	48
TPT-TPA-HARDWARE	50
TPT-TPAMIBS	57
TPT-TRAFFIC	58
TPT-TSE	64
Using HP OpenView With IPS MIBs	68
Loading TippingPoint Enterprise MIBs	68
MIB Application Builder	68
Discovering the IPS	69
Creating Graphs with Application Builder	69

List of Tables

NMS and MIBs	1
Table A-1 - TIPPINGPOINT-REG-MIB sub-trees	2
Table A-2 - Compact Flash data objects	2
Table A-3 - Compact Flash notification objects	3
Table A-4 - Rejected SYN objects	3
Table A-5 - Proxied connections objects	5
Table A-6 - Rejected connections Per Second (CPS) objects	6
Table A-7 - Accepted connections Per Second (CPS) objects	8
Table A-8 - Rejected connections Per Second (EST) objects	9
Table A-9 - Accepted connections Per Second (EST) objects	11
Table A-10 - Temperature objects	12
Table A-11 - Fan objects	13
Table A-12 - Fan objects	14
Table A-13 - Fan objects	15
Table A-14 - Global high availability objects	16
Table A-15 - Intrinsic Network HA notification objects	18
Table A-16 - Transparent HA notification objects	19
Table A-17 - ZPHA notification objects	19
Table A-18 - Performance Protection state change notification objects	19
Table A-19 - IP address table objects	20
Table A-20 - License objects	21
Table A-21 - General notification objects	22
Table A-22 - Management notification objects	22
Table A-23 - Log file rollover notifications	22
Table A-24 - Discovery notifications	23
Table A-25 - System log notifications	24
Table A-26 - Quarantine notifications	25
Table A-27 - Congestion threshold notifications	25
Table A-28 - Installed DV objects	26
Table A-29 - Auxiliary DV objects	26
Table A-30 - Network processor statistics rules table objects	27
Table A-31 - Network processor tier statistics objects	27
Table A-32 - Other network processor objects	28
Table A-33 - Policy notification objects	29
Table A-34 - Policy log notification objects	32
Table A-35 - Policy variable objects	33
Table A-36 - Digital Vaccine variable objects	33
Table A-37 - Per-policy variable objects	34
Table A-38 - Top Ten Policies table objects	34
Table A-39 - Alerts by severity table objects	34
Table A-40 - Alerts by protocol table objects	35
Table A-41 - Alerts by zone table objects	35
Table A-42 - Permits by zone table objects	36
Table A-43 - Blocks by zone table objects	36
Table A-44 - P2P by zone table objects	37
Table A-45 - Frames by size table objects	37
Table A-46 - Frames by type table objects	38
Table A-47 - Packets by protocol table objects	38
Table A-48 - Port statistics table objects	39
Table A-49 - Policy name and description table objects	39
Table A-50 - Security zone pair information and statistics table objects	39
Table A-51 - Port configuration settings objects	40
Table A-52 - Port configuration settings objects	41

Table A-53 - Resource notification objects	42
Table A-54 - File system information objects	43
Table A-55 - Memory information objects	44
Table A-56 - CPU information objects	44
Table A-57 - Chassis temperature information objects	45
Table A-58 - Power supply information objects	46
Table A-59 - System log count objects	46
Table A-60 - System metric objects	47
Table A-61 - System information objects	47
Table A-62 - SMS top level MIBs	48
Table A-63 - SMS conformance top level MIBs	48
Table A-64 - SMS notification top level MIBs	48
Table A-65 - Model number objects	48
Table A-66 - SMS Notification MIBs	48
Table A-67 - SMS MIB Variables	49
Table A-68 - Hardware objects	50
Table A-69 - Hardware notification objects	51
Table A-70 - Port objects	51
Table A-71 - Chassis data objects	52
Table A-72 - Fan objects	53
Table A-73 - Power supply objects	55
Table A-74 - Power entry objects	56
Table A-75 - TPA top level MIBs	57
Table A-76 - Conformance top level MIBs	57
Table A-77 - Notification top level MIBs	57
Table A-78 - Model Numbers	58
Table A-79 - Temperature objects	58
Table A-80 - Rate Limiter objects	59
Table A-81 - Traffic threshold objects	60
Table A-82 - Temperature objects	62
Table A-83 - Adaptive Filter Configuration objects	64
Table A-84 - Connection blocks table objects	64
Table A-85 - Rate limit streams table objects	65
Table A-86 - Connection Trusts table objects	66

NMS and MIBs

Overview

This guide describes how to configure the TippingPoint system for management by Network Management Systems (NMS), a common term for SNMP management systems. It includes the following sections:

- “Enabling NMS Communication” on page 1
- “Using the IPS MIBs” on page 2
 - “TIPPINGPOINT-REG-MIB” on page 2
 - “TPT-COMPACT-FLASH” on page 2
 - “TPT-DDOS” on page 3
 - “TPT-HEALTH” on page 12
 - “TPT-HIGH-AVAIL” on page 16
 - “TPT-HOST” on page 20
 - “TPT-LICENSE” on page 21
 - “TPT-MISC-NOTIFY” on page 22
 - “TPT-MULTIDV” on page 26
 - “TPT-NPSTATS” on page 27
 - “TPT-POLICY” on page 29
 - “TPT-PORT-CONFIG” on page 40
 - “TPT-PORT-MAPPING” on page 41
 - “TPT-RESOURCE” on page 42
 - “TPT-SMSMIBS” on page 48
 - “TPT-SMS-TRAP-MIB” on page 48
 - “TPT-TPA-HARDWARE” on page 50
 - “TPT-TPAMIBS” on page 57
 - “TPT-TRAFFIC” on page 58
 - “TPT-TSE” on page 64
- “Using HP OpenView With IPS MIBs” on page 68

NOTE: The MIB files are available in a .zip file and can be downloaded from the TippingPoint TMC at <https://tmc.tippingpoint.com>.

Enabling NMS Communication

Before you begin, you must enable NMS communication on the IPS. In the Command Line Interface (CLI), use the `conf t nms` command to configure the SNMP trap port number (default 162), and the community string. Once you have entered this information, your NMS can manage TippingPoint IPS devices. For detailed information about the `CONF T NMS` command, refer to the *TippingPoint Command Line Interface Reference*.

If the IPS does not permit you to configure the NMS settings, the device may be under SMS management. Use the `CONF T NO SMS` command to disable SMS management before continuing.

Using the IPS MIBs

This section describes the MIB files available for the IPS. You can download a .zip file containing the complete MIB files from the TMC at <https://tmc.tippingpoint.com>.

TIPPINGPOINT-REG-MIB

Defines the OID sub-tree assigned to TippingPoint by the Internet Assigned Numbers Agency (IANA), as well as sub-trees for registered modules, object and event definitions, agent profiles, management application requirements, and experimental definitions.

NOTE: This MIB file must be loaded before you load any other TippingPoint MIB files.

Table A-1 TIPPINGPOINT-REG-MIB sub-trees

Object	OID	Description
tpt-reg	1.3.6.1.4.1.10734.1	Sub-tree for the registered modules.
tpt-generic	1.3.6.1.4.1.10734.2	Sub-tree for common object and event definitions.
tpt-products	1.3.6.1.4.1.10734.3	Sub-tree for specific object and event definitions.
tpt-caps	1.3.6.1.4.1.10734.4	Sub-tree for agent profiles.
tpt-reqs	1.3.6.1.4.1.10734.5	Sub-tree for management application requirements.
tpt-expr	1.3.6.1.4.1.10734.6	Sub-tree for experimental definitions.

TPT-COMPACT-FLASH

Defines the status and operating mode of the compact flash card

Table A-2 Compact Flash data objects

Object	OID	Description
tpt-compact-flash	1.3.6.1.4.1.10734.3.3.2.14	Sub-tree for all compact flash information.
compactFlashPresent	1.3.6.1.4.1.10734.3.3.2.14.1	Indicates compact flash presence. <ul style="list-style-type: none">• 0: present• 1: absent
compactFlashMounted	1.3.6.1.4.1.10734.3.3.2.14.2	Indicates compact flash mount status. <ul style="list-style-type: none">• 0: mounted• 1: unmounted
compactFlashFormatted	1.3.6.1.4.1.10734.3.3.2.14.3	Indicates compact flash format status. <ul style="list-style-type: none">• 0: formatted• 1: unformatted

Table A-2 Compact Flash data objects

Object	OID	Description
compactFlashOperationMode	1.3.6.1.4.1.10734.3.3.2.14.4	Indicates compact flash operation mode. <ul style="list-style-type: none"> 0: secure mode—requires authentication 1: auto-mount enabled—compact flash cards are automatically mounted when inserted
vendorInformation	1.3.6.1.4.1.10734.3.3.2.14.5	Sub-tree of compact flash informational details.
serialNumber	1.3.6.1.4.1.10734.3.3.2.14.5.1	Compact Flash serial number.
model	1.3.6.1.4.1.10734.3.3.2.14.5.2	Compact Flash model name.
capacity	1.3.6.1.4.1.10734.3.3.2.14.5.3	Compact Flash capacity.
revision	1.3.6.1.4.1.10734.3.3.2.14.5.4	Compact Flash firmware revision.

The following notifications and SNMP traps send information about the compact flash.

Table A-3 Compact Flash notification objects

Object	OID	Description
tptCompactFlashDeviceID	1.3.6.1.4.1.10734.3.3.3.1.261	The unique identifier of the device sending this notification.
tptCompactFlashDeviceStatus	1.3.6.1.4.1.10734.3.3.3.1.262	Compact flash status notification.
tptCFInsertedNotify	1.3.6.1.4.1.10734.3.3.3.0.51	Notification indicating that a compact flash card was inserted.
tptCFEjectedNotify	1.3.6.1.4.1.10734.3.3.3.0.52	Notification indicating that a compact flash card was removed.

TPT-DDOS

Defines the conditions and actions for DDoS and SYN Proxy.

SYN Proxy Filter Statistics

Rejected SYNs.

Table A-4 Rejected SYNs objects

Object	OID	Description
rejectSynHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.9.5	Historical (sampled) data every second for a minute.
rejectSynHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.9.5.1	An entry in the rejected SYNs per second history seconds table. Rows cannot be created or deleted.
rejectSynHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.9.5.1.1	The global identifier of a DDoS filter group.
rejectSynHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.9.5.1.2	The index (0-59) of the second.

Table A-4 Rejected SYNs objects

Object	OID	Description
rejectSynHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.9.5.1.3	The count of filter-specific units matching the criteria for this filter in the specified second.
rejectSynHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.9.5.1.4	The time SecondsUnitCount was updated (in seconds since January 1, 1970).
rejectSynHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.9.6	Historical (sampled) data every minute for an hour.
rejectSynHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.9.6.1	An entry in the rejected SYNs per minute history seconds table. Rows cannot be created or deleted.
rejectSynHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.9.6.1.1	The global identifier of a DDoS filter group.
rejectSynHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.9.6.1.2	The index (0-59) of the minute.
rejectSynHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.9.6.1.3	The average of the SecondsUnitCount values corresponding to this minute.
rejectSynHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.9.6.1.4	The time MinutesUnitCount was updated (in seconds since January 1, 1970).
rejectSynHistHoursTable	1.3.6.1.4.1.10734.3.3.2.9.7	Historical (sampled) data every hour for a day.
rejectSynHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.9.7.1	An entry in the rejected SYNs per hours history seconds table. Rows cannot be created or deleted.
rejectSynHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.9.7.1.1	The global identifier of a DDoS filter group.
rejectSynHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.9.7.1.2	The index (0-23) of the hour.
rejectSynHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.9.7.1.3	The average of the MinutesUnitCount values corresponding to this hour.
rejectSynHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.9.7.1.4	The time HoursUnitCount was updated (in seconds since January 1, 1970).
rejectSynHistDaysTable	1.3.6.1.4.1.10734.3.3.2.9.8	Historical (sampled) data every day for 35 days.
rejectSynHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.9.8.1	An entry in the rejected SYNs per days history seconds table. Rows cannot be created or deleted.
rejectSynHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.9.8.1.1	The global identifier of a DDoS filter group.
rejectSynHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.9.8.1.2	The index (0-34) of the day.

Table A-4 Rejected SYNs objects

Object	OID	Description
rejectSynHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.9.8.1.3	The average of the HoursUnitCount values corresponding to this day.
rejectSynHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.9.8.1.4	The time DaysUnitCount was updated (in seconds since January 1, 1970).

Proxied connections

Table A-5 Proxied connectionsobjects

Object	OID	Description
proxyConnHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.9.9	Historical (sampled) data every second for a minute.
proxyConnHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.9.9.1	An entry in the proxied connections per second history seconds table. Rows cannot be created or deleted.
proxyConnHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.9.9.1.1	The global identifier of a DDoS filter group.
proxyConnHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.9.9.1.2	The index (0-59) of the second.
proxyConnHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.9.9.1.3	The count of filter-specific units matching the criteria for this filter in the specified second.
proxyConnHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.9.9.1.4	The time SecondsUnitCount was updated (in seconds since January 1, 1970).
proxyConnHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.9.10	Historical (sampled) data every minute for an hour.
proxyConnHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.9.10.1	An entry in the proxied connections per minute history seconds table. Rows cannot be created or deleted.
proxyConnHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.9.10.1.1	The global identifier of a DDoS filter group.
proxyConnHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.9.10.1.2	The index (0-59) of the minute.
proxyConnHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.9.10.1.3	The average of the SecondsUnitCount values corresponding to this minute.
proxyConnHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.9.10.1.4	The time MinutesUnitCount was updated (in seconds since January 1, 1970).
proxyConnHistHoursTable	1.3.6.1.4.1.10734.3.3.2.9.11	Historical (sampled) data every hour for a day.

Table A-5 Proxied connectionsobjects

Object	OID	Description
proxyConnHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.9.11.1	An entry in the proxied connections per hours history seconds table. Rows cannot be created or deleted.
proxyConnHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.9.11.1.1	The global identifier of a DDoS filter group.
proxyConnHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.9.11.1.2	The index (0-23) of the hour.
proxyConnHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.9.11.1.3	The average of the MinutesUnitCount values corresponding to this hour.
proxyConnHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.9.11.1.4	The time HoursUnitCount was updated (in seconds since January 1, 1970).
proxyConnHistDaysTable	1.3.6.1.4.1.10734.3.3.2.9.12	Historical (sampled) data every day for 35 days.
proxyConnHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.9.12.1	An entry in the proxied connections per days history seconds table. Rows cannot be created or deleted.
proxyConnHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.9.12.1.1	The global identifier of a DDoS filter group.
proxyConnHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.9.12.1.2	The index (0-34) of the day.
proxyConnHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.9.12.1.3	The average of the HoursUnitCount values corresponding to this day.
proxyConnHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.9.12.1.4	The time DaysUnitCount was updated (in seconds since January 1, 1970).

CPS Filter Statistics

Rejected Connections Per Second (CPS)

Table A-6 Rejected connections Per Second (CPS) objects

Object	OID	Description
rejectCpsHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.9.15	Historical (sampled) data every second for a minute.
rejectCpsHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.9.15.1	An entry in the rejected connections per second (CPS) per second history seconds table. Rows cannot be created or deleted.
rejectCpsHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.9.15.1.1	The global identifier of a DDoS filter group.
rejectCpsHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.9.15.1.2	The index (0-59) of the second.

Table A-6 Rejected connections Per Second (CPS) objects

Object	OID	Description
rejectCpsHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.9.15.1.3	The count of filter-specific units matching the criteria for this filter in the specified second.
rejectCpsHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.9.15.1.4	The time SecondsUnitCount was updated (in seconds since January 1, 1970).
rejectCpsHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.9.16	Historical (sampled) data every minute for an hour.
rejectCpsHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.9.16.1	An entry in the rejected connections per second (CPS) per minute history seconds table. Rows cannot be created or deleted.
rejectCpsHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.9.16.1.1	The global identifier of a DDoS filter group.
rejectCpsHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.9.16.1.2	The index (0-59) of the minute.
rejectCpsHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.9.16.1.3	The average of the SecondsUnitCount values corresponding to this minute.
rejectCpsHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.9.16.1.4	The time MinutesUnitCount was updated (in seconds since January 1, 1970).
rejectCpsHistHoursTable	1.3.6.1.4.1.10734.3.3.2.9.17	Historical (sampled) data every hour for a day.
rejectCpsHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.9.17.1	An entry in the rejected connections per second (CPS) per hours history seconds table. Rows cannot be created or deleted.
rejectCpsHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.9.17.1.1	The global identifier of a DDoS filter group.
rejectCpsHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.9.17.1.2	The index (0-23) of the hour.
rejectCpsHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.9.17.1.3	The average of the MinutesUnitCount values corresponding to this hour.
rejectCpsHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.9.17.1.4	The time HoursUnitCount was updated (in seconds since January 1, 1970).
rejectCpsHistDaysTable	1.3.6.1.4.1.10734.3.3.2.9.18	Historical (sampled) data every day for 35 days.
rejectCpsHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.9.18.1	An entry in the rejected connections per second (CPS) per days history seconds table. Rows cannot be created or deleted.
rejectCpsHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.9.18.1.1	The global identifier of a DDoS filter group.

Table A-6 Rejected connections Per Second (CPS) objects

Object	OID	Description
rejectCpsHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.9.18.1.2	The index (0-34) of the day.
rejectCpsHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.9.18.1.3	The average of the HoursUnitCount values corresponding to this day.
rejectCpsHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.9.18.1.4	The time DaysUnitCount was updated (in seconds since January 1, 1970).

Accepted Connections Per Second (CPS)

Table A-7 Accepted connections Per Second (CPS) objects

Object	OID	Description
acceptCpsHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.9.19	Historical (sampled) data every second for a minute.
acceptCpsHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.9.19.1	An entry in the accepted connections per second (CPS) per second history seconds table. Rows cannot be created or deleted.
acceptCpsHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.9.19.1.1	The global identifier of a DDoS filter group.
acceptCpsHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.9.19.1.2	The index (0-59) of the second.
acceptCpsHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.9.19.1.3	The count of filter-specific units matching the criteria for this filter in the specified second.
acceptCpsHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.9.19.1.4	The time SecondsUnitCount was updated (in seconds since January 1, 1970).
acceptCpsHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.9.20	Historical (sampled) data every minute for an hour.
acceptCpsHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.9.20.1	An entry in the accepted connections per second (CPS) per minute history seconds table. Rows cannot be created or deleted.
acceptCpsHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.9.20.1.1	The global identifier of a DDoS filter group.
acceptCpsHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.9.20.1.2	The index (0-59) of the minute.
acceptCpsHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.9.20.1.3	The average of the SecondsUnitCount values corresponding to this minute.
acceptCpsHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.9.20.1.4	The time MinutesUnitCount was updated (in seconds since January 1, 1970).
acceptCpsHistHoursTable	1.3.6.1.4.1.10734.3.3.2.9.21	Historical (sampled) data every hour for a day.

Table A-7 Accepted connections Per Second (CPS) objects

Object	OID	Description
acceptCpsHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.9.21.1	An entry in the accepted connections per second (CPS) per hours history seconds table. Rows cannot be created or deleted.
acceptCpsHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.9.21.1.1	The global identifier of a DDoS filter group.
acceptCpsHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.9.21.1.2	The index (0-23) of the hour.
acceptCpsHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.9.21.1.3	The average of the MinutesUnitCount values corresponding to this hour.
acceptCpsHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.9.21.1.4	The time HoursUnitCount was updated (in seconds since January 1, 1970).
acceptCpsHistDaysTable	1.3.6.1.4.1.10734.3.3.2.9.22	Historical (sampled) data every day for 35 days.
acceptCpsHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.9.22.1	An entry in the accepted connections per second (CPS) per days history seconds table. Rows cannot be created or deleted.
acceptCpsHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.9.22.1.1	The global identifier of a DDoS filter group.
acceptCpsHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.9.22.1.2	The index (0-34) of the day.
acceptCpsHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.9.22.1.3	The average of the HoursUnitCount values corresponding to this day.
acceptCpsHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.9.22.1.4	The time DaysUnitCount was updated (in seconds since January 1, 1970).

EST Filter Statistics

Rejected Connections Per Second (EST)

Table A-8 Rejected connections Per Second (EST) objects

Object	OID	Description
rejectEstHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.9.25	Historical (sampled) data every second for a minute.
rejectEstHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.9.25.1	An entry in the rejected connections per second (EST) per second history seconds table. Rows cannot be created or deleted.
rejectEstHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.9.25.1.1	The global identifier of a DDoS filter group.
rejectEstHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.9.25.1.2	The index (0-59) of the second.

Table A-8 Rejected connections Per Second (EST) objects

Object	OID	Description
rejectEstHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.9.25.1.3	The count of filter-specific units matching the criteria for this filter in the specified second.
rejectEstHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.9.25.1.4	The time SecondsUnitCount was updated (in seconds since January 1, 1970).
rejectEstHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.9.26	Historical (sampled) data every minute for an hour.
rejectEstHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.9.26.1	An entry in the rejected connections per second (EST) per minute history seconds table. Rows cannot be created or deleted.
rejectEstHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.9.26.1.1	The global identifier of a DDoS filter group.
rejectEstHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.9.26.1.2	The index (0-59) of the minute.
rejectEstHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.9.26.1.3	The average of the SecondsUnitCount values corresponding to this minute.
rejectEstHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.9.26.1.4	The time MinutesUnitCount was updated (in seconds since January 1, 1970).
rejectEstHistHoursTable	1.3.6.1.4.1.10734.3.3.2.9.27	Historical (sampled) data every hour for a day.
rejectEstHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.9.27.1	An entry in the rejected connections per second (EST) per hours history seconds table. Rows cannot be created or deleted.
rejectEstHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.9.27.1.1	The global identifier of a DDoS filter group.
rejectEstHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.9.27.1.2	The index (0-23) of the hour.
rejectEstHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.9.27.1.3	The average of the MinutesUnitCount values corresponding to this hour.
rejectEstHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.9.27.1.4	The time HoursUnitCount was updated (in seconds since January 1, 1970).
rejectEstHistDaysTable	1.3.6.1.4.1.10734.3.3.2.9.28	Historical (sampled) data every day for 35 days.
rejectEstHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.9.28.1	An entry in the rejected connections per second (EST) per days history seconds table. Rows cannot be created or deleted.
rejectEstHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.9.28.1.1	The global identifier of a DDoS filter group.

Table A-8 Rejected connections Per Second (EST) objects

Object	OID	Description
rejectEstHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.9.28.1.2	The index (0-34) of the day.
rejectEstHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.9.28.1.3	The average of the HoursUnitCount values corresponding to this day.
rejectEstHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.9.28.1.4	The time DaysUnitCount was updated (in seconds since January 1, 1970).

Accepted Connections Per Second (EST)

Table A-9 Accepted connections Per Second (EST) objects

Object	OID	Description
acceptEstHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.9.29	Historical (sampled) data every second for a minute.
acceptEstHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.9.29.1	An entry in the accepted connections per second (EST) per second history seconds table. Rows cannot be created or deleted.
acceptEstHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.9.29.1.1	The global identifier of a DDoS filter group.
acceptEstHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.9.29.1.2	The index (0-59) of the second.
acceptEstHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.9.29.1.3	The count of filter-specific units matching the criteria for this filter in the specified second.
acceptEstHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.9.29.1.4	The time SecondsUnitCount was updated (in seconds since January 1, 1970).
acceptEstHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.9.30	Historical (sampled) data every minute for an hour.
acceptEstHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.9.30.1	An entry in the accepted connections per second (EST) per minute history seconds table. Rows cannot be created or deleted.
acceptEstHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.9.30.1.1	The global identifier of a DDoS filter group.
acceptEstHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.9.30.1.2	The index (0-59) of the minute.
acceptEstHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.9.30.1.3	The average of the SecondsUnitCount values corresponding to this minute.
acceptEstHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.9.30.1.4	The time MinutesUnitCount was updated (in seconds since January 1, 1970).
acceptEstHistHoursTable	1.3.6.1.4.1.10734.3.3.2.9.31	Historical (sampled) data every hour for a day.

Table A-9 Accepted connections Per Second (EST) objects

Object	OID	Description
acceptEstHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.9.31.1	An entry in the accepted connections per second (EST) per hours history seconds table. Rows cannot be created or deleted.
acceptEstHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.9.31.1.1	The global identifier of a DDoS filter group.
acceptEstHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.9.31.1.2	The index (0-23) of the hour.
acceptEstHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.9.31.1.3	The average of the MinutesUnitCount values corresponding to this hour.
acceptEstHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.9.31.1.4	The time HoursUnitCount was updated (in seconds since January 1, 1970).
acceptEstHistDaysTable	1.3.6.1.4.1.10734.3.3.2.9.32	Historical (sampled) data every day for 35 days.
acceptEstHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.9.32.1	An entry in the accepted connections per second (EST) per days history seconds table. Rows cannot be created or deleted.
acceptEstHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.9.32.1.1	The global identifier of a DDoS filter group.
acceptEstHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.9.32.1.2	The index (0-34) of the day.
acceptEstHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.9.32.1.3	The average of the HoursUnitCount values corresponding to this day.
acceptEstHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.9.32.1.4	The time DaysUnitCount was updated (in seconds since January 1, 1970).

TPT-HEALTH

Indicates the health status of the IPS. Features monitored temperatures, fan speeds, and voltage levels. The TPT-HEALTH MIB includes the following objects.

Temperature

The Temperature objects monitor the device temperature. Alarms will be generated when the temperature at a sensor passes a specified threshold.

Table A-10 Temperature objects

Object	OID	Description
healthTempTable	1.3.6.1.4.1.10734.3.3.2.13.1	A table listing the readings at the device temperature sensors.
healthTempEntry	1.3.6.1.4.1.10734.3.3.2.13.1.1	An entry in the temperature table. Rows are predefined and cannot be created or deleted.
healthTempIndex	1.3.6.1.4.1.10734.3.3.2.13.1.1.1	The index number of the entry.

Table A-10 Temperature objects

Object	OID	Description
healthTempChannel	1.3.6.1.4.1.10734.3.3.2.13.1.1.2	The location of the temperature sensor. For the N-Platform, this is always at the device center.
healthTempValue	1.3.6.1.4.1.10734.3.3.2.13.1.1.3	The temperature in degrees centigrade.
healthTempSeverity	1.3.6.1.4.1.10734.3.3.2.13.1.1.4	May be one of the following values: <ul style="list-style-type: none"> • 0: normal • 1: informational note • 2: minor • 3: major • 4: critical
healthTempThresholdType	1.3.6.1.4.1.10734.3.3.2.13.1.1.5	Determines the application of thresholds. <ul style="list-style-type: none"> • minimum (1): Value should not go below threshold. • range (2): Value should remain with a designated range. • maximum (3): value should not go above threshold.
healthTempMajor	1.3.6.1.4.1.10734.3.3.2.13.1.1.6	The major threshold temperature in degrees centigrade.
healthTempCritical	1.3.6.1.4.1.10734.3.3.2.13.1.1.7	The critical threshold temperature in degrees centigrade.

Fans

The Fan objects monitor the fan performance and health.

Table A-11 Fan objects

Object	OID	Description
healthFanTable	1.3.6.1.4.1.10734.3.3.2.13.2	A table listing all fans inside the device.
healthFanEntry	1.3.6.1.4.1.10734.3.3.2.13.2 .1	An entry in the fans table. Rows are predefined and cannot be created or deleted.
healthFanIndex	1.3.6.1.4.1.10734.3.3.2.13.2 .1.1	The index number of the entry.
healthFanChannel	1.3.6.1.4.1.10734.3.3.2.13.2 .1.2	A string identifying the fan.
healthFanValue	1.3.6.1.4.1.10734.3.3.2.13.2 .1.3	The speed of the fan in RPM.

Table A-11 Fan objects

Object	OID	Description
healthFanSeverity	1.3.6.1.4.1.10734.3.3.2.13.2 .1.4	May be one of the following values: <ul style="list-style-type: none"> • 0: normal • 1: informational note • 2: minor • 3: major • 4: critical
healthFanThresholdType	1.3.6.1.4.1.10734.3.3.2.13.2 .1.5	Determines the application of thresholds. <ul style="list-style-type: none"> • minimum (1): Value should not go below threshold. • range (2): Value should remain with a designated range. • maximum (3): value should not go above threshold.
healthFanMajor	1.3.6.1.4.1.10734.3.3.2.13.2 .1.6	The major threshold speed in RPM.
healthFanMinor	1.3.6.1.4.1.10734.3.3.2.13.2 .1.7	The critical threshold speed in RPM.

Voltage

The Voltage objects monitor the voltage levels at various locations within the device.

Table A-12 Fan objects

Object	OID	Description
healthVoltageTable	1.3.6.1.4.1.10734.3.3.2.13.3	A table listing all voltages at various locations inside the device.
healthVoltageEntry	1.3.6.1.4.1.10734.3.3.2.13.3 .1	An entry in the voltage table. Rows are predefined and cannot be created or deleted.
healthVoltageIndex	1.3.6.1.4.1.10734.3.3.2.13.3 .1.1	The index number of the entry.
healthVoltageChannel	1.3.6.1.4.1.10734.3.3.2.13.3 .1.2	The location of the voltage sensor.
healthVoltageValue	1.3.6.1.4.1.10734.3.3.2.13.3 .1.3	The voltage reading in millivolts.
healthVoltageSeverity	1.3.6.1.4.1.10734.3.3.2.13.3 .1.4	May be one of the following values: <ul style="list-style-type: none"> • 0: normal • 1: informational note • 2: minor • 3: major • 4: critical

Table A-12 Fan objects

Object	OID	Description
healthVoltageThresholdType	1.3.6.1.4.1.10734.3.3.2.13.3 .1.5	Determines the application of thresholds. <ul style="list-style-type: none"> • minimum (1): Value should not go below threshold. • range (2): Value should remain with a designated range. • maximum (3): value should not go above threshold.
healthVoltageMajor	1.3.6.1.4.1.10734.3.3.2.13.3 .1.6	The major threshold delta above or below the nominal voltage value, in millivolts.
healthVoltageMinor	1.3.6.1.4.1.10734.3.3.2.13.3 .1.7	The critical threshold delta above or below the nominal voltage value, in millivolts.
healthVoltageNominal	1.3.6.1.4.1.10734.3.3.2.13.3 .1.8	The optimal voltage value at this sensor location.

I2C

The I2C objects monitor the I2C bus timeouts.

Table A-13 Fan objects

Object	OID	Description
healthI2CTable	1.3.6.1.4.1.10734.3.3.2.13.4	A table listing all I2C bus timeouts.
healthI2CEntry	1.3.6.1.4.1.10734.3.3.2.13.4 .1	An entry in the I2C table. Rows are predefined and cannot be created or deleted.
healthI2CIndex	1.3.6.1.4.1.10734.3.3.2.13.4 .1.1	The index number of the entry.
healthI2CChannel	1.3.6.1.4.1.10734.3.3.2.13.4 .1.2	Description of the I2C bus.
healthI2CValue	1.3.6.1.4.1.10734.3.3.2.13.4 .1.3	The number of timeouts on this I2C bus since the device was booted.
healthI2CSeverity	1.3.6.1.4.1.10734.3.3.2.13.4 .1.4	Indicates whether the number of I2C bus timeouts is acceptable or excessive. May be one of the following values: <ul style="list-style-type: none"> • 0: normal • 1: informational note • 2: minor • 3: major • 4: critical

Table A-13 Fan objects

Object	OID	Description
healthI2CThresholdType	1.3.6.1.4.1.10734.3.3.2.13.4 .1.5	Determines the application of thresholds. <ul style="list-style-type: none"> • minimum (1): Value should not go below threshold. • range (2): Value should remain with a designated range. • maximum (3): value should not go above threshold.
healthI2CMajor	1.3.6.1.4.1.10734.3.3.2.13.4 .1.6	The major threshold number of I2C bus timeouts.
healthI2CMinor	1.3.6.1.4.1.10734.3.3.2.13.4 .1.7	The critical threshold number of I2C bus timeouts.

TPT-HIGH-AVAIL

Defines the conditions and actions for Intrinsic Network HA, Transparent Network HA, and Zero-Power HA, and also offers information about the current fault state of the device.

Table A-14 Global high availability objects

Object	OID	Description
highAvailTimeStamp	1.3.6.1.4.1.10734.3.3.2.6.1	The last transition of the fault state in seconds since January 1, 1970. The value is zero if the fault state has not changed since the last reboot.
highAvailFaultState	1.3.6.1.4.1.10734.3.3.2.6.2	The current fault state of the device: <ul style="list-style-type: none"> • 0: normal • 1: fallback
highAvailFaultCause	1.3.6.1.4.1.10734.3.3.2.6.3	The reason for the current fault state: <ul style="list-style-type: none"> • 0: none • 1: suspended task • 2: out of memory • 3: hardware breaking point • 4: TSE failure • 5: watchdog timeout • 6: user reset • 7: user-initiated fallback • 8: threshold failure • 9: software watchdog timeout • 10: OAM fault • 11: hard disk disabled

Table A-14 Global high availability objects

Object	OID	Description
highAvailThresholdEnabled	1.3.6.1.4.1.10734.3.3.2.6.4	The current Layer-2 Fallback (L2FB) threshold-enabled setting for the device.
highAvailThresholdPercent	1.3.6.1.4.1.10734.3.3.2.6.5	If the fallback threshold is enabled, the percent packet loss at which the device is configured to enter L2FB.
highAvailEnabled	1.3.6.1.4.1.10734.3.3.2.6.6	Indicates whether intrinsic network HA has been enabled.
highAvailTransparentState	1.3.6.1.4.1.10734.3.3.2.6.7	State of the connection to the device's transparent HA partner: <ul style="list-style-type: none"> • 0: not connected • 1: unresponsive • 2: connected
highAvailTransparentEnabled	1.3.6.1.4.1.10734.3.3.2.6.8	Indicates whether transparent HA has been enabled.
highAvailTransparentPartner	1.3.6.1.4.1.10734.3.3.2.6.9	Network address of the device's transparent HA partner.
highAvailZeroPowerState	1.3.6.1.4.1.10734.3.3.2.6.10	The current ZPHA state.
highAvailZeroPowerQuantity	1.3.6.1.4.1.10734.3.3.2.6.11	The number of segments with ZPHA modules.
highAvailZeroPowerTable	1.3.6.1.4.1.10734.3.3.2.6.12	Table of segments with ZPHA modules.
highAvailZeroPowerEntry	1.3.6.1.4.1.10734.3.3.2.6.12.1	An entry in the ZPHA table.
highAvailZeroPowerIndex	1.3.6.1.4.1.10734.3.3.2.6.12.1.1	The index number of the entry.
highAvailZeroPowerSegment	1.3.6.1.4.1.10734.3.3.2.6.12.1.2	The name of the segment on which ZPHA is enabled.
highAvailZeroPowerActive	1.3.6.1.4.1.10734.3.3.2.6.12.1.3	The current ZPHA state of the segment: <ul style="list-style-type: none"> • 0: normal, ZPHA inactive • 1: IPS bypass, ZPHA active
highAvailZeroPowerAction	1.3.6.1.4.1.10734.3.3.2.6.12.1.4	The action taken when ZPHA is active: <ul style="list-style-type: none"> • 0: unknown • 1: normal • 2: bypass

Table A-14 Global high availability objects

Object	OID	Description
highAvailZeroPowerMode	1.3.6.1.4.1.10734.3.3.2.6.12.1.5	The fiber mode of this ZPHA: <ul style="list-style-type: none"> • 0: unknown • 2: single • 3: multi
highAvailZeroPowerPresence	1.3.6.1.4.1.10734.3.3.2.6.13	Indicates ZPHA presence: <ul style="list-style-type: none"> • 0: present • 1: absent

The following notifications and SNMP traps apply to Intrinsic Network HA.

Table A-15 Intrinsic Network HA notification objects

Object	OID	Description
tptlhaNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.81	The unique identifier of the device sending the notification.
tptlhaNotifyTimeStamp	1.3.6.1.4.1.10734.3.3.3.1.82	The timestamp of the notification in seconds since January 1, 1970.
tptlhaNotifyFaultState	1.3.6.1.4.1.10734.3.3.3.1.83	The current fault state of the device: <ul style="list-style-type: none"> • 0: normal • 1: fallback
tptlhaNotifyFaultCause	1.3.6.1.4.1.10734.3.3.3.1.84	The reason for the current fault state: <ul style="list-style-type: none"> • 0: none • 1: suspended task • 2: out of memory • 3: hardware breaking point • 4: TSE failure • 5: watchdog timeout • 6: user reset • 7: user-initiated fallback • 8: threshold failure • 9: software watchdog timeout • 10: OAM fault • 11: hard disk disabled
tptlhaNotify	1.3.6.1.4.1.10734.3.3.3.0.15	The notification object that informs the management station of changes in the intrinsic HA fault state of the device.

The following notifications and SNMP traps apply to Transparent Network HA.

Table A-16 Transparent HA notification objects

Object	OID	Description
tptTrhaNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.86	The unique identifier of the device sending the notification.
tptTrhaNotifyTimeStamp	1.3.6.1.4.1.10734.3.3.3.1.87	The timestamp of the notification in seconds since January 1, 1970.
tptTrhaNotifyNewState	1.3.6.1.4.1.10734.3.3.3.1.88	State of the connection to the device's transparent HA partner: <ul style="list-style-type: none"> • 0: not connected • 1: unresponsive • 2: connected
tptTrhaNotify	1.3.6.1.4.1.10734.3.3.3.0.18	The notification object that informs the management station of changes in the transparent HA state of the device.

The following notifications and SNMP traps apply to Zero-Power HA (ZPHA).

Table A-17 ZPHA notification objects

Object	OID	Description
tptZphaNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.161	The unique identifier of the device sending the notification.
tptZphaNotifyTimeStamp	1.3.6.1.4.1.10734.3.3.3.1.162	The timestamp of the notification in seconds since January 1, 1970.
tptZphaNotifySegmentName	1.3.6.1.4.1.10734.3.3.3.1.163	The name of the segment on which ZPHA is enabled.
tptZphaNotifyNewState	1.3.6.1.4.1.10734.3.3.3.1.164	The current ZPHA state of the segment: <ul style="list-style-type: none"> • 0: normal, ZPHA inactive • 1: IPS bypass, ZPHA active
tptZphaNotify	1.3.6.1.4.1.10734.3.3.3.0.24	The notification object that informs the management station of changes in the ZPHA state of the device.

The following notifications and SNMP traps apply to changes in the Performance Protection state.

Table A-18 Performance Protection state change notification objects

Object	OID	Description
tptPerfProtNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.141	The unique identifier of the device sending the notification.
tptPerfProtNotifyTimeStamp	1.3.6.1.4.1.10734.3.3.3.1.142	The timestamp of the notification in seconds since January 1, 1970.

Table A-18 Performance Protection state change notification objects

Object	OID	Description
tptPerfProtNotifyPhase	1.3.6.1.4.1.10734.3.3.3.1.143	Indicates the current performance protection mode: <ul style="list-style-type: none"> • 1: entering • 2: continuing • 3: exiting
tptPerfProtNotifyPacketLoss	1.3.6.1.4.1.10734.3.3.3.1.144	The current packet loss rate per thousand. When exiting performance protection mode, the value will always be zero (0).
tptPerfProtNotifyLossThreshold	1.3.6.1.4.1.10734.3.3.3.1.145	The current packet loss threshold per thousand.
tptPerfProtNotifyDuration	1.3.6.1.4.1.10734.3.3.3.1.146	The number of seconds that performance protection will be active.
tptPerfProtNotifyMissedAlerts	1.3.6.1.4.1.10734.3.3.3.1.147	The number of alerts missed during the performance protection period. When exiting performance protection mode, the value will always be zero (0).
tptPerfProtNotify	1.3.6.1.4.1.10734.3.3.3.0.21	The notification object that informs the management station of changes in the performance protection mode of the device.

TPT-HOST

Defines the IPS host information, the default gateway address, and indicates whether the device is currently configured for service access.

Table A-19 IP address table objects

Object	OID	Description
hostIpTable	1.3.6.1.4.1.10734.3.3.2.12.1	Table of IP addresses on the device and their attributes.
hostIpEntry	1.3.6.1.4.1.10734.3.3.2.12.1.1	An entry in the host IP address table. Rows cannot be added or deleted.
hostIpIndex	1.3.6.1.4.1.10734.3.3.2.12.1.1.1	The index number of the entry.
hostIpAddress	1.3.6.1.4.1.10734.3.3.2.12.1.1.2	IP address in CIDR format.
hostIpType	1.3.6.1.4.1.10734.3.3.2.12.1.1.3	Indicates whether the address is IPv4 or IPv6 and how it was configured.
hostIpActive	1.3.6.1.4.1.10734.3.3.2.12.1.1.4	Whether the address is active.
hostIPv4Gateway	1.3.6.1.4.1.10734.3.3.2.12.2	The IPv4 default gateway.
hostIPv6Gateway	1.3.6.1.4.1.10734.3.3.2.12.3	The IPv6 default gateway.
hostIPv6Enabled	1.3.6.1.4.1.10734.3.3.2.12.5	Indicates whether IPv6 is enabled on the device.

Table A-19 IP address table objects

Object	OID	Description
hostIPv6AutoConfig	1.3.6.1.4.1.10734.3.3.2.12.5	Indicates whether IPv6 automatic configuration is enabled on the device.
hostFipsCfgMode	1.3.6.1.4.1.10734.3.3.2.12.6	Indicates the FIPS mode that is enabled on the device.
hostFipsActive	1.3.6.1.4.1.10734.3.3.2.12.7	The currently active FIPS mode.
hostSSLCert	1.3.6.1.4.1.10734.3.3.2.12.8	The currently active SSL cert.
hostInitState	1.3.6.1.4.1.10734.3.3.2.12.9	The current host initialization state.

TPT-LICENSE

Support for TippingPoint license packages, including TOS, Digital Vaccine, Reputation DV, and other services.

Table A-20 license objects

Object	OID	Description
licenseTable	1.3.6.1.4.1.10734.3.3.2.15.1	Table of licensed features.
licenseEntry	1.3.6.1.4.1.10734.3.3.2.15.1.1	An entry in the licensed features table. Rows cannot be added or deleted.
licenseEntryIndex	1.3.6.1.4.1.10734.3.3.2.15.1.1.1	The index number of the entry.
licenseEntryFeature	1.3.6.1.4.1.10734.3.3.2.15.1.1.2	The name of the licensed feature.
licenseEntryStatus	1.3.6.1.4.1.10734.3.3.2.15.1.1.3	Status of the licensed feature: <ul style="list-style-type: none"> • 0: informational message • 1: license valid • 2: warning • 3: error
licenseEntryAction	1.3.6.1.4.1.10734.3.3.2.15.1.1.4	Action to take for the licensed feature.
licenseEntryExpiry	1.3.6.1.4.1.10734.3.3.2.15.1.1.5	The date on which this licensed feature will expire.
licenseEntryDetails	1.3.6.1.4.1.10734.3.3.2.15.1.1.6	Any additional information about this licensed feature.

TPT-MISC-NOTIFY

Notifications and SNMP traps for logs and other features.

NOTE: The MIB file includes references to Network Discovery Scan. This feature is not currently supported on the TippingPoint N-Platform.

This object applies to all notifications.

Table A-21 General notification objects

Object	OID	Description
tptMiscNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.31	The unique identifier of the device sending the notification. This is the first payload parameter for all notifications in the TPT-MISC-NOTIFY module.

The following notifications and SNMP traps communicate with the management station.

Table A-22 Management notification objects

Object	OID	Description
tptManagedNotify	1.3.6.1.4.1.10734.3.3.3.0.9	Informs the management station that the device is now being managed by that station.
tptUnmanagedNotify	1.3.6.1.4.1.10734.3.3.3.0.10	Informs the management station that the device is no longer being managed by that station.

Log File Rollover Notifications

The following notifications and SNMP traps are generated when the log file rolls over.

Table A-23 Log file rollover notifications

Object	OID	Description
tptRolloverNotify	1.3.6.1.4.1.10734.3.3.3.0.11	Informs the management station that a log file has rolled over.
tptRolloverNotifyFileType	1.3.6.1.4.1.10734.3.3.3.1.32	The type of log file that has rolled over. <ul style="list-style-type: none">• 0: system• 1: audit• 2: fault• 3: alert• 4: block• 5: peer
tptRolloverNotifyMaxFiles	1.3.6.1.4.1.10734.3.3.3.1.33	The maximum number of files maintained for this type of log file.

Table A-23 Log file rollover notifications

Object	OID	Description
tptRolloverNotifyNumFiles	1.3.6.1.4.1.10734.3.3.3.1.34	The number of files that have rolled over.
tptRolloverNotifyTime	1.3.6.1.4.1.10734.3.3.3.1.35	The rollover time of most recent file pertaining to this notification, in seconds since January 1, 1970.

Network Discovery Notifications

These notifications are generated by network discovery scans.

Table A-24 Discovery notifications

Object	OID	Description
tptDiscoveryNotifyStartStop	1.3.6.1.4.1.10734.3.3.3.0.12	The notification that indicates whether a network discovery scan has started or stopped.
tptDiscoveryNotifyNewHost	1.3.6.1.4.1.10734.3.3.3.0.13	The notification that indicates that a previously unknown host was discovered by a scan.
tptDiscoveryNotifyScanID	1.3.6.1.4.1.10734.3.3.3.1.42	The unique ID of the scan pertaining to this notification.
tptDiscoveryNotifySegmentName	1.3.6.1.4.1.10734.3.3.3.1.43	The name of the scanned segment.
tptDiscoveryNotifyScanRange	1.3.6.1.4.1.10734.3.3.3.1.44	The network address range requested in the scan.
tptDiscoveryNotifyDelta	1.3.6.1.4.1.10734.3.3.3.1.45	An indication of whether discovery results changed from the previous scan. This parameter is undefined if the notification indicates the start of a scan. <ul style="list-style-type: none"> • 1: changed • 2: unchanged
tptDiscoveryNotifyNewHosts	1.3.6.1.4.1.10734.3.3.3.1.46	The number of new hosts found by this scan. This parameter is undefined at the start of a scan.
tptDiscoveryNotifyChanged	1.3.6.1.4.1.10734.3.3.3.1.47	The number of hosts for which this scan found different results from the previous scans. This parameter is undefined at the start of a scan.
tptDiscoveryNotifyUnchanged	1.3.6.1.4.1.10734.3.3.3.1.48	The number of hosts for which this scan found the same results as the previous scans. This parameter is undefined at the start of a scan.

Table A-24 Discovery notifications

Object	OID	Description
tptDiscoveryNotifyNotFound	1.3.6.1.4.1.10734.3.3.3.1.49	The number of hosts found by a previous scan, but not by this scan. This parameter is undefined at the start of a scan.
tptDiscoveryNotifyUnknown	1.3.6.1.4.1.10734.3.3.3.1.50	The number of address scanned for where no host was found and for which there was no previous scan data. This parameter is undefined at the start of a scan.
tptDiscoveryNotifyStartTime	1.3.6.1.4.1.10734.3.3.3.1.51	The start time of the scan in seconds since January 1, 1970.
tptDiscoveryNotifyStopTime	1.3.6.1.4.1.10734.3.3.3.1.52	The stop time of the scan in seconds since January 1, 1970.
tptDiscoveryNotifyErrorText	1.3.6.1.4.1.10734.3.3.3.1.53	If the current scan terminated abnormally, this string describes the error condition. The string is empty if the scan terminated normally.
tptDiscoveryNotifyHostNetAddr	1.3.6.1.4.1.10734.3.3.3.1.54	The network address of the newly discovered host.
tptDiscoveryNotifyHostDeviceID	1.3.6.1.4.1.10734.3.3.3.1.55	The unique device identifier of the newly discovered host.
tptDiscoveryNotifySchedID	1.3.6.1.4.1.10734.3.3.3.1.56	The scheduled scan identifier, if applicable.

System Log Notifications

The following notifications and SNMP traps are generated when a critical message, error message, or warning is logged in the system log.

Table A-25 System log notifications

Object	OID	Description
tptSystemLogNotify	1.3.6.1.4.1.10734.3.3.3.0.16	The notification that a critical message, error message, or warning has been logged.
tptSystemLogNotifyText	1.3.6.1.4.1.10734.3.3.3.1.92	The text of the message being logged.
tptSystemLogNotifySequence	1.3.6.1.4.1.10734.3.3.3.1.93	The log file entry sequence number corresponding to this notification.
tptSystemLogNotifySeverity	1.3.6.1.4.1.10734.3.3.3.1.94	The severity of the attack: <ul style="list-style-type: none"> • 1: critical • 2: error • 4: warning

Table A-25 System log notifications

Object	OID	Description
tptSystemLogNotifyTimeSec	1.3.6.1.4.1.10734.3.3.3.1.95	The time that this message was logged, in seconds since January 1, 1970.
tptSystemLogNotifyTimeNano	1.3.6.1.4.1.10734.3.3.3.1.96	The nanoseconds portion of tptSystemLogNotifyTimeSec.

Quarantine Notifications

The following notifications and SNMP traps are generated by quarantine actions.

Table A-26 Quarantine notifications

Object	OID	Description
tptQuarantineNotify	1.3.6.1.4.1.10734.3.3.3.0.20	The notification that indicates that a host has been added to or removed from the quarantine list.
tptQuarantineNotifyNetAddr	1.3.6.1.4.1.10734.3.3.3.1.132	The network address of the host being quarantined or removed from the quarantine list.
tptQuarantineNotifyHostNetAddrV6	1.3.6.1.4.1.10734.3.3.3.1.133	The IPv6 network address of the host.
tptQuarantineNotifyReason	1.3.6.1.4.1.10734.3.3.3.1.134	The reason that the host was quarantined. The parameter is undefined if the host was removed.
tptQuarantineNotifySegmentName	1.3.6.1.4.1.10734.3.3.3.1.135	The segment related to the quarantine or removal from the quarantine list.
tptQuarantineNotifyAction	1.3.6.1.4.1.10734.3.3.3.1.136	Whether the host was added to or removed from the quarantine list. <ul style="list-style-type: none"> • 1: add • 2: remove

Congestion Notifications

The following notifications and SNMP traps are generated when congestion thresholds are met.

Table A-27 Congestion threshold notifications

Object	OID	Description
tptCongestionPacketLoss	1.3.6.1.4.1.10734.3.3.3.1.153	The current packet loss rate per thousand.
tptCongestionNotifyPhase	1.3.6.1.4.1.10734.3.3.3.1.154	Indicates whether the device is entering, continuing, or exiting congestion threshold mode.
tptCongestionThreshold	1.3.6.1.4.1.10734.3.3.3.1.155	The current packet loss threshold per thousand.
tptTier3CongestionPacketLoss	1.3.6.1.4.1.10734.3.3.3.1.156	The current Tier 3 packet loss rate per thousand.

Table A-27 Congestion threshold notifications

Object	OID	Description
tptTier3CongestionNotifyPhase	1.3.6.1.4.1.10734.3.3.3.1.157	Indicates whether the device is entering, continuing, or exiting Tier 3 congestion threshold mode.
tptTier3CongestionThreshold	1.3.6.1.4.1.10734.3.3.3.1.158	The current Tier 3 packet loss threshold per thousand.
tptCongestionThresholdNotify	1.3.6.1.4.1.10734.3.3.3.0.25	The notification that the device-wide congestion has reached the configured congestion threshold.
tptiTier3CongestionNotify	1.3.6.1.4.1.10734.3.3.3.0.26	The notification that the Tier 3 congestion has reached the configured congestion threshold.

TPT-MULTIDV

Manages the Multiple Digital Vaccine feature. This feature allows the IPS to manage multiple types of Digital Vaccine packages, if they are currently available from TippingPoint.

Table A-28 Installed DV objects

Object	OID	Description
installedDVTable	1.3.6.1.4.1.10734.3.3.2.1.10.2.1	Table of installed Digital Vaccine (DV) packages.
installedDVEntry	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1	An entry in the Installed DV table. Rows cannot be added or removed.
installedDVIndex	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.1	The index number of the entry.
installedDVVersion	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.2	The installed DV version in string format: MAJOR.MINOR.PATCH.BUILD
installedDVIsActive	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.3	Indicates whether the DV is active. <ul style="list-style-type: none"> • 0: inactive • 1: active

Table A-29 Auxiliary DV objects

Object	OID	Description
auxiliaryDVTable	1.3.6.1.4.1.10734.3.3.2.1.10.2.1	Table of auxiliary Digital Vaccine (DV) packages.
auxiliaryDVEntry	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1	An entry in the Auxiliary DV table. Rows cannot be added or removed.
auxiliaryDVIndex	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.1	The index number of the entry.

Table A-29 Auxiliary DV objects

Object	OID	Description
auxiliaryDVType	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.2	The type of the auxiliary DV.
auxiliaryDVName	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.3	The name of the auxiliary DV.
auxiliaryDVVersion	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.4	The auxiliary DV version number.
auxiliaryDVPackage	1.3.6.1.4.1.10734.3.3.2.1.10.2.1.1.5	The auxiliary DV version in string format: major.minor.patch.build

TPT-NPSTATS

Lists network processor (NP) tier statistics.

The following objects apply to the NP statistics rules table.

Table A-30 Network processor statistics rules table objects

Object	OID	Description
npstatsRulesTable	1.3.6.1.4.1.10734.3.3.2.10.1	A table of network processor statistics, sorted in descending order of the number of flows.
npstatsRulesEntry	1.3.6.1.4.1.10734.3.3.2.10.1.1	An entry in the network processor statistics rules table. Rows cannot be added or deleted.
npstatsRulesRank	1.3.6.1.4.1.10734.3.3.2.10.1.1	The numerical ranking in the table.
npstatsRulesFilter	1.3.6.1.4.1.10734.3.3.2.10.1.2	The filter number.
npstatsRulesFlows	1.3.6.1.4.1.10734.3.3.2.10.1.3	The number of flows that have triggered the filter.
npstatsRulesSuccess	1.3.6.1.4.1.10734.3.3.2.10.1.4	The number of times the filter has been successfully matched.
npstatsRulesTotalPercent	1.3.6.1.4.1.10734.3.3.2.10.1.5	The number of flows that have triggered this filter as a percentage of all flows through the device.
npstatsRulesSuccessPer10K	1.3.6.1.4.1.10734.3.3.2.10.1.6	The number of filter matches for every 10,000 flows triggered.

The following objects apply to the NP tier statistics.

Table A-31 Network processor tier statistics objects

Object	OID	Description
npstatsTiersTable	1.3.6.1.4.1.10734.3.3.2.10.2	A table of network processor statistics, sorted by tier.
npstatsTiersEntry	1.3.6.1.4.1.10734.3.3.2.10.2.1	An entry in the network processor statistics tiers table.

Table A-31 Network processor tier statistics objects

Object	OID	Description
npstatsTierNumber	1.3.6.1.4.1.10734.3.3.2.10.2.1.1	The tier number.
npstatsTiersReceiveMbps	1.3.6.1.4.1.10734.3.3.2.10.2.1.2	The current receive rate on the tier in Mbps.
npstatsTiersTransmitMbps	1.3.6.1.4.1.10734.3.3.2.10.2.1.3	The current transmit rate on the tier in Mbps.
npstatsTiersRxPktsPerSec	1.3.6.1.4.1.10734.3.3.2.10.2.1.4	The current receive rate in packets per second.
npstatsTiersMaxPktsPerSec	1.3.6.1.4.1.10734.3.3.2.10.2.1.5	The maximum receive rate in packets per second.
npstatsTiersAvgBytesPerPkt	1.3.6.1.4.1.10734.3.3.2.10.2.1.6	The average packet size in bytes.
npstatsTiersUtilizationPercent	1.3.6.1.4.1.10734.3.3.2.10.2.1.7	The percent utilization of this tier.
npstatsTiersTiersRatioToNextPer10K	1.3.6.1.4.1.10734.3.3.2.10.2.1.8	The ratio of this tier's throughput to the next per 10,000.
npstatsTiersMaxReceiveMbps	1.3.6.1.4.1.10734.3.3.2.10.2.1.9	The maximum receive rate in Mbps
npstatsTiersMaxTransmitMbps	1.3.6.1.4.1.10734.3.3.2.10.2.1.10	The maximum transmit rate in Mbps.

The following objects apply to other NP statistics.

Table A-32 Other network processor objects

Object	OID	Description
npstatsTiersExtra	1.3.6.1.4.1.10734.3.3.2.10.3	A list of additional network processor statistics information.
npstatsTier1BypassMbps	1.3.6.1.4.1.10734.3.3.2.10.3.1	The current bypass rate in Mbps.
npstatsTier1Balance	1.3.6.1.4.1.10734.3.3.2.10.3.2	The A:B load balance. A value of 1000 is exactly balanced, and 0 indicates all traffic is being handled on one processor.
npstatsTier1MaxPktsPerSecA	1.3.6.1.4.1.10734.3.3.2.10.3.3	The maximum processor A receive rate in packets per second.
npstatsTier1MaxPktsPerSecB	1.3.6.1.4.1.10734.3.3.2.10.3.4	The maximum processor B receive rate in packets per second. Processor B is only available on the TippingPoint 2500N and 5100N.
npstatsTier1TxPktsPerSec	1.3.6.1.4.1.10734.3.3.2.10.3.8	The transmit rate in packets per second.
npstatsTier1MaxTxPktsPerSec	1.3.6.1.4.1.10734.3.3.2.10.3.9	The maximum transmit rate in packets per second.
npstatsTier4TriggerMatchPer1000	1.3.6.1.4.1.10734.3.3.2.10.3.5	Proportion of traffic inspected because of a trigger match (percent value times 100).

Table A-32 Other network processor objects

Object	OID	Description
npstatsTier4ReroutePer1000	1.3.6.1.4.1.10734.3.3.2.10.3.6	Proportion of traffic inspected because of a reroute (percent value times 100).
npstatsTier4TcpSequencePer1000	1.3.6.1.4.1.10734.3.3.2.10.3.7	Proportion of traffic inspected because of TCP sequence (percent value times 100).
npstatsMisc	1.3.6.1.4.1.10734.3.3.2.10.4	Miscellaneous network processor statistical information.
npstatsMiscTxPktsBestEffort	1.3.6.1.4.1.10734.3.3.2.10.4.1	The number of packets transmitted due to best effort mode.

TPT-POLICY

Defines variable definitions, Digital Vaccine information, reports, policy information, and policy notification information.

Policy Notifications

The following notifications and SNMP traps are generated by policy actions.

Table A-33 Policy notification objects

Object	OID	Description
tptPolicyNotify	1.3.6.1.4.1.10734.3.3.3.0.8	The notification that a policy action has resulted from a signature match.
tptPolicyNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.11	The unique identifier of the device sending the policy notification.
tptPolicyNotifyPolicyID	1.3.6.1.4.1.10734.3.3.3.1.12	The unique identifier of the policy that causes the notification.
tptPolicyNotifySignatureID	1.3.6.1.4.1.10734.3.3.3.1.13	The unique identifier of the signature matching the incoming data stream.
tptPolicyNotifySegmentName	1.3.6.1.4.1.10734.3.3.3.1.14	The name of the segment to which the notification applies.
tptPolicyNotifySrcNetAddr	1.3.6.1.4.1.10734.3.3.3.1.15	The IPv4 address of the source of the packet that triggered the policy action.
tptPolicyNotifySrcNetAddrV6	1.3.6.1.4.1.10734.3.3.3.1.128	The IPv6 address of the source of the packet that triggered the policy action.
tptPolicyNotifySrcNetPort	1.3.6.1.4.1.10734.3.3.3.1.16	The source port of the packet that triggered the policy action.
tptPolicyNotifyDestNetAddr	1.3.6.1.4.1.10734.3.3.3.1.17	The IPv4 address of the destination of the packet that triggered the policy action.

Table A-33 Policy notification objects

Object	OID	Description
tptPolicyNotifyDestNetAddrV6	1.3.6.1.4.1.10734.3.3.3.1.129	The IPv6 address of the destination of the packet that triggered the policy action.
tptPolicyNotifyDestNetPort	1.3.6.1.4.1.10734.3.3.3.1.18	The destination port of the packet that triggered the policy action.
tptPolicyNotifyStartTimeSec	1.3.6.1.4.1.10734.3.3.3.1.19	The time at which the policy was first triggered, marking the start of the aggregation period for this notification. Measured in seconds since January 1, 1970.
tptPolicyNotifyAlertAction	1.3.6.1.4.1.10734.3.3.3.1.20	The action associated with this notification. <ul style="list-style-type: none"> • 1: deny • 2: allow
tptPolicyNotifyConfigAction	1.3.6.1.4.1.10734.3.3.3.1.21	The action configured for the policy, which in some cases may differ from the action associated with the notification. <ul style="list-style-type: none"> • 1: deny • 2: allow
tptPolicyNotifyComponentID	1.3.6.1.4.1.10734.3.3.3.1.22	The component identifier of the policy that causes the notification: <ul style="list-style-type: none"> • 0: invalid • 1: deny • 2: allow • 7: alert • 8: block • 9: peer
tptPolicyNotifyHitCount	1.3.6.1.4.1.10734.3.3.3.1.23	The number of policy hits occurring during the aggregation period for this notification.
tptPolicyNotifyAggregationPeriod	1.3.6.1.4.1.10734.3.3.3.1.24	The duration of the aggregation period for this notification, in minutes.
tptPolicyNotifySeverity	1.3.6.1.4.1.10734.3.3.3.1.25	The severity of the attack. <ul style="list-style-type: none"> • 1: warning • 2: minor • 3: major • 4: critical

Table A-33 Policy notification objects

Object	OID	Description
tptPolicyNotifyProtocol	1.3.6.1.4.1.10734.3.3.3.1.26	The network protocol of the packet(s) that triggered the policy action. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
tptPolicyNotifyAlertTimeSec	1.3.6.1.4.1.10734.3.3.3.1.27	The time that the alert was initiated, marking the end of the aggregation period for this notification. Measured in seconds since January 1, 1970.
tptPolicyNotifyAlertTimeNano	1.3.6.1.4.1.10734.3.3.3.1.28	The nanoseconds portion of the AlertTimeSec object.
tptPolicyNotifyPacketTrace	1.3.6.1.4.1.10734.3.3.3.1.29	Indicates if a corresponding packet trace was logged. <ul style="list-style-type: none"> • 0: not logged • 1: logged.
tptPolicyNotifySequence	1.3.6.1.4.1.10734.3.3.3.1.30	The log file entry sequence number corresponding to this notification.
tptPolicyNotifyTraceBucket	1.3.6.1.4.1.10734.3.3.3.1.36	The bucket identifier for a packet trace.
tptPolicyNotifyTraceBegin	1.3.6.1.4.1.10734.3.3.3.1.37	The starting sequence number for a packet trace.
tptPolicyNotifyTraceEnd	1.3.6.1.4.1.10734.3.3.3.1.38	The ending sequence number for a packet trace.
tptPolicyNotifyMessageParams	1.3.6.1.4.1.10734.3.3.3.1.39	A string containing parameters separated by vertical bars () that match information tagged with Message in the DV.
tptPolicyNotifyStartTimeNano	1.3.6.1.4.1.10734.3.3.3.1.40	The nanoseconds portion of StartTimeSec.
tptPolicyNotifyAlertType	1.3.6.1.4.1.10734.3.3.3.1.41	A bit field defined as follows: <ul style="list-style-type: none"> • 0x0001 = Alert • 0x0002 = Block • 0x0020 = Peer-to-peer • 0x0040 = Invalid • 0x0080 = Threshold • 0x0100 = Management.

Table A-33 Policy notification objects

Object	OID	Description
tptPolicyNotifyInputMphy	1.3.6.1.4.1.10734.3.3.3.1.57	The incoming physical port of the triggering packet(s).
tptPolicyNotifyVlanTag	1.3.6.1.4.1.10734.3.3.3.1.58	The VLAN tag of the triggering packet(s).
tptPolicyNotifyZonePair	1.3.6.1.4.1.10734.3.3.3.1.59	A string that identifies the port pair related to this notification.
tptPolicyNotifyActionSetID	1.3.6.1.4.1.10734.3.3.3.1.130	The action set uuid associated with this notification.
tptPolicyNotifyRate	1.3.6.1.4.1.10734.3.3.3.1.131	The rate-limit, in kbps, of the action set associated with this notification.
tptPolicyNotifyFlowControl	1.3.6.1.4.1.10734.3.3.3.1.137	The action set flow control associated with this notification.
tptPolicyNotifyActionSetName	1.3.6.1.4.1.10734.3.3.3.1.138	The action set name associated with this notification.

The following notifications and SNMP traps are generated when policy log entries are created.

Table A-34 Policy log notification objects

Object	OID	Description
tptPolicyLogNotify	1.3.6.1.4.1.10734.3.3.3.0.19	A notification that a some number of policy log entries of a particular type have occurred since the last time the management station retrieved the corresponding log file.
tptPolicyLogNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.121	The unique identifier of the device sending this notification.
tptPolicyLogNotifyComponentID	1.3.6.1.4.1.10734.3.3.3.1.122	The type of log related to this notification: <ul style="list-style-type: none"> • 0: invalid • 1: deny • 2: allow • 7: alert • 8: block • 9: peer
tptPolicyLogNotifyNumber	1.3.6.1.4.1.10734.3.3.3.1.123	The number of policy log entries created since the last log file retrieval.
tptPolicyLogNotifyTrigger	1.3.6.1.4.1.10734.3.3.3.1.124	The number of policy log entries needed to trigger this notification.
tptPolicyLogNotifySequence	1.3.6.1.4.1.10734.3.3.3.1.125	The current log file entry sequence number.

Policy Variable Objects

The following variables apply to various policy statistics.

Table A-35 Policy variable objects

Object	OID	Description
policyPacketsDropped	1.3.6.1.4.1.10734.3.3.2.1.1	The total number of packets discarded due to network congestion.
policyPacketsBlocked	1.3.6.1.4.1.10734.3.3.2.1.2	The cumulative number of packets blocked by policy actions.
policyPacketsIncoming	1.3.6.1.4.1.10734.3.3.2.1.3	The total number of incoming packets.
policyPacketsOutgoing	1.3.6.1.4.1.10734.3.3.2.1.4	The total number of outgoing packets.
policyPacketsInvalid	1.3.6.1.4.1.10734.3.3.2.1.6	The total number of invalid packets discarded.
policyPacketsPermitted	1.3.6.1.4.1.10734.3.3.2.1.7	The total number of packets permitted by policy actions.
policyPacketsDropped64	1.3.6.1.4.1.10734.3.3.2.1.31	The total number of packets discarded due to network congestion.
policyPacketsBlocked64	1.3.6.1.4.1.10734.3.3.2.1.32	The cumulative number of packets blocked by of policy actions.
policyPacketsIncoming64	1.3.6.1.4.1.10734.3.3.2.1.33	The total number of incoming packets.
policyPacketsOutgoing64	1.3.6.1.4.1.10734.3.3.2.1.34	The total number of outgoing packets.
policyPacketsInvalid64	1.3.6.1.4.1.10734.3.3.2.1.36	The total number of invalid packets discarded.
policyPacketsPermitted64	1.3.6.1.4.1.10734.3.3.2.1.37	The total number of packets permitted by policy actions.
policyPacketsRateLimited64	1.3.6.1.4.1.10734.3.3.2.1.38	The total number of packets discarded by rate limiting filters.
policyPacketsTrusted64	1.3.6.1.4.1.10734.3.3.2.1.39	The total number of packets trusted by policy actions.

The following policy objects refer to the Digital Vaccine installed on the device.

Table A-36 Digital Vaccine variable objects

Object	OID	Description
policyDVObjs	1.3.6.1.4.1.10734.3.3.2.1.10	Sub-tree of Digital Vaccine information.
policyDVVersion	1.3.6.1.4.1.10734.3.3.2.1.10 .1	The version number of the DV installed on this device.

Policy Information Tables

There are several tables that provide statistics about policy performance.

The following table lists the bytes and packets affected by each policy.

Table A-37 Per-policy variable objects

Object	OID	Description
policyCounterTable	1.3.6.1.4.1.10734.3.3.2.1.5	Table of per-policy counter values.
policyCounterEntry	1.3.6.1.4.1.10734.3.3.2.1.5.1	An entry in the policy counter table. Rows cannot be added or deleted.
policyGlobalID	1.3.6.1.4.1.10734.3.3.2.1.5.1.1	The global ID of a policy.
policyDescriptiveName	1.3.6.1.4.1.10734.3.3.2.1.5.1.2	The name of a policy.
policyCountBytes	1.3.6.1.4.1.10734.3.3.2.1.5.1.3	The number of bytes affected by the policy.
policyCountPackets	1.3.6.1.4.1.10734.3.3.2.1.5.1.4	The number of packets affected by the policy.
policyCreationTime	1.3.6.1.4.1.10734.3.3.2.1.5.1.5	The time the policy was pushed to NetPAL.

The following table ranks the top ten policies according to hit count.

Table A-38 Top Ten Policies table objects

Object	OID	Description
topTenHitsByPolicyTable	1.3.6.1.4.1.10734.3.3.2.1.11	Table of the ten policies with the largest number of hit counts.
topTenHitsByPolicyEntry	1.3.6.1.4.1.10734.3.3.2.1.11.1	An entry in the top ten policies table.
topTenRank	1.3.6.1.4.1.10734.3.3.2.1.11.1.1	The numerical ranking of the policy in the table. A rank of 1 indicates the policy has the largest number of hits.
policyHitCount	1.3.6.1.4.1.10734.3.3.2.1.11.1.2	The number of alerts generated by the policy.
policyName	1.3.6.1.4.1.10734.3.3.2.1.11.1.3	The policy name.
policyUUID	1.3.6.1.4.1.10734.3.3.2.1.11.1.4	The global identifier of the policy.

The following table lists the number of alerts generated by each severity level.

Table A-39 Alerts by severity table objects

Object	OID	Description
alertsBySeverityTable	1.3.6.1.4.1.10734.3.3.2.1.12	Table of alert counts of all policies at each severity level.
alertsBySeverityEntry	1.3.6.1.4.1.10734.3.3.2.1.12.1	An entry in the alerts by severity table.

Table A-39 Alerts by severity table objects

Object	OID	Description
alertSeverity	1.3.6.1.4.1.10734.3.3.2.1.12.1.1	The severity of a policy. <ul style="list-style-type: none"> • 1: warning • 2: minor • 3: major • 4: critical
severityAlertCount	1.3.6.1.4.1.10734.3.3.2.1.12.1.2	The number of alerts generated by all policies of a given severity.

The following table lists the number of alerts generated by each protocol type.

Table A-40 Alerts by protocol table objects

Object	OID	Description
alertsByProtocolTable	1.3.6.1.4.1.10734.3.3.2.1.13	Table of alert counts of all policies at each protocol level.
alertsByProtocolEntry	1.3.6.1.4.1.10734.3.3.2.1.13.1	An entry in the alerts by protocol table.
alertProtocol	1.3.6.1.4.1.10734.3.3.2.1.13.1.1	The protocol of a policy. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
protocolAlertCount	1.3.6.1.4.1.10734.3.3.2.1.13.1.2	The number of alerts generated by all policies of a given protocol.

The following table lists the number of alerts generated by each virtual segment.

NOTE: The MIBs refer to “security zone pairs”. This terminology has been deprecated and replaced by “virtual segment”, but is still used by the MIB for compatibility purposes.

Table A-41 Alerts by zone table objects

Object	OID	Description
alertsByZoneTable	1.3.6.1.4.1.10734.3.3.2.1.14	Table of alert counts of all policies at each virtual segment.
alertsByZoneEntry	1.3.6.1.4.1.10734.3.3.2.1.14.1	An entry in the alerts by virtual segment table.
alertSlot	1.3.6.1.4.1.10734.3.3.2.1.14.1.1	The virtual segment affected by a policy.

Table A-41 Alerts by zone table objects

Object	OID	Description
alertPort	1.3.6.1.4.1.10734.3.3.2.1.14.1.2	The port identifying the virtual segment affected by the policy.
zoneAlertCount	1.3.6.1.4.1.10734.3.3.2.1.14.1.3	The number of all alerts generated by all policies applied to a given virtual segment.

The following table lists the number of permits generated by each virtual segment.

NOTE: The MIBs refer to “security zone pairs”. This terminology has been deprecated and replaced by “virtual segment”, but is still used by the MIB for compatibility purposes.

Table A-42 Permits by zone table objects

Object	OID	Description
permitsByZoneTable	1.3.6.1.4.1.10734.3.3.2.1.15	Table of permit counts of all policies at each virtual segment.
permitsByZoneEntry	1.3.6.1.4.1.10734.3.3.2.1.15.1	An entry in the permits by virtual segment table.
permitSlot	1.3.6.1.4.1.10734.3.3.2.1.15.1.1	The virtual segment affected by a policy.
permitPort	1.3.6.1.4.1.10734.3.3.2.1.15.1.2	The port identifying the virtual segment affected by the policy.
zonePermitCount	1.3.6.1.4.1.10734.3.3.2.1.15.1.3	The number of all permits generated by all policies applied to a given virtual segment.

The following table lists the number of blocks generated by each virtual segment.

NOTE: The MIBs refer to “security zone pairs”. This terminology has been deprecated and replaced by “virtual segment”, but is still used by the MIB for compatibility purposes.

Table A-43 Blocks by zone table objects

Object	OID	Description
blocksByZoneTable	1.3.6.1.4.1.10734.3.3.2.1.16	Table of block counts of all policies at each virtual segment.
blocksByZoneEntry	1.3.6.1.4.1.10734.3.3.2.1.16.1	An entry in the blocks by virtual segment table.
blockSlot	1.3.6.1.4.1.10734.3.3.2.1.16.1.1	The virtual segment affected by a policy.
blockPort	1.3.6.1.4.1.10734.3.3.2.1.16.1.2	The port identifying the virtual segment affected by the policy.
zoneBlockCount	1.3.6.1.4.1.10734.3.3.2.1.16.1.3	The number of all blocks generated by all policies applied to a given virtual segment.

The following table lists the number of P2Ps generated by each virtual segment.

NOTE: The MIBs refer to “security zone pairs”. This terminology has been deprecated and replaced by “virtual segment”, but is still used by the MIB for compatibility purposes.

Table A-44 P2P by zone table objects

Object	OID	Description
p2psByZoneTable	1.3.6.1.4.1.10734.3.3.2.1.17	Table of P2P counts of all policies at each virtual segment.
p2psByZoneEntry	1.3.6.1.4.1.10734.3.3.2.1.17.1	An entry in the P2Ps by virtual segment table.
p2pSlot	1.3.6.1.4.1.10734.3.3.2.1.17.1.1	The virtual segment affected by a policy.
p2pPort	1.3.6.1.4.1.10734.3.3.2.1.17.1.2	The port identifying the virtual segment affected by the policy.
zonep2pCount	1.3.6.1.4.1.10734.3.3.2.1.17.1.3	The number of all P2Ps generated by all policies applied to a given virtual segment.

This table lists the number of frames received, sorted by frame size category.

Table A-45 Frames by size table objects

Object	OID	Description
framesBySizeTable	1.3.6.1.4.1.10734.3.3.2.1.18	Table of frame counts received in each size category.
framesBySizeEntry	1.3.6.1.4.1.10734.3.3.2.1.18.1	An entry in the frames by size table. Rows cannot be added or deleted.
frameSize	1.3.6.1.4.1.10734.3.3.2.1.18.1.1	The frame size category. <ul style="list-style-type: none"> • 64 bytes • 65-127 bytes • 128-255 bytes • 256-511 bytes • 512-1023 bytes • 1024-1518 bytes • 1519-4095 bytes • 4096-9216 bytes • 9217-16383 bytes • undersize packets • oversize packets
sizeFrameCount	1.3.6.1.4.1.10734.3.3.2.1.18.1.2	The number of frames received in a given size category.

This table lists the number of frames received, sorted by type.

Table A-46 Frames by type table objects

Object	OID	Description
framesByTypeTable	1.3.6.1.4.1.10734.3.3.2.1.19	Table of frame counts received in each type category.
framesByTypeEntry	1.3.6.1.4.1.10734.3.3.2.1.19.1	An entry in the frames by type table. Rows cannot be added or deleted.
frameType	1.3.6.1.4.1.10734.3.3.2.1.19.1.1	The frame type category. <ul style="list-style-type: none"> • 1: unicast • 2: broadcast • 3: multicast • 4: MAC control • 5: FCS error • 6: align error • 7: symbol error
typeFrameCount	1.3.6.1.4.1.10734.3.3.2.1.19.1.2	The number of frames received in a given type category.

This table lists the number of packets received, sorted by protocol.

Table A-47 Packets by protocol table objects

Object	OID	Description
packetsByProtocolTable	1.3.6.1.4.1.10734.3.3.2.1.20	Table of packet counts received in each protocol.
packetsByProtocolEntry	1.3.6.1.4.1.10734.3.3.2.1.20.1	An entry in the packets by protocol table. Rows cannot be added or deleted.
packetProtocol	1.3.6.1.4.1.10734.3.3.2.1.20.1.1	The packet protocol category. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
protocolPacketCount	1.3.6.1.4.1.10734.3.3.2.1.20.1.2	The number of packets received in a given protocol category.

This table lists statistics for each physical port.

Table A-48 Port statistics table objects

Object	OID	Description
portStatsTable	1.3.6.1.4.1.10734.3.3.2.1.23	Table of statistics for each physical port.
portStatsEntry	1.3.6.1.4.1.10734.3.3.2.1.23.1	An entry in the port statistics table. Rows cannot be added or deleted.
portNumber	1.3.6.1.4.1.10734.3.3.2.1.23.1.1	The port number.
portName	1.3.6.1.4.1.10734.3.3.2.1.23.1.2	The port name.
portVlanTranslations	1.3.6.1.4.1.10734.3.3.2.1.23.1.3	The number of packets leaving the egress port with translated VLAN IDs.

This table lists all policies defined on the device.

Table A-49 Policy name and description table objects

Object	OID	Description
policyByNumberTable	1.3.6.1.4.1.10734.3.3.2.1.21	Table of policies defined on the device.
policyByNumberEntry	1.3.6.1.4.1.10734.3.3.2.1.21.1	An entry in the policy by number table.
policyNumber	1.3.6.1.4.1.10734.3.3.2.1.21.1.1	The policy number. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
numberName	1.3.6.1.4.1.10734.3.3.2.1.21.1.2	The policy name.
numberDesc	1.3.6.1.4.1.10734.3.3.2.1.21.1.3	The policy description.

NOTE: The MIBs refer to “security zone pairs”. This terminology has been deprecated and replaced by “virtual segment”, but is still used by the MIB for compatibility purposes.

This table lists the statistics for all virtual segments.

Table A-50 Security zone pair information and statistics table objects

Object	OID	Description
securityZonePairTable	1.3.6.1.4.1.10734.3.3.2.1.22	Table of information and statistics for each virtual segment.
securityZonePairEntry	1.3.6.1.4.1.10734.3.3.2.1.22.1	An entry in the table.
szpName	1.3.6.1.4.1.10734.3.3.2.1.22.1.1	The name of a virtual segment.

Table A-50 Security zone pair information and statistics table objects

Object	OID	Description
szplnZoneName	1.3.6.1.4.1.10734.3.3.2.1.22.1.2	The incoming part of a virtual segment.
szpOutZoneName	1.3.6.1.4.1.10734.3.3.2.1.22.1.3	The outgoing part of a virtual segment.
szpUUID	1.3.6.1.4.1.10734.3.3.2.1.22.1.4	The UUID of a virtual segment.
szplnZoneUUID	1.3.6.1.4.1.10734.3.3.2.1.22.1.5	The UUID of the incoming part of the virtual segment.
szpOutZoneUUID	1.3.6.1.4.1.10734.3.3.2.1.22.1.6	The UUID of the outgoing part of the virtual segment.
szplnPackets	1.3.6.1.4.1.10734.3.3.2.1.22.1.7	The number of packets received on the virtual segment.
szplnOctets	1.3.6.1.4.1.10734.3.3.2.1.22.1.8	The number of bytes received on this virtual segment.
szpAlerts	1.3.6.1.4.1.10734.3.3.2.1.22.1.9	The number of alerts generated on this virtual segment.
szpBlocks	1.3.6.1.4.1.10734.3.3.2.1.22.1.10	The number of blocks generated on this virtual segment.
szpPermits	1.3.6.1.4.1.10734.3.3.2.1.22.1.11	The number of permits generated on this virtual segment.
szpPrecedence	1.3.6.1.4.1.10734.3.3.2.1.22.1.12	The precedence of the virtual segment.

TPT-PORT-CONFIG

Defines port configuration settings.

Table A-51 Port configuration settings objects

Object	OID	Description
portConfigTable	1.3.6.1.4.1.10734.3.3.2.4.1	Table of ports on the device and their configuration settings.
portConfigEntry	1.3.6.1.4.1.10734.3.3.2.4.1.1	An entry in the ports table.
portConfigSlot	1.3.6.1.4.1.10734.3.3.2.4.1.1.1	The segment on which the port is located.
portConfigPort	1.3.6.1.4.1.10734.3.3.2.4.1.1.2	The port number.
portConfigLineSpeed	1.3.6.1.4.1.10734.3.3.2.4.1.1.3	The line speed configuration: <ul style="list-style-type: none"> • 0: default • 1: 1GbE • 2: 100 Mb • 3: 10 Mb • 4: 10 GbE

Table A-51 Port configuration settings objects

Object	OID	Description
portConfigDuplex	1.3.6.1.4.1.10734.3.3.2.4.1.1.4	The duplex configuration. <ul style="list-style-type: none"> • 0: default • 1: half • 2: full
portConfigAutoNeg	1.3.6.1.4.1.10734.3.3.2.4.1.1.5	The auto-negotiation configuration. <ul style="list-style-type: none"> • 0: default • 1: on • 2: off
portConfigShutdown	1.3.6.1.4.1.10734.3.3.2.4.1.1.6	The shutdown configuration. <ul style="list-style-type: none"> • 0: disabled—The port can come up normally. • 1: enabled—The port is manually removed from service.
portConfigLoopback	1.3.6.1.4.1.10734.3.3.2.4.1.1.7	The loopback configuration. <ul style="list-style-type: none"> • 0: disabled • 1: enabled
portConfigFailover	1.3.6.1.4.1.10734.3.3.2.4.1.1.8	The failover action configuration. <ul style="list-style-type: none"> • 0: block • 1: permit
portConfigLDMode	1.3.6.1.4.1.10734.3.3.2.4.1.1.9	The link-down synchronization mode. <ul style="list-style-type: none"> • 0: hub • 1: breaker • 2: wire
portConfigLDTimeout	1.3.6.1.4.1.10734.3.3.2.4.1.1.10	The link-down synchronization timeout configuration.

TPT-PORT-MAPPING

Defines the mapping between logical ports and slots and physical ports and slots.

Table A-52 Port configuration settings objects

Object	OID	Description
tpt-port-mapping-objs	1.3.6.1.4.1.10734.3.3.2.16	Configurable logical to physical port mapping on a device.
portMappingTable	1.3.6.1.4.1.10734.3.3.2.16.1	Table of logical slots/ports on the device and their mapping to the physical ports.
portMappingEntry	1.3.6.1.4.1.10734.3.3.2.16.1.1	An entry in the slot/port table. Rows cannot be created or deleted.
portMappingLogicalSlot	1.3.6.1.4.1.10734.3.3.2.16.1.1.1	Slot number for this logical port.

Table A-52 Port configuration settings objects

Object	OID	Description
portMappingLogicalPort	1.3.6.1.4.1.10734.3.3.2.16.1.1.2	Port number for this logical port.
portMappingLogicalIfIndex	1.3.6.1.4.1.10734.3.3.2.16.1.1.3	The entry in the IF-MIB interface table that corresponds to this logical port.
portMappingPhysicalSlot	1.3.6.1.4.1.10734.3.3.2.16.1.1.4	Slot number for the mapped physical port.
portMappingPhysicalPort	1.3.6.1.4.1.10734.3.3.2.16.1.1.5	Port number for the mapped physical port.
portMappingPhysicalIfIndex	1.3.6.1.4.1.10734.3.3.2.16.1.1.6	The entry in the IF-MIB interface table that corresponds to the mapped physical port.
portMappingSegmentName	1.3.6.1.4.1.10734.3.3.2.16.1.1.7	The name of the segment pertaining to this logical port.
portMappingPhysicalVlanId	1.3.6.1.4.1.10734.3.3.2.16.1.1.8	The VLAN ID used on the physical port. 0 indicates the traffic is untagged or not applicable for this port.

TPT-RESOURCE

Describes memory, power supply, temperature, and voltage information for the device.

Notifications

The following notifications and SNMP traps send information to the management system about the systemresources.

Table A-53 Resource notification objects

Object	OID	Description
tptResourceNotify	1.3.6.1.4.1.10734.3.3.3.0.14	Sub-tree of notifications that indicate when a resource parameter has crossed a predefined threshold.
tptResourceNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.61	The unique identifier of the device sending the notification.
tptResourceNotify Identifier	1.3.6.1.4.1.10734.3.3.3.1.62	The type of resource that triggered the notification. <ul style="list-style-type: none"> • 1: filesystem • 2: CPU • 3: memory • 4: chassis temperature • 5: fan • 6: power supply • 7: hard disk
tptResourceNotifyFSIndex	1.3.6.1.4.1.10734.3.3.3.1.63	For a filesystem resource, the value is the index number of the filesystem. Otherwise, the value is zero (0).

Table A-53 Resource notification objects

Object	OID	Description
tptResourceNotifyCurrentValue	1.3.6.1.4.1.10734.3.3.3.1.64	The current value of the resource that triggered the notification.
tptResourceNotifyThresholdMaj	1.3.6.1.4.1.10734.3.3.3.1.65	The major threshold of this resource, between green and yellow states.
tptResourceNotifyThresholdCrit	1.3.6.1.4.1.10734.3.3.3.1.66	The critical threshold of this resource, between yellow and red states.
tptResourceNotifyRangeMin	1.3.6.1.4.1.10734.3.3.3.1.67	The minimum end of the range of values that this resource can take.
tptResourceNotifyRangeMax	1.3.6.1.4.1.10734.3.3.3.1.68	The maximum end of the range of values that this resource can take.
tptResourceNotifyStateBefore	1.3.6.1.4.1.10734.3.3.3.1.69	The state of the resource before the current threshold transition.
tptResourceNotifyAfter	1.3.6.1.4.1.10734.3.3.3.1.70	The state of this resource after the current threshold transition.
tptResourceNotifyTimeStamp	1.3.6.1.4.1.10734.3.3.3.1.71	The timestamp of the event that generated the notification, in seconds since January 1, 1970.

File System

The following objects provide information about the device file system.

Table A-54 File system information objects

Object	OID	Description
resourcenumber ofFilesystems	1.3.6.1.4.1.10734.3.3.2.5.1	The number of filesystems on the device's hard disk.
resourceFSTable	1.3.6.1.4.1.10734.3.3.2.5.2	Table of filesystem resource information.
resourceFSEntry	1.3.6.1.4.1.10734.3.3.2.5.2.1	An entry in the resource filesystem table. Rows cannot be added or deleted.
resourceFSInUseMB	1.3.6.1.4.1.10734.3.3.2.5.2.1.1	The number of MB in use for the filesystem.
resourceFSThresholdMaj	1.3.6.1.4.1.10734.3.3.2.5.2.1.2	The major threshold for the percent of MB in use for the filesystem.
resourceFSThresholdCrit	1.3.6.1.4.1.10734.3.3.2.5.2.1.3	The critical threshold for the percent of MB in use for the filesystem.
resourceFSRangeMin	1.3.6.1.4.1.10734.3.3.2.5.2.1.4	The minimum value of the range of MB in use, usually zero (0).
resourceFSRangeMax	1.3.6.1.4.1.10734.3.3.2.5.2.1.5	The total size in MB of the filesystem.

Table A-54 File system information objects

Object	OID	Description
resourceFSName	1.3.6.1.4.1.10734.3.3.2.5.2.1.6	The name of this filesystem.
resourceFSIndex	1.3.6.1.4.1.10734.3.3.2.5.2.1.7	The number of the table row, starting at one (1).

Memory

The following objects provide information about the device memory usage.

Table A-55 Memory information objects

Object	OID	Description
resourceHPMemoryObjs	1.3.6.1.4.1.10734.3.3.2.5.3	Sub-tree of host processor memory information.
resourceHPMemoryInUsePercent	1.3.6.1.4.1.10734.3.3.2.5.3.1	The percentage of host processor memory in use.
resourceHPMemoryThresholdMaj	1.3.6.1.4.1.10734.3.3.2.5.3.2	The major threshold value for host processor memory usage.
resourceHPMemoryThresholdCrit	1.3.6.1.4.1.10734.3.3.2.5.3.3	The critical threshold value for host processor memory usage.
resourceHPMemoryRangeMin	1.3.6.1.4.1.10734.3.3.2.5.3.4	The minimum percentage of host processor memory usage, usually zero (0).
resourceHPMemoryRangeMax	1.3.6.1.4.1.10734.3.3.2.5.3.5	The maximum percentage of host processor memory usage, usually 100.
resourceHPMemoryTotal	1.3.6.1.4.1.10734.3.3.2.5.3.6	The total size in bytes of host processor memory.

CPU

The following objects provide information about CPU usage.

Table A-56 CPU information objects

Object	OID	Description
resourceHPCPUObjs	1.3.6.1.4.1.10734.3.3.2.5.4	Sub-tree of host processor CPU information.
resourceHPCPUBusyPercent	1.3.6.1.4.1.10734.3.3.2.5.4.1	The percentage of host processor CPU that is currently busy.
resourceHPCPUThresholdMaj	1.3.6.1.4.1.10734.3.3.2.5.4.2	The major threshold value for host processor CPU activity.
resourceHPCPUThresholdCrit	1.3.6.1.4.1.10734.3.3.2.5.4.3	The critical threshold value of host processor CPU activity.
resourceHPCPURangeMin	1.3.6.1.4.1.10734.3.3.2.5.4.4	The minimum percentage of host processor CPU activity, usually zero (0).
resourceHPCPURangeMax	1.3.6.1.4.1.10734.3.3.2.5.4.5	The maximum percentage of host processor CPU activity, usually 100.

Table A-56 CPU information objects

Object	OID	Description
resourceNPCPUBusyPercentA	1.3.6.1.4.1.10734.3.3.2.5.4.6	Total Utilization of XLR A.
resourceNPCPUBusyPercentTier2A	1.3.6.1.4.1.10734.3.3.2.5.4.7	F Thread Utilization of XLR A.
resourceNPCPUBusyPercentTier3A	1.3.6.1.4.1.10734.3.3.2.5.4.8	KS Thread Utilization of XLR A.
resourceNPCPUBusyPercentTier4A	1.3.6.1.4.1.10734.3.3.2.5.4.9	L Thread Utilization of XLR A.
resourceNPCPUBusyPercentB	1.3.6.1.4.1.10734.3.3.2.5.4.10	Total Utilization of XLR B.
resourceNPCPUBusyPercentTier2B	1.3.6.1.4.1.10734.3.3.2.5.4.11	F Thread Utilization of XLR B.
resourceNPCPUBusyPercentTier3B	1.3.6.1.4.1.10734.3.3.2.5.4.12	KS Thread Utilization of XLR B.
resourceNPCPUBusyPercentTier4B	1.3.6.1.4.1.10734.3.3.2.5.4.13	L Thread Utilization of XLR B.

Chassis Temperature

The following objects provide information about the chassis temperature. All values are in degrees Centigrade.

Table A-57 Chassis temperature information objects

Object	OID	Description
resourceChassisTempObjs	1.3.6.1.4.1.10734.3.3.2.5.5	Sub-tree of chassis temperature information.
resourceChassisTempDegreesC	1.3.6.1.4.1.10734.3.3.2.5.5.1	The chassis temperature.
resourceChassisTempThresholdMajor	1.3.6.1.4.1.10734.3.3.2.5.5.2	The major threshold value for chassis temperature.
resourceChassisTempThresholdCritical	1.3.6.1.4.1.10734.3.3.2.5.5.3	The critical threshold value of chassis temperature.
resourceChassisTempRangeMin	1.3.6.1.4.1.10734.3.3.2.5.5.4	The minimum value of the chassis temperature range.
resourceChassisTempRangeMax	1.3.6.1.4.1.10734.3.3.2.5.5.5	The maximum value of the chassis temperature range.

Power Supply

The following objects provide information about the chassis temperature.

Table A-58 Power supply information objects

Object	OID	Description
resourcePowerSupplyObjs	1.3.6.1.4.1.10734.3.3.2.5.9	Sub-tree of power supply information.
resourcePowerSupplyStatus	1.3.6.1.4.1.10734.3.3.2.5.9.1	If the device has dual power supplies and power supply monitoring is enabled, this value indicates whether one or both power supplies is functioning. <ul style="list-style-type: none">• 0: unknown; the device does not have dual power supplies, or power supply monitoring is disabled.• 1: red—critical• 2: yellow—warning• 3: green—normal
resourcePowerSupplyQuantity	1.3.6.1.4.1.10734.3.3.2.5.9.2	The number of power supplies.
resourcePowerSupplyMonitoring	1.3.6.1.4.1.10734.3.3.2.5.9.3	Indicates if power supply monitoring is enabled: <ul style="list-style-type: none">• 0: disabled• 1: enabled

System Log Count

The following objects provide system log statistics.

Table A-59 System log count objects

Object	OID	Description
resourceLogCountObjs	1.3.6.1.4.1.10734.3.3.2.5.7	Sub-tree of system log entry counts, sorted by type.
resourceLogCountCritical	1.3.6.1.4.1.10734.3.3.2.5.7.1	The number of Critical syslog entries.
resourceLogCountError	1.3.6.1.4.1.10734.3.3.2.5.7.2	The number of Error syslog entries.
resourceLogCountWarning	1.3.6.1.4.1.10734.3.3.2.5.7.3	The number of Warning syslog entries.
resourceLogCountInfo	1.3.6.1.4.1.10734.3.3.2.5.7.4	The number of Info syslog entries.

System Metrics

The following objects provide system metric statistics.

Table A-60 System metric objects

Object	OID	Description
resourceMetricObjs	1.3.6.1.4.1.10734.3.3.2.5.8	Sub-tree of selected system performance metrics.
resourceMetricFastpath	1.3.6.1.4.1.10734.3.3.2.5.8.1	Fast path throughput in bits per second.
resourceMetricSmartPath	1.3.6.1.4.1.10734.3.3.2.5.8.2	Smart path throughput in bits per second.
resourceMetricCongestion	1.3.6.1.4.1.10734.3.3.2.5.8.3	Congestion count in packets.

System Information

The following objects provide information about the system.

Table A-61 System information objects

Object	OID	Description
resourceVersion	1.3.6.1.4.1.10734.3.3.2.5.6	Operating system build version and date.
resourceDateTime	1.3.6.1.4.1.10734.3.3.2.5.10	Current date and time of device in seconds since January 1, 1970. There is no time zone offset.
resourceSnmpRunState	1.3.6.1.4.1.10734.3.3.2.5.11	Indicates which SNMP versions are running. <ul style="list-style-type: none">• 0: none• 1: SNMP v2• 2: SNMP v3• 3: Both v2 and v3
resourceSnmpConfig	1.3.6.1.4.1.10734.3.3.2.5.12	Indicates which SNMP versions are configured. <ul style="list-style-type: none">• 0: none• 1: SNMP v2• 2: SNMP v3• 3: Both v2 and v3
resourceRemoteAuthEnabled	1.3.6.1.4.1.10734.3.3.2.5.13	Indicates whether remote authentication is enabled.
resourceRemoteAuthTimeout	1.3.6.1.4.1.10734.3.3.2.5.14	The remote authentication timeout in seconds.

TPT-SMSMIBS

Defines interactions between the SMS and the customer's NMS.

Table A-62 SMS top level MIBs

Object	OID	Description
tpt-sms-conf	1.3.6.1.4.1.10734.3.4.1	SMS conformance objects sub-tree.
tpt-sms-objs	1.3.6.1.4.1.10734.3.4.2	SMS managed objects sub-tree.
tpt-sms-events	1.3.6.1.4.1.10734.3.4.3	SMS events sub-tree that includes all payload variables needed for notifications.

Table A-63 SMS conformance top level MIBs

Object	OID	Description
tpt-sms-groups	1.3.6.1.4.1.10734.3.4.1.1	SMS groups sub-tree.
tpt-sms-compls	1.3.6.1.4.1.10734.3.4.1.2	SMS compliance MIBs sub-tree.

Table A-64 SMS notification top level MIBs

Object	OID	Description
tpt-sms-eventsV2	1.3.6.1.4.1.10734.3.4.3.0	SMS events notification MIBs.
tpt-sms-notifypayload	1.3.6.1.4.1.10734.3.4.3.1	SMS MIB variables sent as part of a notification payload.

Table A-65 Model number objects

Object	OID	Description
tpt-sms-family	1.3.6.1.4.1.10734.1.3	Registration for the SMS.

TPT-SMS-TRAP-MIB

Describes the notifications sent to and from an SMS device.

Table A-66 SMS Notification MIBs

Object	OID	Description
tptSmsQuarantineRequest	1.3.6.1.4.1.10734.3.4.3.0.1	The SMS asks an external NMS to quarantine an endstation using the data embedded in the request.
tptSmsQuarantineAck	1.3.6.1.4.1.10734.3.4.3.0.2	The external NMS notifies the SMS that a quarantine request was processed.
tptSmsQuarantineReleaseRequest	1.3.6.1.4.1.10734.3.4.3.0.3	The SMS asks an external NMS to unquarantine an endstation using the data embedded in the request.
tptSmsQuarantineReleaseAck	1.3.6.1.4.1.10734.3.4.3.0.4	The external NMS notifies the SMS that an unquarantine request was processed.

Table A-66 SMS Notification MIBs

Object	OID	Description
tptSmsQuarantinePolicyNotification	1.3.6.1.4.1.10734.3.4.3.0.5	The SMS sends notification of a policy match
tptSmsUnQuarantineRequest	1.3.6.1.4.1.10734.3.4.3.0.6	Commands the SMS to unquarantine an endstation.
tptSmsQuarantineCommand	1.3.6.1.4.1.10734.3.4.3.0.14	Commands the SMS to quarantine an endstation.
tptSmsReboot	1.3.6.1.4.1.10734.3.4.3.0.8	Indicates that the SMS is rebooting.
tptSmsShuttingDown	1.3.6.1.4.1.10734.3.4.3.0.9	Indicates that the system is shutting down.
tptSmsReady	1.3.6.1.4.1.10734.3.4.3.0.10	Indicates that the system is ready.
tptSmsAuthenticationError	1.3.6.1.4.1.10734.3.4.3.0.11	Indicates that an authentication error has occurred.
tptSmsEgpNeighborDownstate	1.3.6.1.4.1.10734.3.4.3.0.12	Indicates that the EGP neighbor is going to downstate.
tptSmsSystemRestart	1.3.6.1.4.1.10734.3.4.3.0.13	Indicates that the server process has restarted.

NOTE: The following variables cannot be retrieved by the NMS.

Table A-67 SMS MIB Variables

Object	OID	Description
tptSmsQuarantineNotifyId	1.3.6.1.4.1.10734.3.4.3.1.1	A unique incrementing integer assigned to each quarantine event.
tptSmsQuarantineNotifyData	1.3.6.1.4.1.10734.3.4.3.1.2	A string that identifies the device to be quarantined. The format is NAME:VALUE. Multiple parameters are separated by a new line.
tptSmsQuarantinePolicyMatchData	1.3.6.1.4.1.10734.3.4.3.1.3	A string that identifies the matching policy.
tptSmsQuarantineNotifyType	1.3.6.1.4.1.10734.3.4.3.1.4	A string that identifies the matching policy.
tptSmsQuarantineDeviceIP	1.3.6.1.4.1.10734.3.4.3.1.5	The IP address used as a trap parameter
tptSmsQuarantineDeviceMAC	1.3.6.1.4.1.10734.3.4.3.1.6	The MAC address used as a trap parameter.
tptSmsQuarantineSwitchPort	1.3.6.1.4.1.10734.3.4.3.1.7	The port number or index used as a trap parameter.
tptSmsQuarantineEndpointUser	1.3.6.1.4.1.10734.3.4.3.1.8	A string that identifies the matching policy.

Table A-67 SMS MIB Variables

Object	OID	Description
tptSmsQuarantineNotifyActionList	1.3.6.1.4.1.10734.3.4.3.1.9	A string that identifies the matching policy.
tptSmsQuarantineNotifyParamList	1.3.6.1.4.1.10734.3.4.3.1.10	A string that identifies the matching policy.
tptSmsQuarantineNotifyOptionList	1.3.6.1.4.1.10734.3.4.3.1.11	A string that identifies the matching policy.
tptSmsQuarantinePolicyName	1.3.6.1.4.1.10734.3.4.3.1.12	The name of an SMS quarantine policy.
tptSmsQuarantineDataGroup	1.3.6.1.4.1.10734.3.4.1.1.1	Payload of SMS quarantine traps consisting of a unique identifier and a parseable string.
tptSmsQuarantineNotifyGroup	1.3.6.1.4.1.10734.3.4.1.1.2	SMS quarantine traps sent to an NMS to indicate devices that require a quarantine operation.
tptSmsQuarantineNotifyAckGroup	1.3.6.1.4.1.10734.3.4.1.1.3	SMS quarantine traps sent to an SMS system to indicate devices that have been quarantined.
tptSmsQuarantineRequestGroup	1.3.6.1.4.1.10734.3.4.1.1.4	SMS quarantine traps received to indicate devices that require a (un)quarantine operation.

TPT-TPA-HARDWARE

Describes the device hardware and its components, including ports, chassis, fans, and power supplies.

Table A-68 Hardware objects

Object	OID	Description
hw-numFans	1.3.6.1.4.1.10734.3.3.2.3.7	The number of fan subunits on the device.
hw-numPowerSupplies	1.3.6.1.4.1.10734.3.3.2.3.8	The number of power supply subunits on the device.
hw-numPEMs	1.3.6.1.4.1.10734.3.3.2.3.9	The number of power entry module subunits on the device.
hw-certificateNumber	1.3.6.1.4.1.10734.3.3.2.3.10	The hardware certificate number of the device.
hw-serialNumber	1.3.6.1.4.1.10734.3.3.2.3.11	The hardware serial number of the device.

Notifications

The following notifications and SNMP traps send information to the management system about hardware status.

Table A-69 Hardware notification objects

Object	OID	Description
tptHardwareNotify	1.3.6.1.4.1.10734.3.3.3.0.7	Notification of changes in the device hardware state.
tptHardwareNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.1	The unique identifier of the device sending this notification.
tptHardwareNotifySlot	1.3.6.1.4.1.10734.3.3.3.1.2	The slot with the state change that triggered the notification.
tptHardwareNotifyPort	1.3.6.1.4.1.10734.3.3.3.1.3	The port with the state change that triggered the notification.
tptHardwareNotifyMeType	1.3.6.1.4.1.10734.3.3.3.1.4	The type of hardware that triggered the notification.
tptHardwareNotifyCfgType	1.3.6.1.4.1.10734.3.3.3.1.5	The configuration of the hardware that triggered the notification.
tptHardwareNotifyHlState	1.3.6.1.4.1.10734.3.3.3.1.6	The high-level hardware state: <ul style="list-style-type: none"> • 0: out of service • 1: initializing • 2: active • 3: standby • 4: diagnostic • 5: loopback • 6: active-FAF • 7: standby-FAF • 8: active - degraded • 9: standby - degraded
tptHardwareNotifyHlStateQual	1.3.6.1.4.1.10734.3.3.3.1.7	Additional information about the high-level state.

Ports

The following objects provide information about the physical port hardware.

NOTE: The MIBs refer to “slots”, terminology used in previous versions of the TippingPoint operating system and TippingPoint IPS devices. Slots are no longer used, but certain subsystems may be considered as existing on virtual slots as follows:

Slot 1: Management processing

Slot 3: Physical network ports

Slot 5: Traffic processing

Table A-70 Port objects

Object	OID	Description
hw-slotTable	1.3.6.1.4.1.10734.3.3.2.3.1	Table of slots on the device.
hw-slotEntry	1.3.6.1.4.1.10734.3.3.2.3.1.1	An entry in the slot/port table.

Table A-70 Port objects

Object	OID	Description
slotNumber	1.3.6.1.4.1.10734.3.3.2.3.1.1.1	Slot number.
slotPort	1.3.6.1.4.1.10734.3.3.2.3.1.1.2	Port number.
slotInterface	1.3.6.1.4.1.10734.3.3.2.3.1.1.15	The entry in the IF-MIB interface table that corresponds to this port.
slotLineType	1.3.6.1.4.1.10734.3.3.2.3.1.1.16	The line type of the port. <ul style="list-style-type: none"> • 0: undefined • 1: copper • 2: optical
slotDuplexState	1.3.6.1.4.1.10734.3.3.2.3.1.1.17	The current port duplex state. <ul style="list-style-type: none"> • 0: unknown • 1: half • 2: full
slotPhysical	1.3.6.1.4.1.10734.3.3.2.3.1.1.18	Physical port number.

Chassis

The following objects provide information about the chassis.

Table A-71 Chassis data objects

Object	OID	Description
hw-chasTable	1.3.6.1.4.1.10734.3.3.2.3.2	Table of chassis data for the device. Represented as a table with one row.
hw-chasEntry	1.3.6.1.4.1.10734.3.3.2.3.2.1	An entry in the chassis table.
chasNumber	1.3.6.1.4.1.10734.3.3.2.3.2.1.1	The number for this entry in the chassis table. This number is always zero (0).
chasType	1.3.6.1.4.1.10734.3.3.2.3.2.1.3	Type of hardware element: <ul style="list-style-type: none"> • 0: unequipped • 1: chassis
chasCfgType	1.3.6.1.4.1.10734.3.3.2.3.2.1.4	The chassis configuration: <ul style="list-style-type: none"> • 0: unconfigured • 1: simplex • 2: duplex • 3: load share • 4: autonomous

Table A-71 Chassis data objects

Object	OID	Description
chasRunState	1.3.6.1.4.1.10734.3.3.2.3.2.1.5	The high-level hardware state of the chassis: <ul style="list-style-type: none"> • 0: out of service • 1: initializing • 2: active • 3: standby • 4: diagnostic • 5: loopback • 6: active-FAF • 7: standby-FAF • 8: active - degraded • 9: standby - degraded
chasQualifier1	1.3.6.1.4.1.10734.3.3.2.3.2.1.6	Further qualification/detail on the high-level hardware state. <ul style="list-style-type: none"> • 1: degraded • 13: yellow alarm • 14: red alarm • 25: high temperature alarm
chasQualifier2	1.3.6.1.4.1.10734.3.3.2.3.2.1.7	
chasQualifier3	1.3.6.1.4.1.10734.3.3.2.3.2.1.8	
chasQualifier4	1.3.6.1.4.1.10734.3.3.2.3.2.1.9	
chasStartTime	1.3.6.1.4.1.10734.3.3.2.3.2.1.10	The time at which the chassis was powered up.
chasVendorID	1.3.6.1.4.1.10734.3.3.2.3.2.1.11	The identifying number of the chassis vendor.
chasDeviceID	1.3.6.1.4.1.10734.3.3.2.3.2.1.12	An identifying number specific to the chassis.
chasProductID	1.3.6.1.4.1.10734.3.3.2.3.2.1.13	Version and other inventory information.
chasFPGAVersion	1.3.6.1.4.1.10734.3.3.2.3.2.1.14	The version of the TippingPoint FPGA chip on the chassis.

Fans

The following objects provide information about the fan hardware. For fan health, see “[Fans](#)” on page 13.

Table A-72 Fan objects

Object	OID	Description
hw-fanTable	1.3.6.1.4.1.10734.3.3.2.3.3	Table of fan data for the device. Represented as a table with one row.
hw-fanEntry	1.3.6.1.4.1.10734.3.3.2.3.3.1	An entry in the fan table.
fanSubunit	1.3.6.1.4.1.10734.3.3.2.3.3.1.1	The number for this entry in the fan table. The controller is always zero (0).

Table A-72 Fan objects

Object	OID	Description
fanType	1.3.6.1.4.1.10734.3.3.2.3.3.1.3	Type of hardware element: <ul style="list-style-type: none"> • 0: unequipped • 19: fan controller • 20: fan subunit
fanCfgType	1.3.6.1.4.1.10734.3.3.2.3.3.1.4	The fan configuration: <ul style="list-style-type: none"> • 0: unconfigured • 1: simplex • 2: duplex • 3: load share • 4: autonomous
fanRunState	1.3.6.1.4.1.10734.3.3.2.3.3.1.5	The high-level hardware state of the fan: <ul style="list-style-type: none"> • 0: out of service • 1: initializing • 2: active • 3: standby • 4: diagnostic • 5: loopback • 6: active-FAF • 7: standby-FAF • 8: active - degraded • 9: standby - degraded
fanQualifier1	1.3.6.1.4.1.10734.3.3.2.3.3.1.6	Further qualification/detail on the high-level hardware state. <ul style="list-style-type: none"> • 1: degraded • 13: yellow alarm • 14: red alarm
fanQualifier2	1.3.6.1.4.1.10734.3.3.2.3.3.1.7	
fanQualifier3	1.3.6.1.4.1.10734.3.3.2.3.3.1.8	
fanQualifier4	1.3.6.1.4.1.10734.3.3.2.3.3.1.9	
fanStartTime	1.3.6.1.4.1.10734.3.3.2.3.3.1.10	The time at which the fan was powered up.
fanVendorID	1.3.6.1.4.1.10734.3.3.2.3.3.1.11	The identifying number of the fan vendor.
fanDeviceID	1.3.6.1.4.1.10734.3.3.2.3.3.1.12	An identifying number specific to the fan.
fanProductID	1.3.6.1.4.1.10734.3.3.2.3.3.1.13	Versions and other inventory information.
fanFPGAVersion	1.3.6.1.4.1.10734.3.3.2.3.3.1.14	The version of the TippingPoint FPGA chip on the fan.

Power Supply

The following objects provide information about the power supply hardware.

Table A-73 Power supply objects

Object	OID	Description
hw-psTable	1.3.6.1.4.1.10734.3.3.2.3.4	Table of power supply data for the device. Represented as a table with one row.
hw-psEntry	1.3.6.1.4.1.10734.3.3.2.3.4.1	An entry in the power supply table.
psSubunit	1.3.6.1.4.1.10734.3.3.2.3.4.1.1	The number for this entry in the power supply table. This number is always zero (0).
psType	1.3.6.1.4.1.10734.3.3.2.3.4.1.3	Type of hardware element: 0: unequipped 17: power supply 18: power supply sub-unit
psCfgType	1.3.6.1.4.1.10734.3.3.2.3.4.1.4	The power supply configuration: <ul style="list-style-type: none"> 0: unconfigured 1: simplex 2: duplex 3: load share 4: autonomous
psRunState	1.3.6.1.4.1.10734.3.3.2.3.4.1.5	The high-level hardware state of the power supply: <ul style="list-style-type: none"> 0: out of service 1: initializing 2: active 3: standby 4: diagnostic 5: loopback 6: active-FAF 7: standby-FAF 8: active - degraded 9: standby - degraded
psQualifier1	1.3.6.1.4.1.10734.3.3.2.3.4.1.6	Further qualification/detail on the high-level hardware state. <ul style="list-style-type: none"> 1: degraded 13: yellow alarm 14: red alarm
psQualifier2	1.3.6.1.4.1.10734.3.3.2.3.4.1.7	
psQualifier3	1.3.6.1.4.1.10734.3.3.2.3.4.1.8	
psQualifier4	1.3.6.1.4.1.10734.3.3.2.3.4.1.9	
psStartTime	1.3.6.1.4.1.10734.3.3.2.3.4.1.10	The time at which the power supply was powered up.
psVendorID	1.3.6.1.4.1.10734.3.3.2.3.4.1.11	The identifying number of the power supply vendor.

Table A-73 Power supply objects

Object	OID	Description
psDeviceID	1.3.6.1.4.1.10734.3.3.2.3.4.1.12	An identifying number specific to the power supply.
psProductID	1.3.6.1.4.1.10734.3.3.2.3.4.1.13	Versions and other inventory information.
psFPGAVersion	1.3.6.1.4.1.10734.3.3.2.3.4.1.14	The version of the TippingPoint FPGA chip on the power supply.

Power Entry Modules

The following objects provide information about power entry modules.

Table A-74 Power entry objects

Object	OID	Description
hw-pemTable	1.3.6.1.4.1.10734.3.3.2.3.5	Table of power entry module data for the device. Represented as a table with one row.
hw-pemEntry	1.3.6.1.4.1.10734.3.3.2.3.5.1	An entry in the power entry module table.
pemSubunit	1.3.6.1.4.1.10734.3.3.2.3.5.1.1	The number for this entry in the power entry module table. This number is always zero (0).
pemType	1.3.6.1.4.1.10734.3.3.2.3.5.1.3	Type of hardware element: 0: unequipped 21: power entry module
pemCfgType	1.3.6.1.4.1.10734.3.3.2.3.5.1.4	The power entry module configuration: <ul style="list-style-type: none"> • 0: unconfigured • 1: simplex • 2: duplex • 3: load share • 4: autonomous
pemRunState	1.3.6.1.4.1.10734.3.3.2.3.5.1.5	The high-level hardware state of the power entry module: <ul style="list-style-type: none"> • 0: out of service • 1: initializing • 2: active • 3: standby • 4: diagnostic • 5: loopback • 6: active-FAF • 7: standby-FAF • 8: active - degraded • 9: standby - degraded

Table A-74 Power entry objects

Object	OID	Description
pemQualifier1	1.3.6.1.4.1.10734.3.3.2.3.5.1.6	Further qualification/detail on the high-level hardware state. <ul style="list-style-type: none"> • 1: degraded • 13: yellow alarm • 14: red alarm
pemQualifier2	1.3.6.1.4.1.10734.3.3.2.3.5.1.7	
pemQualifier3	1.3.6.1.4.1.10734.3.3.2.3.5.1.8	
pemQualifier4	1.3.6.1.4.1.10734.3.3.2.3.5.1.9	
pemStartTime	1.3.6.1.4.1.10734.3.3.2.3.5.1.10	The time at which the power entry module was powered up.
pemVendorID	1.3.6.1.4.1.10734.3.3.2.3.5.1.11	The identifying number of the power entry module vendor.
pemDeviceID	1.3.6.1.4.1.10734.3.3.2.3.5.1.12	An identifying number specific to the power entry module.
pemProductID	1.3.6.1.4.1.10734.3.3.2.3.5.1.13	Versions and other inventory information.
pemFPGAVersion	1.3.6.1.4.1.10734.3.3.2.3.5.1.14	The version of the TippingPoint FPGA chip on the power entry module.

TPT-TPAMIBS

Defines the MIB sub-trees.

Table A-75 TPA top level MIBs

Object	OID	Description
tpt-tpa-conf	1.3.6.1.4.1.10734.3.3.1	Conformance objects sub-tree.
tpt-tpa-objs	1.3.6.1.4.1.10734.3.3.2	Managed objects sub-tree.
tpt-tpa-events	1.3.6.1.4.1.10734.3.3.3	Events sub-tree that includes all payload variables needed for notifications.

Table A-76 Conformance top level MIBs

Object	OID	Description
tpt-tpa-groups	1.3.6.1.4.1.10734.3.3.1.1	Groups sub-tree
tpt-tpa-compls	1.3.6.1.4.1.10734.3.3.1.2	Compliance MIBs sub-tree

Table A-77 Notification top level MIBs

Object	OID	Description
tpt-tpa-eventsV2	1.3.6.1.4.1.10734.3.3.3.0	Notification MIBs sub-tree.
tpt-tpa-unkparams	1.3.6.1.4.1.10734.3.3.3.1	Sub-tree for all MIB variables sent as part of a notification payload.

Table A-78 Model Numbers

Object	OID	Description
tpt-tpa-family	1.3.6.1.4.1.10734.1.3	Common grouping for TippingPoint network security devices.
tpt-model-10	1.3.6.1.4.1.10734.1.3.11	Registration for the TippingPoint 10
tpt-model-660N	1.3.6.1.4.1.10734.1.3.27	Registration for the TippingPoint 660N
tpt-model-1400N	1.3.6.1.4.1.10734.1.3.28	Registration for the TippingPoint 1400N
tpt-model-2500N	1.3.6.1.4.1.10734.1.3.29	Registration for the TippingPoint 2500N
tpt-model-5100N	1.3.6.1.4.1.10734.1.3.30	Registration for the TippingPoint 5100N
tpt-model-110	1.3.6.1.4.1.10734.1.3.31	Registration for the TippingPoint 110.
tpt-model-330	1.3.6.1.4.1.10734.1.3.32	Registration for the TippingPoint 330.
tpt-model-6100N	1.3.6.1.4.1.10734.1.3.34	Registration for the TippingPoint 6100N

NOTE: The MIB file lists many model numbers, but only the N-Platform and 10, 110, and 330 model numbers are documented here.

TPT-TRAFFIC

The TPT-TRAFFIC MIB defines traffic rate-limiting information.

NOTE: The MIB file includes traffic threshold information. This feature is not currently supported in the TippingPoint N-Platform.

Notifications

The following notifications send information to the management system when traffic thresholds are crossed and logged.

Table A-79 Temperature objects

Object	OID	Description
tptThresholdNotifyDeviceID	1.3.6.1.4.1.10734.3.3.3.1.111	The unique identifier of the device sending the threshold notification.
tptThresholdNotifyPolicyID	1.3.6.1.4.1.10734.3.3.3.1.112	The unique identifier of the policy that initiates the notification.
tptThresholdNotifySignatureID	1.3.6.1.4.1.10734.3.3.3.1.113	The unique identifier of the signature associated with the policy.

Table A-79 Temperature objects

Object	OID	Description
tpfThresholdNotifySegmentName	1.3.6.1.4.1.10734.3.3.3.1.114	The segment to which the notification refers.
tpfThresholdNotifyZonePair	1.3.6.1.4.1.10734.3.3.3.1.115	The virtual segment to which the notification refers.
tpfThresholdFilterNotify	1.3.6.1.4.1.10734.3.3.3.0.17	Informs the management station that a traffic threshold filter has been crossed and the crossing logged.

Rate Limiter

The following objects provide rate limit statistics.

Table A-80 Rate Limiter objects

Object	OID	Description
rateLimitTable	1.3.6.1.4.1.10734.3.3.2.8.1	A table providing data about an rate limit action set.
rateLimitEntry	1.3.6.1.4.1.10734.3.3.2.8.1.1	An entry in the rate limit table. Rows cannot be added or deleted.
rateLimitGlobalID	1.3.6.1.4.1.10734.3.3.2.8.1.1.1	The global ID of a rate limit action set.
rateLimitRequestedRate	1.3.6.1.4.1.10734.3.3.2.8.1.1.2	The bit rate in Kbps defined by the action set creator.
rateLimitActualRate	1.3.6.1.4.1.10734.3.3.2.8.1.1.3	The bit rate in Kbps defined at the hardware level.
rateLimitPacketsSent	1.3.6.1.4.1.10734.3.3.2.8.1.1.4	The number of packets sent via this action set since the table was last cleared.
rateLimitPacketsDropped	1.3.6.1.4.1.10734.3.3.2.8.1.1.5	The number of packets dropped by this action set since the table was last cleared.
rateLimitPacketsQueued	1.3.6.1.4.1.10734.3.3.2.8.1.1.6	The number of packets queued and ready to be sent via this action set.
rateLimitHistNumSeconds	1.3.6.1.4.1.10734.3.3.2.8.1.1.7	The number of seconds of valid historical sample data available.
rateLimitHistNumMinutes	1.3.6.1.4.1.10734.3.3.2.8.1.1.8	The number of minutes of valid historical sample data available.
rateLimitHistNumHours	1.3.6.1.4.1.10734.3.3.2.8.1.1.9	The number of hours of valid historical sample data available.
rateLimitHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.8.2	Historical sample data as recorded every second for a minute.
rateLimitHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.8.2.1	An entry in the rate limit history seconds table.

Table A-80 Rate Limiter objects

Object	OID	Description
rateLimitHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.8.2.1.1	The global ID of a rate limit action set.
rateLimitHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.8.2.1.2	The index (0-59) of a second.
rateLimitHistSecondsBytesSent	1.3.6.1.4.1.10734.3.3.2.8.2.1.3	The number of bytes sent in the specified second.
rateLimitHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.8.2.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.
rateLimitHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.8.3	Historical sample data as recorded every minute for an hour.
rateLimitHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.8.3.1	An entry in the rate limit history minutes table.
rateLimitHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.8.3.1.1	The global ID of a rate limit action set.
rateLimitHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.8.3.1.2	The index (0-59) of a minute.
rateLimitHistMinutesBytesSent	1.3.6.1.4.1.10734.3.3.2.8.3.1.3	The number of bytes sent in the specified minute.
rateLimitHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.8.3.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.
rateLimitHistHoursTable	1.3.6.1.4.1.10734.3.3.2.8.4	Historical sample data as recorded every hour for a day.
rateLimitHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.8.4.1	An entry in the rate limit history hours table.
rateLimitHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.8.4.1.1	The global ID of a rate limit action set.
rateLimitHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.8.4.1.2	The index (0-23) of an hour.
rateLimitHistHoursBytesSent	1.3.6.1.4.1.10734.3.3.2.8.4.1.3	The number of bytes sent in the specified hour.
rateLimitHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.8.4.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.

Traffic Threshold

The following objects provide traffic threshold statistics.

Table A-81 Traffic threshold objects

Object	OID	Description
thresholdTable	1.3.6.1.4.1.10734.3.3.2.8.9	A table providing data about a traffic threshold filter.
thresholdEntry	1.3.6.1.4.1.10734.3.3.2.8.9.1	An entry in the traffic threshold filter list. Rows cannot be added or deleted

Table A-81 Traffic threshold objects

Object	OID	Description
thresholdGlobalID	1.3.6.1.4.1.10734.3.3.2.8.9.1.1	The global identifier of a traffic threshold filter.
thresholdState	1.3.6.1.4.1.10734.3.3.2.8.9.1.2	The state of this filter: <ul style="list-style-type: none"> • Green: operating normally • Yellow: warning • Red: critical
thresholdUnits	1.3.6.1.4.1.10734.3.3.2.8.9.1.3	The units monitored by this threshold filter, such as packets per second.
thresholdHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.8.5	Historical sample data as recorded every second for a minute.
thresholdHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.8.5.1	An entry in the traffic threshold history seconds table.
thresholdHistSecondsGlobalID	1.3.6.1.4.1.10734.3.3.2.8.5.1.1	The global ID of a traffic threshold filter.
thresholdHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.8.5.1.2	The index (0-59) of a second.
thresholdHistSecondsUnitCount	1.3.6.1.4.1.10734.3.3.2.8.5.1.3	The number of filter-specific units matching the traffic criteria for this filter in the specified second.
thresholdHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.8.5.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.
thresholdHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.8.6	Historical sample data as recorded every minute for an hour.
thresholdHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.8.6.1	An entry in the traffic threshold history minutes table.
thresholdHistMinutesGlobalID	1.3.6.1.4.1.10734.3.3.2.8.6.1.1	The global ID of a traffic threshold filter.
thresholdHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.8.6.1.2	The index (0-59) of a minute.
thresholdHistMinutesUnitCount	1.3.6.1.4.1.10734.3.3.2.8.6.1.3	The average of thresholdSecondsUnitCount values corresponding to this minute.
thresholdHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.8.6.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.
thresholdHistHoursTable	1.3.6.1.4.1.10734.3.3.2.8.7	Historical sample data as recorded every hour for a day.
thresholdHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.8.7.1	An entry in the traffic threshold history hours table.
thresholdHistHoursGlobalID	1.3.6.1.4.1.10734.3.3.2.8.7.1.1	The global ID of a traffic threshold filter.

Table A-81 Traffic threshold objects

Object	OID	Description
thresholdHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.8.7.1.2	The index (0-23) of an hour.
thresholdHistHoursUnitCount	1.3.6.1.4.1.10734.3.3.2.8.7.1.3	The average of thresholdMinutesUnitCount values corresponding to this hour.
thresholdHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.8.7.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.
thresholdHistDaysTable	1.3.6.1.4.1.10734.3.3.2.8.8	Historical sample data as recorded every hour for a day.
thresholdHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.8.8.1	An entry in the traffic threshold history Days table.
thresholdHistDaysGlobalID	1.3.6.1.4.1.10734.3.3.2.8.8.1.1	The global ID of a traffic threshold filter.
thresholdHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.8.8.1.2	The index (0-34) of the day.
thresholdHistDaysUnitCount	1.3.6.1.4.1.10734.3.3.2.8.8.1.3	The average of thresholdHourssUnitCount values corresponding to this day.
thresholdHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.8.8.1.4	The time that this statistic was updated, measured in seconds since January 1, 1970.

Interface Traffic History

The following objects provide historical data about traffic across device interfaces.

Table A-82 Temperature objects

Object	OID	Description
interfaceHistSecondsTable	1.3.6.1.4.1.10734.3.3.2.8.10	Historical sample data as recorded every second for a minute.
interfaceHistSecondsEntry	1.3.6.1.4.1.10734.3.3.2.8.10.1	An entry in the interface history seconds table.
interfaceHistSecondsIfIndex	1.3.6.1.4.1.10734.3.3.2.8.10.1.1	The ifIndex of the interface.
interfaceHistSecondsIndex	1.3.6.1.4.1.10734.3.3.2.8.10.1.2	The index (0-59) of a second.
interfaceHistSecondsUnitCountIn	1.3.6.1.4.1.10734.3.3.2.8.10.1.3	The incoming traffic on the interface port in octets during the specified second.
interfaceHistSecondsUnitCountOut	1.3.6.1.4.1.10734.3.3.2.8.10.1.4	The outgoing traffic on the interface port in octets in the specified second.
interfaceHistSecondsTimestamp	1.3.6.1.4.1.10734.3.3.2.8.10.1.5	The time that this statistic was updated, measured in seconds since January 1, 1970.
interfaceHistMinutesTable	1.3.6.1.4.1.10734.3.3.2.8.11	Historical sample data as recorded every minute for an hour.

Table A-82 Temperature objects

Object	OID	Description
interfaceHistMinutesEntry	1.3.6.1.4.1.10734.3.3.2.8.11.1	An entry in the interface history minutes table.
interfaceHistMinutesIfIndex	1.3.6.1.4.1.10734.3.3.2.8.11.1.1	The ifIndex of the interface.
interfaceHistMinutesIndex	1.3.6.1.4.1.10734.3.3.2.8.11.1.2	The index (0-59) of a minute.
interfaceHistMinutesUnitCountIn	1.3.6.1.4.1.10734.3.3.2.8.11.1.3	The average of SecondsUnitCountIn values corresponding to this minute.
interfaceHistMinutesUnitCountOut	1.3.6.1.4.1.10734.3.3.2.8.11.1.4	The average of SecondsUnitCountOut values corresponding to this minute.
interfaceHistMinutesTimestamp	1.3.6.1.4.1.10734.3.3.2.8.11.1.5	The time that this statistic was updated, measured in seconds since January 1, 1970.
interfaceHistHoursTable	1.3.6.1.4.1.10734.3.3.2.8.12	Historical sample data as recorded every hour for a day.
interfaceHistHoursEntry	1.3.6.1.4.1.10734.3.3.2.8.12.1	An entry in the interface history hours table.
interfaceHistHoursIfIndex	1.3.6.1.4.1.10734.3.3.2.8.12.1.1	The ifIndex of the interface.
interfaceHistHoursIndex	1.3.6.1.4.1.10734.3.3.2.8.12.1.2	The index (0-23) of an hour.
interfaceHistHoursUnitCountIn	1.3.6.1.4.1.10734.3.3.2.8.12.1.3	The average of MinutesUnitCountIn values corresponding to this hour.
interfaceHistHoursUnitCountOut	1.3.6.1.4.1.10734.3.3.2.8.12.1.4	The average of MinutesUnitCountOut values corresponding to this hour.
interfaceHistHoursTimestamp	1.3.6.1.4.1.10734.3.3.2.8.12.1.5	The time that this statistic was updated, measured in seconds since January 1, 1970.
interfaceHistDaysTable	1.3.6.1.4.1.10734.3.3.2.8.13	Historical sample data as recorded every hour for a day.
interfaceHistDaysEntry	1.3.6.1.4.1.10734.3.3.2.8.13.1	An entry in the interface history Days table.
interfaceHistDaysIfIndex	1.3.6.1.4.1.10734.3.3.2.8.13.1.1	The ifIndex of the interface.
interfaceHistDaysIndex	1.3.6.1.4.1.10734.3.3.2.8.13.1.2	The index (0-34) of the day.
interfaceHistDaysUnitCountIn	1.3.6.1.4.1.10734.3.3.2.8.13.1.3	The average of HoursUnitCountIn values corresponding to this day.
interfaceHistDaysUnitCountOut	1.3.6.1.4.1.10734.3.3.2.8.13.1.4	The average of HoursUnitCountOut values corresponding to this day.
interfaceHistDaysTimestamp	1.3.6.1.4.1.10734.3.3.2.8.13.1.5	The time that this statistic was updated, measured in seconds since January 1, 1970.

TPT-TSE

Defines TSE settings, including adaptive filtering.

Adaptive Filter Configuration

The following table lists the top ten filters in the Adaptive Filter Configuration list.

Table A-83 Adaptive Filter Configuration objects

Object	OID	Description
topTenAdaptFilterTable	1.3.6.1.4.1.10734.3.3.2.7.1	Adaptive filter configuration top ten list.
topTenAdaptFilterEntry	1.3.6.1.4.1.10734.3.3.2.7.1.1	An entry in the adaptive filter configuration top ten list. Rows cannot be added or deleted.
topTenAdaptFilterRank	1.3.6.1.4.1.10734.3.3.2.7.1.1.1	The numerical ranking of a filter in the adaptive filter top ten list.
adaptFilterName	1.3.6.1.4.1.10734.3.3.2.7.1.1.2	The name of the filter.
adaptFilterUUID	1.3.6.1.4.1.10734.3.3.2.7.1.1.3	The global identifier of the filter.
adaptFilterSegment	1.3.6.1.4.1.10734.3.3.2.7.1.1.4	The segment to which the filter applies.
adaptFilterEnabledState	1.3.6.1.4.1.10734.3.3.2.7.1.1.5	The state of the filter.
adaptFilterCfgState	1.3.6.1.4.1.10734.3.3.2.7.1.1.6	Whether adaptive filter configuration is enabled for the filter.
adaptFilterSigID	1.3.6.1.4.1.10734.3.3.2.7.1.1.7	The global identifier of a signature.
adaptFilterProfile	1.3.6.1.4.1.10734.3.3.2.7.1.1.8	The name of the profile associated with the filter.

Connection Blocks Table

The following table lists all connection blocks.

Table A-84 Connection blocks table objects

Object	OID	Description
connectionBlockTable	1.3.6.1.4.1.10734.3.3.2.7.2	Table of connections that correspond to blocked streams.
connectionBlockEntry	1.3.6.1.4.1.10734.3.3.2.7.2.1	An entry in the connection block table. Rows cannot be added or deleted.
connectionBlockIndex	1.3.6.1.4.1.10734.3.3.2.7.2.1.1	The index number of the entry in the connection block table.
connectionBlockSrcAddr	1.3.6.1.4.1.10734.3.3.2.7.2.1.2	The source IPv4 address of a blocked connection.
connectionBlockSrcAddrV6	1.3.6.1.4.1.10734.3.3.2.7.2.1.9	The source IPv6 address of a blocked connection.
connectionBlockSrcPort	1.3.6.1.4.1.10734.3.3.2.7.2.1.3	The source port of a blocked connection.

Table A-84 Connection blocks table objects

Object	OID	Description
connectionBlockDestAddr	1.3.6.1.4.1.10734.3.3.2.7.2.1.4	The destination IPv4 address of a blocked connection.
connectionBlockDestAddrV6	1.3.6.1.4.1.10734.3.3.2.7.2.1.10	The destination IPv6 address of a blocked connection.
connectionBlockDestPort	1.3.6.1.4.1.10734.3.3.2.7.2.1.5	The destination port of a blocked connection.
connectionBlockProtocol	1.3.6.1.4.1.10734.3.3.2.7.2.1.6	The transmission protocol of a blocked connection. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
connectionBlockPort	1.3.6.1.4.1.10734.3.3.2.7.2.1.7	The segment on which the incoming data caused the connection to be blocked.
connectionBlockReason	1.3.6.1.4.1.10734.3.3.2.7.2.1.8	The UUID of the signature that caused the block.
connectionBlockTotalCount	1.3.6.1.4.1.10734.3.3.2.7.3	The total number of connections corresponding to blocked streams. Only the first 50 are included in the connection block table.

Rate Limit Streams Table

The following table lists connections that have been rate limited.

Table A-85 Rate limit streams table objects

Object	OID	Description
rateLimitStreamTable	1.3.6.1.4.1.10734.3.3.2.7.4	Table of connections that correspond to rate limited streams.
rateLimitStreamEntry	1.3.6.1.4.1.10734.3.3.2.7.4.1	An entry in the rate limited stream table. Rows cannot be added or deleted.
rateLimitStreamIndex	1.3.6.1.4.1.10734.3.3.2.7.4.1.1	The index number of the entry in the rate limited stream table.
rateLimitStreamSrcAddr	1.3.6.1.4.1.10734.3.3.2.7.4.1.2	The source IPv4 address of a rate limited stream.
rateLimitStreamSrcAddrV6	1.3.6.1.4.1.10734.3.3.2.7.4.1.9	The source IPv6 address of a rate limited stream.

Table A-85 Rate limit streams table objects

Object	OID	Description
rateLimitStreamSrcPort	1.3.6.1.4.1.10734.3.3.2.7.4.1.3	The source port of a rate limited stream.
rateLimitStreamDestAddr	1.3.6.1.4.1.10734.3.3.2.7.4.1.4	The destination IPv4 address of a rate limited stream.
rateLimitStreamDestAddrV6	1.3.6.1.4.1.10734.3.3.2.7.4.1.10	The destination IPv6 address of a rate limited stream.
rateLimitStreamDestPort	1.3.6.1.4.1.10734.3.3.2.7.4.1.5	The destination port of a rate limited stream.
rateLimitStreamProtocol	1.3.6.1.4.1.10734.3.3.2.7.4.1.6	The protocol of a rate limited stream. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
rateLimitStreamPort	1.3.6.1.4.1.10734.3.3.2.7.4.1.7	The segment on which the incoming data caused the connection to be rate limited.
rateLimitStreamReason	1.3.6.1.4.1.10734.3.3.2.7.4.1.8	The UUID of the signature that caused the rate limit.
rateLimitStreamTotalCount	1.3.6.1.4.1.10734.3.3.2.7.5	The total number of connections corresponding to rate limited streams. Only the first 50 are included in the rate limited stream table.

Connection Trusts Table

The following table lists trusted connections.

Table A-86 Connection Trusts table objects

Object	OID	Description
connectionTrustTable	1.3.6.1.4.1.10734.3.3.2.7.2	Table of connections that correspond to trusted streams.
connectionTrustEntry	1.3.6.1.4.1.10734.3.3.2.7.2.1	An entry in the connection trust table. Rows cannot be added or deleted.
connectionTrustIndex	1.3.6.1.4.1.10734.3.3.2.7.2.1.1	The index number of the entry in the connection trust table.
connectionTrustSrcAddr	1.3.6.1.4.1.10734.3.3.2.7.2.1.2	The source IPv4 address of a trusted connection.
connectionTrustSrcAddrV6	1.3.6.1.4.1.10734.3.3.2.7.2.1.9	The source IPv6 address of a trusted connection.

Table A-86 Connection Trusts table objects

Object	OID	Description
connectionTrustSrcPort	1.3.6.1.4.1.10734.3.3.2.7.2.1.3	The source port of a trusted connection.
connectionTrustDestAddr	1.3.6.1.4.1.10734.3.3.2.7.2.1.4	The destination IPv4 address of a trusted connection.
connectionTrustDestAddrV6	1.3.6.1.4.1.10734.3.3.2.7.2.1.10	The destination IPv6 address of a trusted connection.
connectionTrustDestPort	1.3.6.1.4.1.10734.3.3.2.7.2.1.5	The destination port of a trusted connection.
connectionTrustProtocol	1.3.6.1.4.1.10734.3.3.2.7.2.1.6	The protocol of a trusted connection. <ul style="list-style-type: none"> • 1: ICMP • 2: UDP • 3: TCP • 4: other IP • 5: ARP • 6: other ETH • 7: ICMP v6 • 8: other IPV6
connectionTrustPort	1.3.6.1.4.1.10734.3.3.2.7.2.1.7	The segment on which the incoming data caused the connection to be trusted.
connectionTrustReason	1.3.6.1.4.1.10734.3.3.2.7.2.1.8	The UUID of the signature that caused the trust.
connectionTrustTotalCount	1.3.6.1.4.1.10734.3.3.2.7.3	The total number of connections corresponding to trusted streams. Only the first 50 are included in the connection trust table.

Using HP OpenView With IPS MIBs

HP OpenView is a well-known commercial network management system. Much of this information can be transposed onto other network management systems.

This section focuses on adding enterprise MIB monitoring and reporting to HP OpenView. The examples in this section were created on HP OpenView 7.0.1 running on Windows XP Professional Service Pack 1.

NOTE: This book assumes that you have already installed HP OpenView. Refer to the OpenView documentation for more information about that product.

This section includes the following:

- "Loading TippingPoint Enterprise MIBs" on page 68
- "MIB Application Builder" on page 68
- "Discovering the IPS" on page 69
- "Creating Graphs with Application Builder" on page 69

Loading TippingPoint Enterprise MIBs

Before you begin, you must configure OpenView to understand the TippingPoint Enterprise MIBs.

1. In the OpenView Root Map, select the Options menu.
2. Select **Load/Unload MIBs: SNMP**.
3. Load TIPPINGPOINT-REG-MIB.
4. Load the remaining TPT MIBs in any order. OpenView may prompt you when loading the MIBs regarding adding a macro definition. This is normal behavior, and you should accept the MIB.

MIB Application Builder

OpenView includes a tool called MIB Application Builder that allows you to build custom applications that retrieve data using SNMP and to retrieve any information stored in a MIB.

1. Select **Options => MIB Application Builder: SNMP**.
The **MIB Application Builder: SNMP** dialog box displays.
2. Select **Edit => New item**.
The application prompts you with three fields: Application ID, Application Type and Application Title.
 - a. Enter 111 for the **Application ID**.
 - b. Leave the **Application Type** as **Form**.
 - c. Enter an **Application Title**.
3. Select the MIB Objects that have the information that you want to view.
4. Click **Next**.
The **MIB Application Builder / Add MIB Objects** screen displays.
5. In the navigation tree, locate **iso.org.dod.internet.private.enterprises**. You are now at the start of the IPS MIBs.
6. In the tree, select the variables that you want to monitor and click **Add**. Click **Close** to return to the previous screen.
7. Depending on how you added the objects, you may need to reorder them. You can reorder the variables by using the up and down arrows in the **New MIB Application - Display Fields** form.
8. Click **Next** to continue to the **New MIB Application - NMN Integration** dialog screen.
9. Enter **TippingPoint** after **Configuration->**. The line should appear as Configuration->TippingPoint under **Menu Location**. This creates a menu item under the Configuration menu on the main screen.
10. You can select an object on the map. Select **Configuration** from the menu and retrieve the information you created if the device is a TippingPoint device.
11. Close the **MIB Application Builder** dialog box.

Discovering the IPS

By default, OpenView assumes that you would rather automatically discover devices as they arrive on the network. This form of discovery can be a slow process and may not display devices for days (depending on the size of your network). To expedite that process, you use the `loadhosts` command.

1. Open your text editor and create a file named `hosts`.
2. In the file, enter the IP address of your IPS and the hostname. This format is similar to the UNIX `/etc/hosts` file format. For example, you might enter the following information:
3. `192.168.65.20NDS10`
4. Save the file and open a command shell.
5. Run the `loadhosts` command on the file. The command takes the network mask and the file as arguments. For example:

```
LOADHOSTS -M 255.255.255.0 HOSTS
```

After you run the `loadhosts` command, the device is now discovered by OpenView. When you open the Internet icon on your OpenView map, a green square displays. This icon should be your device or devices. Select this icon and choose **Configuration** from the menu bar to view the device.

OpenView has a number of built-in applications that can retrieve data from standard MIBs. For example, when you open the IPS configuration, all of the Ethernet interfaces associated with that device are displayed. When you right-click on the interface and choose **Interface Properties**. Information for that interface is displayed.

Creating Graphs with Application Builder

You can create an application to graph the data with the MIB Application Builder tool.

1. Select the Application Builder from the **Options** menu.
2. Open your existing applications and double-click to edit.
3. Change the **Application Type** from a **Form** to a **Graph**.
4. Set "10" as the **Poll Interval** and "abc" as the **Y-axis** label. You can change these settings to fit your needs.
5. To generate the graph for your device, select the IPS green square. Choose **TippingPoint** from the **Configuration** menu. A graph displays for the device. Allow the graph to run about 30 seconds to begin trending the data.



