

```
#
version 5.20.106, Release 2512P04, Standard
#
sysname RTR
#
clock timezone MU add 04:00:00
#
domain default enable system
#
bridge enable
bridge routing-enable
bridge 1 enable
bridge 1 routing ip
#
dar p2p signature-file cfa0:/p2p_default.mtd
#
port-security enable
#
undo ip http enable
#
password-recovery enable
#
vlan 1
#
domain system
access-limit disable
state active
idle-cut disable
self-service-url disable
#
dhcp server ip-pool vlan11
network xxxxxxxx mask yyyyyyyy
gateway-list qqqqqqqqqq
expired day 0 hour 8
#
dhcp server ip-pool vlan111
network ssssssssssssss mask kkkkkkkkkkkkkk
gateway-list rrrrrrrrrrrrrrrr
#
user-group system
group-attribute allow-guest
#
cwmp
undo cwmp enable
#
interface Aux0
async mode flow
link-protocol ppp
#
interface Cellular0/0
async mode protocol
```

```
link-protocol ppp
#
interface Atm2/0
  shdsl annex a
  shdsl wire 2
  ip virtual-reassembly
#
interface Atm2/0.1 P2P
  bridge-set 1
  pvc 8/35
    encapsulation aal5snap
    map bridge-group broadcast
    map ip default broadcast
#
interface Atm4/0
  shdsl annex a
  shdsl wire 2
  ip virtual-reassembly
#
interface Atm4/0.1 P2P
  bridge-set 1
  pvc 8/35
    encapsulation aal5snap
    map bridge-group broadcast
    map ip default broadcast
#
interface NULL0
#
interface GigabitEthernet0/0
  port link-mode route
  ip address ffffffff nnnnnnnnnnnnnnnnn
#
interface GigabitEthernet0/0.11
  vlan-type dot1q vid 11
  ip address dddddddddd bbbbbbbbbbbbbbbb
  ip count inbound-packets
  ip count outbound-packets
#
interface GigabitEthernet0/0.111
  description --- VOICE
  vlan-type dot1q vid 111
  ip address rrrrrrrrrr hhhhhhhhhhhhhh
#
interface GigabitEthernet0/1
  port link-mode route
#
interface Bridge-templatl
  ip address gggggggg 111111111111
  ospf network-type p2p
#
ospf 999
  area 0.0.0.0
```

```
network aaaaaaaaa cccccc  
network wwwwwwww ffffffff  
network nnnnnnnn eeeeeeee
```

```
#  
subscriber-line5/0  
#  
subscriber-line5/1  
#
```