

Summary

	Controlled APs
Synchronized	32
Detected	32
Configured	34

Network Tree

- Controller
 - VSCs
 - HP ProCurve
 - Prueba Cobertura
 - PruebaVcs2
 - AH WLAN
 - Wireless
 - TRF
 - VOZIP
 - AHGUEST
 - AH
 - TerminalesRadioFrecuencia
 - Prueba**
 - Controlled APs
 - Default Group
 - Prueba
 - San Fernando
 - Mostoles

Wireless clients

Max clients per radio:

Allow traffic between: wireless clients

Client data tunnel

Always tunnel client traffic

Quality of service

Allowed wireless rates

VSC egress mapping

Traffic type	Map to
Unauthenticated:	<input type="text" value="VLAN -> Prueba (123)"/>
Authenticated:	<input type="text" value="VLAN -> Prueba (123)"/>
Intercepted:	<input type="text" value="VLAN -> Prueba (123)"/>

Default user data rates

Max. transmit: kbps

Max. receive: kbps

Wireless security filters

Restrict wireless traffic to this controller

Authentication

Local

Remote

General

RADIUS accounting:

VPN-based authentication

Authentication

Local

Remote

General

RADIUS accounting:

MAC-based authentication

Authentication

Local

Remote

General

RADIUS accounting:

Location-aware